

SeeSnake® Compact C40 Camera System with TruSense (63828)



Specifications

Line Capacity 1.5" to 6" (38mm to 152mm)

Push Cable Length 131' (40m)

Push Cable Diameter 0.26" (6.7 mm) with 3 mm [0.12 in] Fiberglass core

Push Cable Jacket Polypropylene

Push Cable Bend Minimum Radius 2.5" (63.5 mm)

Weight (without batteries) 17.6 lbs. (8.0 kg)

Size Length 25" (63.5 cm)

Width 14" (35.6 cm)

Height 17" (43.2 cm)

Camera Type 1" (25 mm)

Operating Temperature 14°F to 122°F (-10°C to 50°C)

Storage Temperature 14°F to 158°F (-10°C to 70°C)

Ingress Protection without Monitor IPx5

Light Source High-Intensity LED Sonde 512 Hz

Ridgid NaviTrack Scout Locator (19238)



Specifications

Weight 3 lbs (1.4 kg).

Power Source 4 C-Cell batteries or Rechargeable RIDGID® Professional 18V battery with RIDGID® SeekTech® 18V Adaptor (optional).

Battery Life Varies with battery rating, use and operating factors. Four size C, alkaline batteries provide approximately 12 to 24 hours.

STANDARD FREQUENCIES

Sonde 16 Hz, 512 Hz, 640 Hz, 874 kHz and 33 kHz.

Line Trace 128 Hz, 1 kHz, 8 kHz and 33 kHz.

Passive AC Line Trace 60 Hz, 50 Hz.

Meets FCC Class B and EN 55022 Class B requirements.