

# Cherokee Nation

# Durbin Feeling Language Center

## Renovation

### Project Manual

### Construction Documents

February 4, 2026



**Owner:**

The Cherokee Nation  
P.O. Box 948  
Tahlequah, OK 74465



**Architect:**

Blue River Architects, LLC  
21 N. Greenwood Ave, STE 201  
Tulsa, OK 74120  
Phone: 918.877.9036





**SECTION 00 0110**  
**TABLE OF CONTENTS**

**PROCUREMENT AND CONTRACTING REQUIREMENTS**

**DIVISION 00 -- PROCUREMENT AND CONTRACTING REQUIREMENTS**

00 0110 - Table of Contents

**SPECIFICATIONS**

**DIVISION 01 -- GENERAL REQUIREMENTS**

01 1000 - Summary  
01 2000 - Price and Payment Procedures  
01 2100 - Allowances  
01 2300 - Alternates  
01 2500 - Substitution Procedures  
01 3000 - Administrative Requirements  
01 4000 - Quality Requirements  
01 5000 - Temporary Facilities and Controls  
01 6000 - Product Requirements  
01 7000 - Execution and Closeout Requirements  
01 7800 - Closeout Submittals

**DIVISION 02 -- EXISTING CONDITIONS**

02 4100 - Demolition

**DIVISION 06 -- WOOD, PLASTICS, AND COMPOSITES**

06 1000 - Rough Carpentry  
06 4100 - Architectural Wood Casework  
06 8316 - Fiberglass Reinforced Paneling

**DIVISION 07 -- THERMAL AND MOISTURE PROTECTION**

07 7200 - Roof Accessories  
07 9200 - Joint Sealants

**DIVISION 08 -- OPENINGS**

08 1113 - Hollow Metal Doors and Frames  
08 4313 - Aluminum-Framed Storefronts  
08 7100 - Door Hardware  
08 8000 - Glazing

**DIVISION 09 -- FINISHES**

09 0561 - Common Work Results for Flooring Preparation  
09 2116 - Gypsum Board Assemblies  
09 3000 - Tiling  
09 5100 - Acoustical Ceilings  
09 6500 - Resilient Flooring  
09 9123 - Interior Painting

**DIVISION 10 -- SPECIALTIES**

10 2113.19 - Plastic Toilet Compartments

## 10 2800 - Toilet, Bath, and Laundry Accessories

## SECTION 01 1000 SUMMARY

### PART 1 GENERAL

#### 1.01 PROJECT

- A. Project Name: Durbin Feeling Language Center Renovation
- B. Owner's Name: The Cherokee Nation of Oklahoma.
- C. Architect's Name: Blue River Architects, LLC.
- D. The Project consists of the alteration of an school building.

#### 1.02 CONTRACT DESCRIPTION

- A. Contract Type: Refer to bidding information for Cherokee Nation

#### 1.03 WORK BY OWNER

- A. Items noted NIC (Not in Contract) will be supplied and installed by Owner after Date of Substantial Completion. Some items include:
  - 1. Movable cabinets.
  - 2. Furnishings.
  - 3. Small equipment.
  - 4. Rugs.
  - 5. Artwork.
- B. It is the responsibility of the Contractor to coordinate all NIC and/or Owner-furnished items with Owner. Contractor is responsible for rough-in power and backing requirements.
- B. Owner will supply and install the following:
- C. Owner will supply the following for installation by Contractor:

#### 1.04 OWNER OCCUPANCY

- A. Owner intends to occupy the Project by the date stated in the Agreement as the contract completion date.
- B. Cooperate with Owner to minimize conflict and to facilitate Owner's operations.
- C. Schedule the Work to accommodate Owner occupancy.

#### 1.05 CONTRACTOR USE OF SITE AND PREMISES

- A. Construction Operations: Limited to areas noted on Drawings.
  - 1. Locate and conduct construction activities in ways that will limit disturbance to site.
- B. Arrange use of site and premises to allow:
  - 1. Work by Others.
  - 2. Work by Owner.
- C. Provide access to and from site as required by law and by Owner:
  - 1. Do not obstruct roadways, sidewalks, or other public ways without permit.
- D. Time Restrictions:
  - 1. Limit conduct of work to the hours of 4pm to 10pm, weekends, and/or when school is not in session.
  - 2. As requested by Owner.

### PART 2 PRODUCTS - NOT USED

### PART 3 EXECUTION - NOT USED

END OF SECTION 01 1000

This page intentionally left blank

**SECTION 01 2000**  
**PRICE AND PAYMENT PROCEDURES**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Procedures for preparation and submittal of applications for progress payments.
- B. Documentation of changes in Contract Sum and Contract Time.
- C. Change procedures.
- D. Correlation of Contractor submittals based on changes.
- E. Procedures for preparation and submittal of application for final payment.

**1.02 RELATED REQUIREMENTS**

- A. Section 01 7800 - Closeout Submittals: Project record documents.

**1.03 SCHEDULE OF VALUES**

- A. Electronic media printout including equivalent information will be considered in lieu of standard form specified; submit draft to Architect for approval.
- B. Forms filled out by hand will not be accepted.
- C. Format: Utilize the Table of Contents of this Project Manual. Identify each line item with number and title of the specification section.
- D. Include in each line item, the amount of Allowances specified in this section. For unit cost Allowances, identify quantities taken from Contract Documents multiplied by the unit cost to achieve the total for the item.
- E. Include separately from each line item, a direct proportional amount of Contractor's overhead and profit.
- F. Revise schedule to list approved Change Orders, with each Application For Payment.

**1.04 APPLICATIONS FOR PROGRESS PAYMENTS**

- A. Payment Period: Submit at intervals stipulated in the Agreement.
- B. Electronic media printout including equivalent information will be considered in lieu of standard form specified; submit sample to Architect for approval.
- C. Forms filled out by hand will not be accepted.
- D. For each item, provide a column for listing each of the following:
  1. Item Number.
  2. Description of work.
  3. Scheduled Values.
  4. Previous Applications.
  5. Work in Place and Stored Materials under this Application.
  6. Authorized Change Orders.
  7. Total Completed and Stored to Date of Application.
  8. Percentage of Completion.
  9. Balance to Finish.
  10. Retainage.
- E. Execute certification by signature of authorized officer.
- F. Use data from approved Schedule of Values. Provide dollar value in each column for each line item for portion of work performed and for stored products.
- G. List each authorized Change Order as a separate line item, listing Change Order number and dollar amount as for an original item of work.
- H. Submit one electronic and three hard-copies of each Application for Payment.

- I. Include the following with the application:
  - 1. Transmittal letter as specified for submittals in Section 01 3000.
  - 2. Construction progress schedule, revised and current as specified in Section 01 3000.
  - 3. Current construction photographs specified in Section 01 3000.
  - 4. Partial release of liens from major subcontractors and vendors.
  - 5. Affidavits attesting to off-site stored products.
- J. When Architect requires substantiating information, submit data justifying dollar amounts in question. Provide one copy of data with cover letter for each copy of submittal. Show application number and date, and line item by number and description.

## 1.05 MODIFICATION PROCEDURES

- A. Submit name of the individual authorized to receive change documents and who will be responsible for informing others in Contractor's employ or subcontractors of changes to Contract Documents.
- B. For minor changes not involving an adjustment to the Contract Sum or Contract Time, Architect will issue instructions directly to Contractor.
- C. For other required changes, Architect will issue a document signed by Owner instructing Contractor to proceed with the change, for subsequent inclusion in a Change Order.
  - 1. The document will describe the required changes and will designate method of determining any change in Contract Sum or Contract Time.
  - 2. Promptly execute the change.
- D. For changes for which advance pricing is desired, Architect will issue a document that includes a detailed description of a proposed change with supplementary or revised drawings and specifications, a change in Contract Time for executing the change with a stipulation of any overtime work required and the period of time during which the requested price will be considered valid. Contractor shall prepare and submit a fixed price quotation within 7 days.
- E. Contractor may propose a change by submitting a request for change to Architect, describing the proposed change and its full effect on the work, with a statement describing the reason for the change, and the effect on the Contract Sum and Contract Time with full documentation.
- F. Computation of Change in Contract Amount: As specified in the Agreement and Conditions of the Contract.
  - 1. For change requested by Architect for work falling under a fixed price contract, the amount will be based on Contractor's price quotation.
  - 2. For change requested by Contractor, the amount will be based on the Contractor's request for a Change Order as approved by Architect.
  - 3. For pre-determined unit prices and quantities, the amount will be based on the fixed unit prices.
  - 4. For change ordered by Architect without a quotation from Contractor, the amount will be determined by Architect based on the Contractor's substantiation of costs as specified for Time and Material work.
- G. Substantiation of Costs: Provide full information required for evaluation.
  - 1. On request, provide the following data:
    - a. Quantities of products, labor, and equipment.
    - b. Taxes, insurance, and bonds.
    - c. Overhead and profit.
    - d. Justification for any change in Contract Time.
  - 2. Support each claim for additional costs with additional information:
    - a. Origin and date of claim.
    - b. Dates and times work was performed, and by whom.
    - c. Time records and wage rates paid.
    - d. Invoices and receipts for products, equipment, and subcontracts, similarly documented.

3. For Time and Material work, submit itemized account and supporting data after completion of change, within time limits indicated in the Conditions of the Contract.
- H. Execution of Change Orders: Architect will issue Change Orders for signatures of parties as provided in the Conditions of the Contract.
- I. After execution of Change Order, promptly revise Schedule of Values and Application for Payment forms to record each authorized Change Order as a separate line item and adjust the Contract Sum.
- J. Promptly revise progress schedules to reflect any change in Contract Time, revise sub-schedules to adjust times for other items of work affected by the change, and resubmit.
- K. Promptly enter changes in Project Record Documents.

#### **1.06 APPLICATION FOR FINAL PAYMENT**

- A. Prepare Application for Final Payment as specified for progress payments, identifying total adjusted Contract Sum, previous payments, and sum remaining due.
- B. Application for Final Payment will not be considered until the following have been accomplished:
  1. All closeout procedures specified in Section 01 7000.

#### **PART 2 PRODUCTS - NOT USED**

#### **PART 3 EXECUTION - NOT USED**

**END OF SECTION 01 2000**

This page intentionally left blank

## **SECTION 01 2100 ALLOWANCES**

### **PART 1 GENERAL**

#### **1.01 SECTION INCLUDES**

- A. Cash allowances.

#### **1.02 CASH ALLOWANCES**

- A. Costs Included in Cash Allowances: Cost of product to Contractor or subcontractor, less applicable trade discounts, less cost of delivery to site , less applicable taxes .
- B. Architect Responsibilities:
  1. Consult with Contractor for consideration and selection of products, suppliers , and installers.
  2. Select products in consultation with Owner and transmit decision to Contractor.
- C. Contractor Responsibilities:
  1. Assist Architect in selection of products, suppliers , and installers.
  2. Obtain proposals from suppliers and installers and offer recommendations.
  3. On notification of which products have been selected, execute purchase agreement with designated supplier and installer.
  4. Arrange for and process shop drawings, product data, and samples. Arrange for delivery.
  5. Promptly inspect products upon delivery for completeness, damage, and defects. Submit claims for transportation damage.

#### **1.03 ALLOWANCES SCHEDULE**

- A. Miscellaneous Repairs Outside Scope of Work: Include the stipulated sum of \$50,000.00 fo use upon Owner's instructions.

### **PART 2 PRODUCTS - NOT USED**

### **PART 3 EXECUTION - NOT USED**

**END OF SECTION 01 2100**

This page intentionally left blank

**SECTION 01 2300  
ALTERNATES**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Description of Alternates.
- B. Procedures for pricing Alternates.
- C. Documentation of changes to Contract Price and Contract Time.

**1.02 ACCEPTANCE OF ALTERNATES**

- A. Alternates quoted on Bid Forms will be reviewed and accepted or rejected at Owner's option. Accepted Alternates will be identified in the Owner-Contractor Agreement.
- B. Coordinate related work and modify surrounding work to integrate the Work of each Alternate.

**1.03 SCHEDULE OF ALTERNATES**

- A. Alternate No. 1 - : Observation Room 176 and Sound Booth 177
  - 1. Base Bid Item: No work in rooms 176 and 177.
  - 2. Alternate Item: All work associated with rooms 176 and 177.
- B. Alternate No. 2 - : Women 119, Men 120, Storage 121, and M.A. Office 132
  - 1. Base Bid Item: No work in rooms 119, 120, 121, and 132.
  - 2. Alternate Item: All work associated with rooms 119, 120, 121, and 132.
- C. Alternate No. 3 - : Existing roof curbs.
  - 1. Base Bid Item: No work.
  - 2. Alternate Item: Remove existing abandoned curbs and repair roof panel indicated on drawings.
- D. Alternate No. 4 - : Parking Lot Striping.
  - 1. Base Bid Item: No work.
  - 2. Alternate Item: Stripe existing parking lot over existing striping.
- E. Alternate No. 5 - : Office 152B
  - 1. Base Bid Item: No work.
  - 2. Alternate Item: All work associated with Office 152B

**PART 2 PRODUCTS - NOT USED**

**PART 3 EXECUTION - NOT USED**

**END OF SECTION 01 2300**

This page intentionally left blank

**SECTION 01 2500**  
**SUBSTITUTION PROCEDURES**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Procedural requirements for proposed substitutions.

**1.02 RELATED REQUIREMENTS**

- A. Section 01 2300 - Alternates, for product alternatives affecting this section.
- B. Section 01 3000 - Administrative Requirements: Submittal procedures, coordination.
- C. Section 01 6000 - Product Requirements: Fundamental product requirements, product options, delivery, storage, and handling.
- D. Section 01 6116 - Volatile Organic Compound (VOC) Content Restrictions: Restrictions on emissions of indoor substitute products.

**1.03 DEFINITIONS**

- A. Substitutions: Changes from Contract Documents requirements proposed by Contractor to materials, products, assemblies, and equipment.
  - 1. Substitutions for Cause: Proposed due to changed Project circumstances beyond Contractor's control.
    - a. Unavailability.
    - b. Regulatory changes.
  - 2. Substitutions for Convenience: Proposed due to possibility of offering substantial advantage to the Project.
    - a. Substitution requests offering advantages solely to the Contractor will not be considered.

**1.04 REFERENCE STANDARDS**

- A. CSI/CSC Form 1.5C - Substitution Request (During the Bidding/Negotiating Stage); Current Edition.
- B. CSI/CSC Form 13.1A - Substitution Request (After the Bidding/Negotiating Phase); Current Edition.

**PART 2 PRODUCTS - NOT USED**

**PART 3 EXECUTION**

**3.01 GENERAL REQUIREMENTS**

- A. A Substitution Request for products, assemblies, materials, and equipment constitutes a representation that the submitter:
  - 1. Has investigated proposed product and determined that it meets or exceeds the quality level of the specified product, equipment, assembly, or system.
  - 2. Agrees to provide the same warranty for the substitution as for the specified product.
  - 3. Agrees to provide same or equivalent maintenance service and source of replacement parts, as applicable.
  - 4. Agrees to coordinate installation and make changes to other work that may be required for the work to be complete, with no additional cost to Owner.
  - 5. Waives claims for additional costs or time extension that may subsequently become apparent.
  - 6. Agrees to reimburse Owner and Architect for review or redesign services associated with re-approval by authorities.
- B. A Substitution Request for specified installer constitutes a representation that the submitter:
  - 1. Has acted in good faith to obtain services of specified installer, but was unable to come to commercial, or other terms.

- C. Document each request with complete data substantiating compliance of proposed substitution with Contract Documents. Burden of proof is on proposer.
  - 1. Note explicitly any non-compliant characteristics.
- D. Where "basis of design" or named products are specified, alternate equivalent manufacturers and materials may be proposed provided they are equal quality and appearance to that specified, in the opinion of the Architect. Contractor shall provide an item-by-item and side-by-side comparison of proposed substitutions. Include all deviations and/or differences between proposed product and specified product. Include side-by-side images to indicate differences in appearance. Substitution forms without this information or incomplete proposals will be returned without review. Contractor to coordinate alternate substrate and backing requirements that may be required and compatibility with other adjacent materials and systems.
- E. Content: Include information necessary for tracking the status of each Substitution Request, and information necessary to provide an actionable response.
  - 1. No specific form is required. Contractor's Substitution Request documentation must include the following:
    - a. Project Information:
      - 1) Official project name and number, and any additional required identifiers established in Contract Documents.
      - 2) Owner's, Architect's, and Contractor's names.
      - 3) Additional information as required to facilitate review.
    - b. Substitution Request Information:
      - 1) Discrete and consecutive Substitution Request number, and descriptive subject/title.
      - 2) Indication of whether the substitution is for cause or convenience.
      - 3) Issue date.
      - 4) Reference to particular Contract Document(s) specification section number, title, and article/paragraph(s).
      - 5) Description of Substitution.
      - 6) Reason why the specified item cannot be provided.
      - 7) Differences between proposed substitution and specified item.
      - 8) Description of how proposed substitution affects other parts of work.
    - c. Attached Comparative Data: Provide point-by-point, side-by-side comparison addressing essential attributes specified, as appropriate and relevant for the item:
      - 1) Physical characteristics.
      - 2) In-service performance.
      - 3) Expected durability.
      - 4) Visual effect.
      - 5) Sustainable design features.
      - 6) Warranties.
      - 7) Other salient features and requirements.
      - 8) Include, as appropriate or requested, the following types of documentation:
        - (a) Product Data:
        - (b) Samples.
        - (c) Certificates, test, reports or similar qualification data.
        - (d) Drawings, when required to show impact on adjacent construction elements.
        - (e) Photos or images.
        - (f) Provide clear, legible, high resolution, electronic documents
          - (1) Blurry, distorted, or miss-aligned text or images, or low quality scans of printed materials will not be reviewed.
    - d. Impact of Substitution:
      - 1) Savings to Owner for accepting substitution.
      - 2) Change to Contract Time due to accepting substitution.

- F. Limit each request to a single proposed substitution item.
  - 1. Submit an electronic document, combining the request form with supporting data into single document.
- G. Substitutions will not be considered when acceptance will require revisions to Contract Documents
- H. Substitution requests that do not follow all specified procedures or contains all specified requirements and information will be returned without review
  - 1. All substitution requests must be reviewed by architect
  - 2. Vendor correspondence or solicitation to engineers or architects's consultants does not constitute a substitution request.

### **3.02 SUBSTITUTION PROCEDURES DURING PROCUREMENT**

- A. Instructions to Bidders specifies time restrictions for submitting substitution requests during the bidding period and the documents required.

### **3.03 SUBSTITUTION PROCEDURES DURING CONSTRUCTION**

- A. Architect will consider requests for substitutions only within 15 days after date of Agreement.
- B. Submit request for Substitution for Cause immediately upon discovery of need for substitution, but not later than 15 days prior to time required for review and approval by Architect, in order to stay on approved project schedule.
- C. Submit request for Substitution for Convenience immediately upon discovery of its potential advantage to the project, but not later than 15 days prior to time required for review and approval by Architect, in order to stay on approved project schedule.
  - 1. In addition to meeting general documentation requirements, document how the requested substitution benefits the Owner through cost savings, time savings, greater energy conservation, or in other specific ways.
  - 2. Document means of coordinating of substitution item with other portions of the work, including work by affected subcontractors.
  - 3. Bear the costs engendered by proposed substitution of:
    - a. Owner's compensation to the Architect for any required redesign, time spent processing and evaluating the request.
    - b. Other construction by Owner.
    - c. Other unanticipated project considerations.
- D. Substitutions will not be considered under one or more of the following circumstances:
  - 1. When they are indicated or implied on shop drawing or product data submittals, without having received prior approval.
  - 2. Without a separate written request.
  - 3. When acceptance will require revisions to Contract Documents.

### **3.04 RESOLUTION**

- A. Architect may request additional information and documentation prior to rendering a decision. Provide this data in an expeditious manner.
- B. Architect will notify Contractor in writing of decision to accept or reject request.
  - 1. Architect's decision following review of proposed substitution will be noted on the submitted form.

### **3.05 ACCEPTANCE**

- A. Accepted substitutions change the work of the Project. They will be documented and incorporated into work of the project by Change Order, Construction Change Directive, Architectural Supplementary Instructions, or similar instruments provided for in the Conditions of the Contract.

### **3.06 CLOSEOUT ACTIVITIES**

- A. See Section 01 7800 - Closeout Submittals, for closeout submittals.

B. Include completed Substitution Request Forms as part of the Project record.

**END OF SECTION 01 2500**

**SECTION 01 3000**  
**ADMINISTRATIVE REQUIREMENTS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. General administrative requirements.
- B. Electronic document submittal service.
- C. Preconstruction meeting.
- D. Progress meetings.
- E. Construction progress schedule.
- F. Progress photographs.
- G. Coordination drawings.
- H. Number of copies of submittals.
- I. Requests for Information (RFI) procedures.
- J. Submittal procedures.

**1.02 RELATED REQUIREMENTS**

- A. Section 01 6000 - Product Requirements: General product requirements.
- B. Section 01 7000 - Execution and Closeout Requirements: Additional coordination requirements.
- C. Section 01 7800 - Closeout Submittals: Project record documents; operation and maintenance data; warranties and bonds.

**1.03 GENERAL ADMINISTRATIVE REQUIREMENTS**

- A. Make the following types of submittals to Architect:
  - 1. Requests for Information (RFI).
  - 2. Shop drawings, product data, and samples.
  - 3. Test and inspection reports.
  - 4. Design data.
  - 5. Manufacturer's instructions and field reports.
  - 6. Applications for payment and change order requests.
  - 7. Progress schedules.
  - 8. Coordination drawings.
  - 9. Contractor's Punch List, Correction Punch List and Final Correction Punch List for Substantial Completion.
  - 10. Closeout submittals.

**PART 2 PRODUCTS - NOT USED**

**PART 3 EXECUTION**

**3.01 ELECTRONIC DOCUMENT SUBMITTAL SERVICE**

- A. All documents transmitted for purposes of administration of the contract are to be in electronic (PDF, MS Word, or MS Excel) format, as appropriate to the document, and transmitted via an Internet-based submittal service that receives, logs and stores documents, provides electronic stamping and signatures, and notifies addressees via email.
  - 1. Besides submittals for review, information, and closeout, this procedure applies to Requests for Information (RFIs), progress documentation, contract modification documents (e.g. supplementary instructions, change proposals, change orders), applications for payment, field reports and meeting minutes, Contractor's correction punchlist, and any other document any participant wishes to make part of the project record.

2. Contractor and Architect are required to use this service.
3. It is Contractor's responsibility to submit documents in allowable format.
4. Subcontractors, suppliers, and Architect's consultants will be permitted to use the service at no extra charge.
5. Users of the service need an email address, internet access, and PDF review software that includes ability to mark up and apply electronic stamps (such as Adobe Acrobat, [www.adobe.com](http://www.adobe.com), or Bluebeam PDF Revu, [www.bluebeam.com](http://www.bluebeam.com)), unless such software capability is provided by the service provider.
6. Paper document transmittals will not be reviewed; emailed electronic documents will not be reviewed.
7. All other specified submittal and document transmission procedures apply, except that electronic document requirements do not apply to samples or color selection charts.

B. Submittal Service: The selected service is:

1. Architect's Electronic Document Submittal Service: TonicDM.

### **3.02 PRECONSTRUCTION MEETING**

- A. Owner will schedule a meeting after Notice of Award.
- B. Attendance Required:
  1. Owner.
  2. Architect.
  3. Contractor.
- C. Agenda:
  1. Execution of Owner-Contractor Agreement.
  2. Submission of executed bonds and insurance certificates.
  3. Submission of list of subcontractors, list of products, schedule of values, and progress schedule.
  4. Submission of initial Submittal schedule.
  5. Designation of personnel representing the parties to Contract .
  6. Procedures and processing of field decisions, submittals, substitutions, applications for payments, proposal request, Change Orders, and Contract closeout procedures.
  7. Scheduling.
- D. Record minutes and distribute copies within two days after meeting to participants, with two copies to Architect, Owner, participants, and those affected by decisions made.

### **3.03 PROGRESS MEETINGS**

- A. Schedule and administer meetings throughout progress of the work at maximum bi-monthly intervals.
- B. Make arrangements for meetings, prepare agenda with copies for participants, preside at meetings.
- C. Attendance Required:
  1. Contractor.
  2. Owner.
  3. Architect.
  4. Contractor's Project Manager and Superintendent.
- D. Agenda:
  1. Review minutes of previous meetings.
  2. Review of work progress.
  3. Field observations, problems, and decisions.
  4. Identification of problems that impede, or will impede, planned progress.
  5. Review of submittals schedule and status of submittals.
  6. Review of off-site fabrication and delivery schedules.
  7. Maintenance of progress schedule.

- 8. Corrective measures to regain projected schedules.
- 9. Planned progress during succeeding work period.
- 10. Maintenance of quality and work standards.
- 11. Effect of proposed changes on progress schedule and coordination.
- 12. Other business relating to work.

E. Record minutes and distribute copies within two days after meeting to participants, with two copies to Architect, Owner, participants, and those affected by decisions made.

### **3.04 CONSTRUCTION PROGRESS SCHEDULE**

- A. Within 10 days after date of the Agreement, submit preliminary schedule defining planned operations for the first 60 days of work, with a general outline for remainder of work.
- B. If preliminary schedule requires revision after review, submit revised schedule within 10 days.
- C. Within 20 days after review of preliminary schedule, submit draft of proposed complete schedule for review.
- D. Within 10 days after joint review, submit complete schedule.
- E. Submit updated schedule with each Application for Payment.

### **3.05 PROGRESS PHOTOGRAPHS**

- A. Submit photographs with each application for payment, taken not more than 3 days prior to submission of application for payment.
- B. Maintain one set of all photographs at project site for reference; same copies as submitted, identified as such.
- C. Photography Type: Digital; electronic files.
- D. Digital Photographs: 24 bit color, minimum resolution of 1600 by 1200 ("2 megapixel"), in JPG format; provide files unaltered by photo editing software.
  - 1. Delivery Medium: TonicDM.
  - 2. File Naming: Include project identification, date and time of view, and view identification.
  - 3. Point of View Sketch: Include digital copy of point of view sketch with each electronic submittal; include point of view identification in each photo file name.

### **3.06 COORDINATION DRAWINGS**

- A. Review drawings prior to submission to Architect.

### **3.07 REQUESTS FOR INFORMATION(RFI)**

- A. Definition: A request seeking one of the following:
  - 1. An interpretation, amplification, or clarification of some requirement of Contract Documents arising from inability to determine from them the exact material, process, or system to be installed; or when the elements of construction are required to occupy the same space (interference); or when an item of work is described differently at more than one place in the Contract Documents.
- B. Whenever possible, request clarifications at the next appropriate project progress meeting, with response entered into meeting minutes, rendering unnecessary the issuance of a formal RFI.
- C. Preparation: Prepare an RFI immediately upon discovery of a need for interpretation of the Contract Documents. Failure to submit a RFI in a timely manner is not a legitimate cause for claiming additional costs or delays in execution of the work.
  - a. Review, coordinate, and comment on requests originating with subcontractors and/or materials suppliers.
  - b. Do not forward requests which solely require internal coordination between subcontractors.
- 2. Prepare using software provided by the Electronic Document Submittal Service.
- 3. Combine RFI and its attachments into a single electronic file. PDF format is preferred.

- D. Reason for the RFI: Prior to initiation of an RFI, carefully study all Contract Documents to confirm that information sufficient for their interpretation is definitely not included.
  - 1. Include in each request Contractor's signature attesting to good faith effort to determine from the Contract Documents information requiring interpretation.
  - 2. Unacceptable Uses for RFIs: Do not use RFIs to request the following:
    - a. Approval of submittals (use procedures specified elsewhere in this section).
    - b. Approval of substitutions (see Section - 01 6000 - Product Requirements)
    - c. Changes that entail change in Contract Time and Contract Sum (comply with provisions of the Conditions of the Contract).
    - d. Different methods of performing work than those indicated in the Contract Drawings and Specifications (comply with provisions of the Conditions of the Contract).
  - 3. Improper RFIs: Requests not prepared in conformance to requirements of this section, and/or missing key information required to render an actionable response. They will be returned without a response, with an explanatory notation.
  - 4. Frivolous RFIs: Requests regarding information that is clearly indicated on, or reasonably inferable from, the Contract Documents, with no additional input required to clarify the question. They will be returned without a response, with an explanatory notation.
- E. Content: Include identifiers necessary for tracking the status of each RFI, and information necessary to provide an actionable response.
  - 1. Official Project name and number, and any additional required identifiers established in Contract Documents.
  - 2. Owner's, Architect's, and Contractor's names.
  - 3. Discrete and consecutive RFI number, and descriptive subject/title.
  - 4. Issue date, and requested reply date.
  - 5. Reference to particular Contract Document(s) requiring additional information/interpretation. Identify pertinent drawing and detail number and/or specification section number, title, and paragraph(s).
  - 6. Annotations: Field dimensions and/or description of conditions which have engendered the request.
  - 7. Contractor's suggested resolution: A written and/or a graphic solution, to scale, is required in cases where clarification of coordination issues is involved, for example; routing, clearances, and/or specific locations of work shown diagrammatically in Contract Documents. If applicable, state the likely impact of the suggested resolution on Contract Time or the Contract Sum.
- F. Attachments: Include sketches, coordination drawings, descriptions, photos, submittals, and other information necessary to substantiate the reason for the request.
- G. RFI Log: Prepare and maintain a tabular log of RFIs for the duration of the project.
  - 1. Indicate current status of every RFI. Update log promptly and on a regular basis.
  - 2. Note dates of when each request is made, and when a response is received.
  - 3. Highlight items requiring priority or expedited response.
  - 4. Highlight items for which a timely response has not been received to date.
  - 5. Identify and include improper or frivolous RFIs.
- H. Review Time: Architect will respond and return RFIs to Contractor within seven calendar days of receipt. For the purpose of establishing the start of the mandated response period, RFIs received after 3:00 PM will be considered as having been received on the following regular working day.
  - 1. Response period may be shortened or lengthened for specific items, subject to mutual agreement, and recorded in a timely manner in progress meeting minutes.
- I. Responses: Content of answered RFIs will not constitute in any manner a directive or authorization to perform extra work or delay the project. If in Contractor's belief it is likely to lead to a change to Contract Sum or Contract Time, promptly issue a notice to this effect, and follow up with an appropriate Change Order request to Owner.

1. Response may include a request for additional information, in which case the original RFI will be deemed as having been answered, and an amended one is to be issued forthwith. Identify the amended RFI with an R suffix to the original number.
2. Do not extend applicability of a response to specific item to encompass other similar conditions, unless specifically so noted in the response.
3. Upon receipt of a response, promptly review and distribute it to all affected parties, and update the RFI Log.
4. Notify Architect within seven calendar days if an additional or corrected response is required by submitting an amended version of the original RFI, identified as specified above.

### **3.08 SUBMITTAL SCHEDULE**

- A. Submit to Architect for review a schedule for submittals in tabular format.
  1. Format schedule to allow tracking of status of submittals throughout duration of construction.
  2. Arrange information to include scheduled date for initial submittal, specification number and title, submittal category (for review or for information), description of item of work covered, and role and name of subcontractor.

### **3.09 NUMBER OF COPIES OF SUBMITTALS**

- A. Electronic Documents: Submit one electronic copy in PDF format; an electronically-marked up file will be returned. Create PDFs at native size and right-side up; illegible files will be rejected.

### **3.10 SUBMITTAL PROCEDURES**

- A. General Requirements:
  1. Deliver each submittal on date noted in submittal schedule, unless an earlier date has been agreed to by all affected parties, and is of the benefit to the project.
    - a. Upload submittals in electronic form to Electronic Document Submittal Service website.
  2. Incomplete submittals will not be reviewed, unless they are partial submittals for distinct portion(s) of the work, and have received prior approval for their use.
  3. Submittals not requested will be recognized, and will be returned "Not Reviewed",
- B. Product Data Procedures:
  1. Submit only information required by individual specification sections.
  2. Collect required information into a single submittal.
  3. Submit concurrently with related shop drawing submittal.
  4. Do not submit (Material) Safety Data Sheets for materials or products.
- C. Shop Drawing Procedures:
  1. Prepare accurate, drawn-to-scale, original shop drawing documentation by interpreting the Contract Documents and coordinating related work.
  2. Do not reproduce the Contract Documents to create shop drawings.
  3. Generic, non-project-specific information submitted as shop drawings do not meet the requirements for shop drawings.
- D. Samples Procedures:
  1. Transmit related items together as single package.
  2. Identify each item to allow review for applicability in relation to shop drawings showing installation locations.
- E. Transmit each submittal with a copy of approved submittal form.
- F. Sequentially number the transmittal form. Revise submittals with original number and a sequential alphabetic suffix.
- G. Identify Project, Contractor, Subcontractor or supplier; pertinent drawing and detail number, and specification section number, as appropriate on each copy.

- H. Apply Contractor's stamp, signed or initialed certifying that review, approval, verification of Products required, field dimensions, adjacent construction Work, and coordination of information is in accordance with the requirements of the Work and Contract Documents.
- I. Schedule submittals to expedite the Project, and coordinate submission of related items.
- J. For each submittal for review, allow 15 days excluding delivery time to and from the Contractor.
- K. Identify variations from Contract Documents and Product or system limitations that may be detrimental to successful performance of the completed Work.
- L. Provide space for Contractor and Architect review stamps.
- M. When revised for resubmission, identify all changes made since previous submission.
- N. Distribute reviewed submittals as appropriate. Instruct parties to promptly report any inability to comply with requirements.

### **3.11 SUBMITTAL REVIEW**

- A. Submittals for Review: Architect will review each submittal, and approve, or take other appropriate action.
- B. Submittals for Information: Architect will acknowledge receipt and review. See below for actions to be taken.
- C. Architect's actions will be reflected by marking each returned submittal using virtual stamp on electronic submittals.

**END OF SECTION 01 3000**

## **SECTION 01 4000** **QUALITY REQUIREMENTS**

### **PART 1 GENERAL**

#### **1.01 SECTION INCLUDES**

- A. Submittals.
- B. Quality assurance.
- C. References and standards.
- D. Inspection agencies and services.
- E. Contractor's construction-related professional design services.
- F. Contractor's design-related professional design services.
- G. Control of installation.
- H. Mock-ups.
- I. Tolerances.
- J. Manufacturers' field services.
- K. Defect Assessment.

#### **1.02 RELATED REQUIREMENTS**

- A. Document 00 3100 - Available Project Information: Soil investigation data.
- B. Section 01 3000 - Administrative Requirements: Submittal procedures.
- C. Section 01 6000 - Product Requirements: Requirements for material and product quality.

#### **1.03 REFERENCE STANDARDS**

- A. ASTM C1021 - Standard Practice for Laboratories Engaged in Testing of Building Sealants; 2008 (Reapproved 2023).
- B. ASTM C1077 - Standard Practice for Agencies Testing Concrete and Concrete Aggregates for Use in Construction and Criteria for Testing Agency Evaluation; 2025a.
- C. ASTM C1093 - Standard Practice for Accreditation of Testing Agencies for Masonry; 2023.
- D. ASTM D3740 - Standard Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction; 2023.
- E. ASTM E329 - Standard Specification for Agencies Engaged in Construction Inspection, Testing, or Special Inspection; 2025a.
- F. ASTM E543 - Standard Specification for Agencies Performing Nondestructive Testing; 2021.
- G. ASTM E699 - Standard Specification for Agencies Involved in Testing, Quality Assurance, and Evaluating of Manufactured Building Components; 2016.
- H. IAS AC89 - Accreditation Criteria for Testing Laboratories; 2021.

#### **1.04 DEFINITIONS**

- A. Contractor's Quality Control Plan: Contractor's management plan for executing the Contract for Construction.
- B. Contractor's Professional Design Services: Design of some aspect or portion of the project by party other than the design professional of record. Provide these services as part of the Contract for Construction.
  1. Design Services Types Required:
    - a. Construction-Related: Services Contractor needs to provide in order to carry out the Contractor's sole responsibilities for construction means, methods, techniques, sequences, and procedures.

- b. Design-Related: Design services explicitly required to be performed by another design professional due to highly-technical and/or specialized nature of a portion of the project. Services primarily involve engineering analysis, calculations, and design, and are not intended to alter the aesthetic aspects of the design.
- C. Design Data: Design-related, signed and sealed drawings, calculations, specifications, certifications, shop drawings and other submittals provided by Contractor, and prepared directly by, or under direct supervision of, appropriately licensed design professional.

## **1.05 CONTRACTOR'S CONSTRUCTION-RELATED PROFESSIONAL DESIGN SERVICES**

- A. Coordination: Contractor's professional design services are subject to requirements of project's Conditions for Construction Contract.
- B. Provide such engineering design services as may be necessary to plan and safely conduct certain construction operations, pertaining to, but not limited to the following:
  - 1. Temporary sheeting, shoring, or supports.
  - 2. Temporary scaffolding.
  - 3. Temporary bracing.
  - 4. Temporary falsework for support of spanning or arched structures.
  - 5. Temporary foundation underpinning.
  - 6. Temporary stairs or steps required for construction access only.
  - 7. Temporary hoist(s) and rigging.
  - 8. Investigation of soil conditions to support construction equipment.

## **1.06 CONTRACTOR'S DESIGN-RELATED PROFESSIONAL DESIGN SERVICES**

- A. Coordination: Contractor's professional design services are subject to requirements of project's Conditions for Construction Contract.
- B. Base design on performance and/or design criteria indicated in individual specification sections.
  - 1. Submit a Request for Interpretation to Architect if the criteria indicated are not sufficient to perform required design services.
- C. Scope of Contractor's Professional Design Services: Provide for the following items of work:
  - 1. Structural Design of Steel Connections: As described in Section 05 1200 - Structural Steel Framing.
  - 2. Structural Design of Steel Connections: As described in Section 05 2100 - Steel Joist Framing.
  - 3. Structural Design of Steel Decking: As described in Section 05 3100 - Steel Decking.
  - 4. Structural Design of Metal Framing: As described in Section 05 4000 - Cold-Formed Metal Framing.
  - 5. Structural Design of Metal Fabrications: As described in Section 05 5000 - Metal Fabrications.
  - 6. Structural Design of Stairs: As described in Section 05 5100 - Metal Stairs.
  - 7. Structural Design of Railings: As described in Section 05 5213 - Pipe and Tube Railings.
  - 8. Structural Design: Include physical characteristics, engineering calculations, and resulting dimensional limitations as described in Section 08 4435 - Protective Framed Glazing Assemblies.
  - 9. Design of Structural Components: Include development of shop drawings, and performing shop and site work, as described in Section 13 3419 - Metal Building Systems.
  - 10. Sprinkler Layout: Coordinate with ceiling installation, detailed pipe layout, and hydraulic calculations as described in Section 21 1300 - Fire-Suppression Sprinkler Systems.
  - 11. Additional design as indicated.
    - a. Contractor shall employ a consultant qualified to interpret structural criteria and other applicable criteria that pertains to the project.

## **1.07 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.

- B. Designer's Qualification Statement: Submit for Architect's knowledge as contract administrator, or for Owner's information.
  - 1. Include information for each individual professional responsible for producing, or supervising production of, design-related professional services provided by Contractor.
    - a. Full name.
    - b. Professional licensure information.
    - c. Statement addressing extent and depth of experience specifically relevant to design of items assigned to Contractor.
- C. Design Data: Submit for Architect's knowledge as contract administrator for the limited purpose of assessing compliance with information given and the design concept expressed in the Contract Documents, or for Owner's information.
  - 1. Include calculations that have been used to demonstrate compliance to performance and regulatory criteria provided, and to determine design solutions.
  - 2. Include required product data and shop drawings.
  - 3. Include a statement or certification attesting that design data complies with criteria indicated, such as building codes, loads, functional, and similar engineering requirements.
  - 4. Include signature and seal of design professional responsible for allocated design services on calculations and drawings.
- D. Test Reports: After each test/inspection, promptly submit two copies of report to Architect and to Contractor.
  - 1. Include:
    - a. Date issued.
    - b. Project title and number.
    - c. Name of inspector.
    - d. Date and time of sampling or inspection.
    - e. Identification of product and specifications section.
    - f. Location in the Project.
    - g. Type of test/inspection.
    - h. Date of test/inspection.
    - i. Results of test/inspection.
    - j. Compliance with Contract Documents.
    - k. When requested by Architect, provide interpretation of results.
  - 2. Test report submittals are for Architect's knowledge as contract administrator for the limited purpose of assessing compliance with information given and the design concept expressed in the Contract Documents, or for Owner's information.
- E. Certificates: When specified in individual specification sections, submit certification by the manufacturer and Contractor or installation/application subcontractor to Architect, in quantities specified for Product Data.
  - 1. Indicate material or product complies with or exceeds specified requirements. Submit supporting reference data, affidavits, and certifications as appropriate.
  - 2. Certificates may be recent or previous test results on material or product, but must be acceptable to Architect.
- F. Manufacturer's Instructions: When specified in individual specification sections, submit printed instructions for delivery, storage, assembly, installation, start-up, adjusting, and finishing, for the Owner's information. Indicate special procedures, perimeter conditions requiring special attention, and special environmental criteria required for application or installation.
- G. Manufacturer's Field Reports: Submit reports for Architect's benefit as contract administrator or for Owner.
  - 1. Submit report in duplicate within 30 days of observation to Architect for information.
  - 2. Submit for information for the limited purpose of assessing compliance with information given and the design concept expressed in the Contract Documents.

## 1.08 QUALITY ASSURANCE

- A. Testing Agency Qualifications:
  - 1. Prior to start of work, submit agency name, address, and telephone number, and names of full time registered Engineer and responsible officer.
  - 2. Submit copy of report of laboratory facilities inspection made by NIST Construction Materials Reference Laboratory during most recent inspection, with memorandum of remedies of any deficiencies reported by the inspection.
  - 3. Qualification Statement: Provide documentation showing testing laboratory is accredited under IAS AC89.
- B. Designer Qualifications: Where professional engineering design services and design data submittals are specifically required of Contractor by Contract Documents, provide services of a Professional Engineer experienced in design of this type of work and licensed in the State in which the Project is located.
- C. Contractor's Quality Control (CQC) Plan:
  - 1. Prior to start of work, submit a comprehensive plan describing how contract deliverables will be produced. Tailor CQC plan to specific requirements of the project. Include the following information:
    - a. Management Structure: Identify personnel responsible for quality. Include a chart showing lines of authority.
      - 1) Include qualifications (in resume form), duties, responsibilities of each person assigned to CQC function.
    - b. Management Approach: Define, describe, and include in the plan specific methodologies used in executing the work.
      - 1) Management and control of documents and records relating to quality.
      - 2) Communications.
      - 3) Coordination procedures.
      - 4) Resource management.
      - 5) Process control.
      - 6) Inspection and testing procedures and scheduling.
      - 7) Control of noncomplying work.
      - 8) Tracking deficiencies from identification, through acceptable corrective action, and verification.
      - 9) Control of testing and measuring equipment.
      - 10) Project materials certification.
      - 11) Managerial continuity and flexibility.
    - c. Owner will not make a separate payment for providing and maintaining a Quality Control Plan. Include associated costs in Bid price.
    - d. Acceptance of the plan is required prior to start of construction activities not including mobilization work. Owner's acceptance of the plan will be conditional and predicated on continuing satisfactory adherence to the plan. Owner reserves the right to require Contractor to make changes to the plan and operations, including removal of personnel, as necessary, to obtain specified quality of work results.
  - D. Quality-Control Personnel Qualifications. Engage a person with requisite training and experience to implement and manage quality assurance (QA) and quality control (QC) for the project.

## 1.09 REFERENCES AND STANDARDS

- A. For products and workmanship specified by reference to a document or documents not included in the Project Manual, also referred to as reference standards, comply with requirements of the standard, except when more rigid requirements are specified or are required by applicable codes.
- B. Comply with reference standard of date of issue current on date of Contract Documents, except where a specific date is established by applicable code.

- C. Obtain copies of standards where required by product specification sections.
- D. Maintain copy at project site during submittals, planning, and progress of the specific work, until Substantial Completion.
- E. Should specified reference standards conflict with Contract Documents, request clarification from Architect before proceeding.
- F. Neither the contractual relationships, duties, or responsibilities of the parties in Contract nor those of Architect shall be altered from Contract Documents by mention or inference otherwise in any reference document.

#### **1.10 TESTING AND INSPECTION AGENCIES AND SERVICES**

- A. Contractor shall employ and pay for services of an independent testing agency to perform other specified testing.
- B. Employment of agency in no way relieves Contractor of obligation to perform Work in accordance with requirements of Contract Documents.
- C. Contractor Employed Agency:
  - 1. Testing agency: Comply with requirements of ASTM E329, ASTM E543, ASTM E699, ASTM C1021, ASTM C1077, ASTM C1093, ASTM D3740, and \_\_\_\_\_.
  - 2. Inspection agency: Comply with requirements of ASTM D3740, ASTM E329, and \_\_\_\_\_.
  - 3. Laboratory Qualifications: Accredited by IAS according to IAS AC89.
  - 4. Laboratory: Authorized to operate in the State in which the Project is located.
  - 5. Testing Equipment: Calibrated at reasonable intervals either by NIST or using an NIST established Measurement Assurance Program, under a laboratory measurement quality assurance program.

#### **PART 2 PRODUCTS - NOT USED**

#### **PART 3 EXECUTION**

##### **3.01 CONTROL OF INSTALLATION**

- A. Monitor quality control over suppliers, manufacturers, products, services, site conditions, and workmanship, to produce work of specified quality.
- B. Comply with manufacturers' instructions, including each step in sequence.
- C. Should manufacturers' instructions conflict with Contract Documents, request clarification from Architect before proceeding.
- D. Comply with specified standards as minimum quality for the work except where more stringent tolerances, codes, or specified requirements indicate higher standards or more precise workmanship.
- E. Have work performed by persons qualified to produce required and specified quality.
- F. Verify that field measurements are as indicated on shop drawings or as instructed by the manufacturer.
- G. Secure products in place with positive anchorage devices designed and sized to withstand stresses, vibration, physical distortion, and disfigurement.

##### **3.02 MOCK-UPS**

- A. Before installing portions of the Work where mock-ups are required, construct mock-ups in location and size indicated for each form of construction and finish required to comply with the following requirements, using materials indicated for the completed Work. The purpose of mock-up is to demonstrate the proposed range of aesthetic effects and workmanship.
- B. Accepted mock-ups establish the standard of quality the Architect will use to judge the Work.
- C. Integrated Exterior Mock-ups: Construct integrated exterior mock-up as indicated on drawings. Coordinate installation of exterior envelope materials and products as required in individual

Specification Sections. Provide adequate supporting structure for mock-up materials as necessary.

1. Provide the minimum integrated exterior mock-up, unless more stringent requirements are indicated on drawings
  - a. 12 ft x 12 ft size to include all specified exterior wall materials, including complete assembly from exterior face to interior face. Include all sealants, flashing and trim and at least one window unit.
- D. Notify Architect fifteen (15) working days in advance of dates and times when mock-ups will be constructed.
- E. Provide supervisory personnel who will oversee mock-up construction. Provide workers that will be employed during the construction at Project.
- F. Tests shall be performed under provisions identified in this section and identified in the respective product specification sections.
- G. Assemble and erect specified items with specified attachment and anchorage devices, flashings, seals, and finishes.
- H. Obtain Architect's approval of mock-ups before starting work, fabrication, or construction.
  1. Architect will issue written comments within seven (7) working days of initial review and each subsequent follow up review of each mock-up.
  2. Make corrections as necessary until Architect's approval is issued.
- I. Architect will use accepted mock-ups as a comparison standard for the remaining Work.
- J. Where mock-up has been accepted by Architect and is specified in product specification sections to be removed, protect mock-up throughout construction, remove mock-up and clear area when directed to do so by Architect.
- K. Legally salvage and recycle the demolished mock-up materials.

### **3.03 TOLERANCES**

- A. Monitor fabrication and installation tolerance control of products to produce acceptable Work. Do not permit tolerances to accumulate.
- B. Comply with manufacturers' tolerances. Should manufacturers' tolerances conflict with Contract Documents, request clarification from Architect before proceeding.
- C. Adjust products to appropriate dimensions; position before securing products in place.

### **3.04 TESTING AND INSPECTION**

- A. See individual specification sections for testing and inspection required.
- B. Testing Agency Duties:
  1. Provide qualified personnel at site. Cooperate with Architect and Contractor in performance of services.
  2. Perform specified sampling and testing of products in accordance with specified standards.
  3. Ascertain compliance of materials and mixes with requirements of Contract Documents.
  4. Promptly notify Architect and Contractor of observed irregularities or non-compliance of Work or products.
  5. Perform additional tests and inspections required by Architect.
  6. Attend preconstruction meetings and progress meetings.
  7. Submit reports of all tests/inspections specified.
- C. Limits on Testing/Inspection Agency Authority:
  1. Agency may not release, revoke, alter, or enlarge on requirements of Contract Documents.
  2. Agency may not approve or accept any portion of the Work.
  3. Agency may not assume any duties of Contractor.
  4. Agency has no authority to stop the Work.

- D. Contractor Responsibilities:
  - 1. Deliver to agency at designated location, adequate samples of materials proposed to be used that require testing, along with proposed mix designs.
  - 2. Cooperate with laboratory personnel, and provide access to the Work and to manufacturers' facilities.
  - 3. Provide incidental labor and facilities:
    - a. To provide access to Work to be tested/inspected.
    - b. To obtain and handle samples at the site or at source of Products to be tested/inspected.
    - c. To facilitate tests/inspections.
    - d. To provide storage and curing of test samples.
  - 4. Notify Architect and laboratory 24 hours prior to expected time for operations requiring testing/inspection services.
  - 5. Employ services of an independent qualified testing laboratory and pay for additional samples, tests, and inspections required by Contractor beyond specified requirements.
  - 6. Arrange with Owner's agency and pay for additional samples, tests, and inspections required by Contractor beyond specified requirements.
- E. Re-testing required because of non-compliance with specified requirements shall be performed by the same agency on instructions by Architect.
- F. Re-testing required because of non-compliance with specified requirements shall be paid for by Contractor.

### **3.05 MANUFACTURERS' FIELD SERVICES**

- A. When specified in individual specification sections, require material or product suppliers or manufacturers to provide qualified staff personnel to observe site conditions, conditions of surfaces and installation, quality of workmanship, start-up of equipment, test, adjust, and balance equipment as applicable, and to initiate instructions when necessary.
- B. Report observations and site decisions or instructions given to applicators or installers that are supplemental or contrary to manufacturers' written instructions.

### **3.06 DEFECT ASSESSMENT**

- A. Replace Work or portions of the Work not complying with specified requirements.
- B. If, in the opinion of Architect, it is not practical to remove and replace the work, Architect will direct an appropriate remedy or adjust payment.

**END OF SECTION 01 4000**

This page intentionally left blank

**SECTION 01 5000**  
**TEMPORARY FACILITIES AND CONTROLS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Temporary utilities.
- B. Temporary telecommunications services.
- C. Temporary sanitary facilities.
- D. Temporary Controls: Barriers, enclosures, and fencing.
- E. Security requirements.
- F. Vehicular access and parking.
- G. Waste removal facilities and services.
- H. Project identification sign.
- I. Field offices.

**1.02 REFERENCE STANDARDS**

- A. ASTM E90 - Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements; 2023.

**1.03 TEMPORARY UTILITIES**

- A. Provide and pay for all electrical power, lighting, water, heating and cooling, and ventilation required for construction purposes.

**1.04 TELECOMMUNICATIONS SERVICES**

- A. Provide, maintain, and pay for telecommunications services to field office at time of project mobilization.

**1.05 TEMPORARY SANITARY FACILITIES**

- A. Provide and maintain required facilities and enclosures. Provide at time of project mobilization.
- B. Maintain daily in clean and sanitary condition.

**1.06 BARRIERS**

**1.07 FENCING**

- A. Provide 6 foot high fence around construction site; equip with vehicular and pedestrian gates with locks.

**1.08 INTERIOR ENCLOSURES**

- A. Provide temporary partitions and ceilings as indicated to separate work areas from Owner-occupied areas, to prevent penetration of dust and moisture into Owner-occupied areas, and to prevent damage to existing materials and equipment.
- B. Construction: Framing and gypsum board sheet materials with closed joints and sealed edges at intersections with existing surfaces:
  1. STC rating of 50 in accordance with ASTM E90.
- C. Paint surfaces exposed to view from Owner-occupied areas.
- D. Maintain emergency egress. Coordinate with Authorities Having Jurisdiction.

**1.09 SECURITY**

- A. Coordinate with Owner's security program.

**1.10 VEHICULAR ACCESS AND PARKING**

- A. Coordinate access and haul routes with governing authorities and Owner.
- B. Provide and maintain access to fire hydrants, free of obstructions.

- C. Provide means of removing mud from vehicle wheels before entering streets.
- D. Provide temporary parking areas to accommodate construction personnel. When site space is not adequate, provide additional off-site parking.

#### **1.11 WASTE REMOVAL**

- A. Provide waste removal facilities and services as required to maintain the site in clean and orderly condition.
- B. If materials to be recycled or re-used on the project must be stored on-site, provide suitable non-combustible containers; locate containers holding flammable material outside the structure unless otherwise approved by the authorities having jurisdiction.
- C. Open free-fall chutes are not permitted. Terminate closed chutes into appropriate containers with lids.

#### **1.12 PROJECT IDENTIFICATION**

- A. Provide project identification sign of design, construction, and location approved by Owner.
- B. No other signs are allowed without Owner permission except those required by law.

#### **1.13 FIELD OFFICES**

- A. Office: Weathertight, with lighting, electrical outlets, heating, cooling equipment, and equipped with sturdy furniture, drawing rack, and drawing display table.
- B. Locate offices a minimum distance of 30 feet from existing and new structures.

#### **1.14 REMOVAL OF UTILITIES, FACILITIES, AND CONTROLS**

- A. Remove temporary utilities, equipment, facilities, materials, prior to Date of Substantial Completion inspection.
- B. Remove underground installations to a minimum depth of 2 feet. Grade site as indicated.
- C. Clean and repair damage caused by installation or use of temporary work.

#### **PART 2 PRODUCTS - NOT USED**

#### **PART 3 EXECUTION - NOT USED**

**END OF SECTION 01 5000**

**SECTION 01 6000**  
**PRODUCT REQUIREMENTS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. General product requirements.
- B. Transportation, handling, storage and protection.
- C. Product option requirements.
- D. Substitution limitations.
- E. Procedures for Owner-supplied products.
- F. Maintenance materials, including extra materials, spare parts, tools, and software.

**1.02 RELATED REQUIREMENTS**

- A. Section 01 2500 - Substitution Procedures: Substitutions made during procurement and/or construction phases.
- B. Section 01 4000 - Quality Requirements: Product quality monitoring.
- C. Section 01 6116 - Volatile Organic Compound (VOC) Content Restrictions: Requirements for VOC-restricted product categories.
- D. Section 01 7419 - Construction Waste Management and Disposal: Waste disposal requirements potentially affecting product selection, packaging and substitutions.

**1.03 REFERENCE STANDARDS**

- A. C2C (DIR) - C2C Certified Products Registry; Cradle to Cradle Products Innovation Institute; Current Edition.
- B. CAL (CDPH SM) - Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers Version 1.2; 2017.
- C. CAN/CSA Z809 - Sustainable Forest Management; 2016 (Reaffirmed 2021).
- D. EN 15804 - Sustainability of Construction Works - Environmental Product Declarations - Core Rules for the Product Category of Construction Products; 2022 (Corrigendum 2021).
- E. GreenScreen (LIST) - GreenScreen for Safer Chemicals List Translator; Clean Production Action; Current Edition.
- F. GreenScreen (METH) - GreenScreen for Safer Chemicals Method v1.2; Clean Production Action; Current Edition.
- G. ISO 14044 - Environmental Management - Life Cycle Assessment - Requirements and Guidelines; 2006, with Amendment (2020).
- H. ISO 21930 - Sustainability in Buildings and Civil Engineering Works — Core Rules for Environmental Product Declarations of Construction Products and Services; 2017.
- I. NSF 332 - Sustainability Assessment for Resilient Floor Coverings; 2022.

**1.04 SUBMITTALS**

- A. Product Data Submittals: Submit manufacturer's standard published data. Mark each copy to identify applicable products, models, options, and other data. Supplement manufacturers' standard data to provide information specific to this Project.
- B. Shop Drawing Submittals: Prepared specifically for this Project; indicate utility and electrical characteristics, utility connection requirements, and location of utility outlets for service for functional equipment and appliances.
- C. Sample Submittals: Illustrate functional and aesthetic characteristics of the product, with integral parts and attachment devices. Coordinate sample submittals for interfacing work.

1. For selection from standard finishes, submit samples of the full range of the manufacturer's standard colors, textures, and patterns.

## **1.05 QUALITY ASSURANCE**

- A. Cradle-to-Cradle Certified: End use product certified Cradle-to-Cradle v2 Basic or Cradle-to-Cradle v3 Bronze, minimum, as evidenced by C2C (DIR).
- B. GreenScreen Chemical Hazard Analysis: Ingredients of 100 parts-per-million or greater evaluated using GreenScreen (METH).
  1. Good: GreenScreen (LIST) evaluation to identify Benchmark 1 hazards; a Health Product Declaration includes this information.
  2. Better: GreenScreen Full Assessment.
  3. Best: GreenScreen Full Assessment by GreenScreen Licensed Profiler.
  4. Acceptable Evidence: GreenScreen report.
- C. Health Product Declarations (HPD): Complete, published declaration with full disclosure of known hazards, prepared using one of the HPDC (HPD-OLT) online tools.
- D. Rapidly Renewable Materials: Made from agricultural products that are typically harvested within a 10-year or shorter cycle.
- E. Reused Products: Materials and equipment previously used in this or other construction, salvaged and refurbished as specified.
  1. Wood fabricated from timber abandoned in transit after harvesting is considered reused, not recycled.
  2. Acceptable Evidence: Information about the origin or source, from Contractor or supplier.
- F. Sustainably Harvested Wood: Solid wood, wood chips, and wood fiber certified or labeled by an organization accredited by one of the following:
  1. The Forest Stewardship Council, The Principles for Natural Forest Management; for Canada visit <http://www.fsccanada.org>, for the USA visit <http://www.fscus.org>.
  2. Acceptable Evidence: Copies of invoices bearing the certifying organization's certification numbers.

## **PART 2 PRODUCTS**

### **2.01 NEW PRODUCTS**

- A. Provide new products unless specifically required or permitted by Contract Documents.
- B. See Section 01 4000 - Quality Requirements, for additional source quality control requirements.
- C. Use of products having any of the following characteristics is not permitted:
  1. Made using or containing CFC's or HCFC's.
  2. Made of wood from newly cut old growth timber.
  3. Containing lead, cadmium, or asbestos.
- D. Where other criteria are met, Contractor shall give preference to products that:
  1. If used on interior, have lower emissions, as defined in Section 01 6116.
  2. If wet-applied, have lower VOC content, as defined in Section 01 6116.
  3. Are extracted, harvested, and/or manufactured closer to the location of the project.
  4. Have longer documented life span under normal use.
  5. Result in less construction waste. See Section 01 7419
  6. Are made of vegetable materials that are rapidly renewable.
  7. Are made of recycled materials.
  8. If made of wood, are made of sustainably harvested wood, wood chips, or wood fiber.
  9. If bio-based, other than wood, are or are made of Sustainable Agriculture Network certified products.
  10. Are Cradle-to-Cradle Certified.
  11. Have a published Environmental Product Declaration (EPD).
  12. Have a published Health Product Declaration (HPD).

13. Have a published GreenScreen Chemical Hazard Analysis.
14. Have a published Manufacturer's Inventory of Chemical Content.

## **2.02 PRODUCT OPTIONS**

- A. Products Specified by Reference Standards or by Description Only: Use any product meeting those standards or description.
- B. Products Specified by Naming One or More Manufacturers: Use a product of one of the manufacturers named and meeting specifications, no options or substitutions allowed.
- C. Products Specified by Naming One or More Manufacturers with a Provision for Substitutions: Submit a request for substitution for any manufacturer not named.

## **2.03 MAINTENANCE MATERIALS**

- A. Furnish extra materials, spare parts, tools, and software of types and in quantities specified in individual specification sections.
- B. Deliver and place in location as directed; obtain receipt prior to final payment.

## **PART 3 EXECUTION**

### **3.01 SUBSTITUTION LIMITATIONS**

- A. See Section 01 2500 - Substitution Procedures.

### **3.02 OWNER-SUPPLIED PRODUCTS**

- A. Owner's Responsibilities:
  1. Arrange for and deliver Owner reviewed shop drawings, product data, and samples, to Contractor.
  2. Arrange and pay for product delivery to site.
  3. On delivery, inspect products jointly with Contractor.
  4. Submit claims for transportation damage and replace damaged, defective, or deficient items.
  5. Arrange for manufacturers' warranties, inspections, and service.
- B. Contractor's Responsibilities:
  1. Review Owner reviewed shop drawings, product data, and samples.
  2. Receive and unload products at site; inspect for completeness or damage jointly with Owner.
  3. Handle, store, install and finish products.
  4. Repair or replace items damaged after receipt.

### **3.03 TRANSPORTATION AND HANDLING**

- A. Package products for shipment in manner to prevent damage; for equipment, package to avoid loss of factory calibration.
- B. If special precautions are required, attach instructions prominently and legibly on outside of packaging.
- C. Coordinate schedule of product delivery to designated prepared areas in order to minimize site storage time and potential damage to stored materials.
- D. Transport and handle products in accordance with manufacturer's instructions.
- E. Transport materials in covered trucks to prevent contamination of product and littering of surrounding areas.
- F. Promptly inspect shipments to ensure that products comply with requirements, quantities are correct, and products are undamaged.
- G. Provide equipment and personnel to handle products by methods to prevent soiling, disfigurement, or damage, and to minimize handling.
- H. Arrange for the return of packing materials, such as wood pallets, where economically feasible.

### **3.04 STORAGE AND PROTECTION**

- A. Provide protection of stored materials and products against theft, casualty, or deterioration.
- B. Designate receiving/storage areas for incoming products so that they are delivered according to installation schedule and placed convenient to work area in order to minimize waste due to excessive materials handling and misapplication. See Section 01 7419.
  - 1. Structural Loading Limitations: Handle and store products and materials so as not to exceed static and dynamic load-bearing capacities of project floor and roof areas.
- C. Store and protect products in accordance with manufacturers' instructions.
- D. Store with seals and labels intact and legible.
- E. Arrange storage of materials and products to allow for visual inspection for the purpose of determination of quantities, amounts, and unit counts.
- F. Store sensitive products in weathertight, climate-controlled enclosures in an environment favorable to product.
- G. For exterior storage of fabricated products, place on sloped supports above ground.
- H. Provide off-site storage and protection when site does not permit on-site storage or protection.
- I. Protect products from damage or deterioration due to construction operations, weather, precipitation, humidity, temperature, sunlight and ultraviolet light, dirt, dust, and other contaminants.
- J. Comply with manufacturer's warranty conditions, if any.
- K. Do not store products directly on the ground.
- L. Cover products subject to deterioration with impervious sheet covering. Provide ventilation to prevent condensation and degradation of products.
- M. Store loose granular materials on solid flat surfaces in a well-drained area. Prevent mixing with foreign matter.
- N. Prevent contact with material that may cause corrosion, discoloration, or staining.
- O. Provide equipment and personnel to store products by methods to prevent soiling, disfigurement, or damage.
- P. Arrange storage of products to permit access for inspection. Periodically inspect to verify products are undamaged and are maintained in acceptable condition.

**END OF SECTION 01 6000**

**SECTION 01 7000**  
**EXECUTION AND CLOSEOUT REQUIREMENTS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Examination, preparation, and general installation procedures.
- B. Requirements for alterations work, including selective demolition, except removal, disposal, and/or remediation of hazardous materials and toxic substances.
- C. Pre-installation meetings.
- D. Cutting and patching.
- E. Surveying for laying out the work.
- F. Cleaning and protection.
- G. Starting of systems and equipment.
- H. Demonstration and instruction of Owner personnel.
- I. Closeout procedures, including Contractor's Correction Punch List, except payment procedures.
- J. General requirements for maintenance service.

**1.02 RELATED REQUIREMENTS**

- A. Section 01 3000 - Administrative Requirements: Submittals procedures, Electronic document submittal service.
- B. Section 01 4000 - Quality Requirements: Testing and inspection procedures.
- C. Section 01 5000 - Temporary Facilities and Controls: Temporary exterior enclosures.
- D. Section 01 5000 - Temporary Facilities and Controls: Temporary interior partitions.
- E. Section 01 5100 - Temporary Utilities: Temporary heating, cooling, and ventilating facilities.
- F. Section 01 5713 - Temporary Erosion and Sediment Control: Additional erosion and sedimentation control requirements.
- G. Section 01 7610 - Temporary Protective Coverings: Materials for protection of installed work.
- H. Section 01 7800 - Closeout Submittals: Project record documents, operation and maintenance data, warranties, and bonds.
- I. Section 01 7900 - Demonstration and Training: Demonstration of products and systems to be commissioned and where indicated in specific specification sections
- J. Section 07 8400 - Firestopping.

**1.03 REFERENCE STANDARDS**

- A. NFPA 241 - Standard for Safeguarding Construction, Alteration, and Demolition Operations; 2022, with Errata (2021).

**1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Survey work: Submit name, address, and telephone number of Surveyor before starting survey work.
  - 1. On request, submit documentation verifying accuracy of survey work.
  - 2. Submit a copy of site drawing signed by the Land Surveyor, that the elevations and locations of the work are in compliance with Contract Documents.
  - 3. Submit surveys and survey logs for the project record.
- C. Cutting and Patching: Submit written request in advance of cutting or alteration that affects:
  - 1. Structural integrity of any element of Project.

2. Integrity of weather exposed or moisture resistant element.
3. Efficiency, maintenance, or safety of any operational element.
4. Visual qualities of sight exposed elements.
5. Work of Owner or separate Contractor.

D. Project Record Documents: Accurately record actual locations of capped and active utilities.

## **1.05 QUALIFICATIONS**

- A. For demolition work, employ a firm specializing in the type of work required.
  1. Minimum of \_\_\_\_ years of documented experience.
- B. For surveying work, employ a land surveyor registered in the State in which the Project is located and acceptable to Architect. Submit evidence of surveyor's Errors and Omissions insurance coverage in the form of an Insurance Certificate. Employ only individual(s) trained and experienced in collecting and recording accurate data relevant to ongoing construction activities,

## **1.06 PROJECT CONDITIONS**

- A. Use of explosives is not permitted.
- B. Grade site to drain. Maintain excavations free of water. Provide, operate, and maintain pumping equipment.
- C. Protect site from puddling or running water. Provide water barriers as required to protect site from soil erosion.
- D. Perform dewatering activities, as required, for the duration of the project.
- E. Ventilate enclosed areas to assist cure of materials, to dissipate humidity, and to prevent accumulation of dust, fumes, vapors, or gases.
- F. Dust Control: Execute work by methods to minimize raising dust from construction operations. Provide positive means to prevent air-borne dust from dispersing into atmosphere and over adjacent property.
  1. Provide dust-proof enclosures to prevent entry of dust generated outdoors.
- G. Erosion and Sediment Control: Plan and execute work by methods to control surface drainage from cuts and fills, from borrow and waste disposal areas. Prevent erosion and sedimentation.
- H. Noise Control: Provide methods, means, and facilities to minimize noise produced by construction operations.
  1. Outdoors: Limit conduct of especially noisy exterior work to the hours of 8 am to 5 pm.
  2. Indoors: Limit conduct of especially noisy interior work to 8 am to 5 pm.
- I. Pest and Rodent Control: Provide methods, means, and facilities to prevent pests and insects from damaging the work.
- J. Rodent Control: Provide methods, means, and facilities to prevent rodents from accessing or invading premises.
- K. Pollution Control: Provide methods, means, and facilities to prevent contamination of soil, water, and atmosphere from discharge of noxious, toxic substances, and pollutants produced by construction operations. Comply with federal, state, and local regulations.

## **1.07 COORDINATION**

- A. Coordinate scheduling, submittals, and work of the various sections of the Project Manual to ensure efficient and orderly sequence of installation of interdependent construction elements, with provisions for accommodating items installed later.
- B. Notify affected utility companies and comply with their requirements.
- C. Verify that utility requirements and characteristics of new operating equipment are compatible with building utilities. Coordinate work of various sections having interdependent responsibilities for installing, connecting to, and placing in service, such equipment.

- D. Coordinate space requirements, supports, and installation of mechanical and electrical work that are indicated diagrammatically on drawings. Follow routing indicated for pipes, ducts, and conduit, as closely as practicable; place runs parallel with lines of building. Utilize spaces efficiently to maximize accessibility for other installations, for maintenance, and for repairs.
- E. In finished areas except as otherwise indicated, conceal pipes, ducts, and wiring within the construction. Coordinate locations of fixtures and outlets with finish elements.
- F. Coordinate completion and clean-up of work of separate sections.
- G. After Owner occupancy of premises, coordinate access to site for correction of defective work and work not in accordance with Contract Documents, to minimize disruption of Owner's activities.

## **PART 2 PRODUCTS**

### **2.01 PATCHING MATERIALS**

- A. New Materials: As specified in product sections; match existing products and work for patching and extending work.
- B. Type and Quality of Existing Products: Determine by inspecting and testing products where necessary, referring to existing work as a standard.
- C. Product Substitution: For any proposed change in materials, submit request for substitution described in Section 01 6000 - Product Requirements.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify that existing site conditions and substrate surfaces are acceptable for subsequent work. Start of work means acceptance of existing conditions.
- B. Verify that existing substrate is capable of structural support or attachment of new work being applied or attached.
- C. Examine and verify specific conditions described in individual specification sections.
- D. Take field measurements before confirming product orders or beginning fabrication, to minimize waste due to over-ordering or misfabrication.
- E. Verify that utility services are available, of the correct characteristics, and in the correct locations.
- F. Prior to Cutting: Examine existing conditions prior to commencing work, including elements subject to damage or movement during cutting and patching. After uncovering existing work, assess conditions affecting performance of work. Beginning of cutting or patching means acceptance of existing conditions.

### **3.02 PREPARATION**

- A. Clean substrate surfaces prior to applying next material or substance.
- B. Seal cracks or openings of substrate prior to applying next material or substance.
- C. Apply manufacturer required or recommended substrate primer, sealer, or conditioner prior to applying any new material or substance in contact or bond.

### **3.03 PREINSTALLATION MEETINGS**

- A. When required in individual specification sections, convene a preinstallation meeting at the site prior to commencing work of the section.
- B. Require attendance of parties directly affecting, or affected by, work of the specific section.
- C. Notify Architect (7) seven days in advance of meeting date.
- D. Prepare agenda and preside at meeting:
  - 1. Review conditions of examination, preparation and installation procedures.
  - 2. Review coordination with related work.

- E. Record minutes and distribute copies within two days after meeting to participants, with two copies to Architect, Owner, participants, and those affected by decisions made.

### **3.04 LAYING OUT THE WORK**

- A. Verify locations of survey control points prior to starting work.
- B. Promptly notify Architect of any discrepancies discovered.
- C. Contractor shall locate and protect survey control and reference points.
- D. Protect survey control points prior to starting site work; preserve permanent reference points during construction.
- E. Promptly report to Architect the loss or destruction of any reference point or relocation required because of changes in grades or other reasons.
- F. Replace dislocated survey control points based on original survey control. Make no changes without prior written notice to Architect.
- G. Utilize recognized engineering survey practices.
- H. Establish elevations, lines and levels. Locate and lay out by instrumentation and similar appropriate means:
  - 1. Site improvements including pavements; stakes for grading, fill and topsoil placement; utility locations, slopes, and invert elevations.
  - 2. Grid or axis for structures.
  - 3. Building foundation, column locations, ground floor elevations.
  - 4. Controlling lines and levels required for mechanical and electrical trades.
- I. Periodically verify layouts by same means.
- J. Maintain a complete and accurate log of control and survey work as it progresses.

### **3.05 GENERAL INSTALLATION REQUIREMENTS**

- A. Install products as specified in individual sections, in accordance with manufacturer's instructions and recommendations, and so as to avoid waste due to necessity for replacement.
- B. Make vertical elements plumb and horizontal elements level, unless otherwise indicated.
- C. Install equipment and fittings plumb and level, neatly aligned with adjacent vertical and horizontal lines, unless otherwise indicated.
- D. Make consistent texture on surfaces, with seamless transitions, unless otherwise indicated.
- E. Make neat transitions between different surfaces, maintaining texture and appearance.

### **3.06 ALTERATIONS**

### **3.07 CUTTING AND PATCHING**

- A. Whenever possible, execute the work by methods that avoid cutting or patching.
- B. See Alterations article above for additional requirements.
- C. Perform whatever cutting and patching is necessary to:
  - 1. Complete the work.
  - 2. Fit products together to integrate with other work.
  - 3. Provide openings for penetration of mechanical, electrical, and other services.
  - 4. Match work that has been cut to adjacent work.
  - 5. Repair areas adjacent to cuts to required condition.
  - 6. Repair new work damaged by subsequent work.
  - 7. Remove samples of installed work for testing when requested.
  - 8. Remove and replace defective and non-complying work.
- D. Execute work by methods that avoid damage to other work and that will provide appropriate surfaces to receive patching and finishing.

- E. Employ original installer to perform cutting for weather exposed and moisture resistant elements, and sight exposed surfaces.
- F. Cut rigid materials using masonry saw or core drill. Pneumatic tools not allowed without prior approval.
- G. Restore work with new products in accordance with requirements of Contract Documents.
- H. Fit work air tight to pipes, sleeves, ducts, conduit, and other penetrations through surfaces.
- I. At penetrations of fire rated walls, partitions, ceiling, or floor construction, completely seal voids with fire rated material in accordance with Section 07 8400, to full thickness of the penetrated element.
- J. Patching:
  - 1. Finish patched surfaces to match finish that existed prior to patching. On continuous surfaces, refinish to nearest intersection or natural break. For an assembly, refinish entire unit.
  - 2. Match color, texture, and appearance.
  - 3. Repair patched surfaces that are damaged, lifted, discolored, or showing other imperfections due to patching work. If defects are due to condition of substrate, repair substrate prior to repairing finish.

### **3.08 PROGRESS CLEANING**

- A. Maintain areas free of waste materials, debris, and rubbish. Maintain site in a clean and orderly condition.
- B. Remove debris and rubbish from pipe chases, plenums, attics, crawl spaces, and other closed or remote spaces, prior to enclosing the space.
- C. Broom and vacuum clean interior areas prior to start of surface finishing, and continue cleaning to eliminate dust.
- D. Collect and remove waste materials, debris, and trash/rubbish from site periodically and dispose off-site; do not burn or bury.

### **3.09 PROTECTION OF INSTALLED WORK**

- A. Protect installed work from damage by construction operations.
- B. Provide special protection where specified in individual specification sections.
- C. Provide temporary and removable protection for installed products. Control activity in immediate work area to prevent damage.
- D. Provide protective coverings at walls, projections, jambs, sills, and soffits of openings.
- E. Protect finished floors, stairs, and other surfaces from traffic, dirt, wear, damage, or movement of heavy objects, by protecting with durable sheet materials.
- F. Protect work from spilled liquids. If work is exposed to spilled liquids, immediately remove protective coverings, dry out work, and replace protective coverings.
- G. Prohibit traffic or storage upon waterproofed or roofed surfaces. If traffic or activity is necessary, obtain recommendations for protection from waterproofing or roofing material manufacturer.
- H. Prohibit traffic from landscaped areas.
- I. Remove protective coverings when no longer needed; reuse or recycle coverings if possible.

### **3.10 SYSTEM STARTUP**

- A. Coordinate schedule for start-up of various equipment and systems.
- B. Notify Architect and Owner seven days prior to start-up of each item.
- C. Verify that each piece of equipment or system has been checked for proper lubrication, drive rotation, belt tension, control sequence, and for conditions that may cause damage.

- D. Verify tests, meter readings, and specified electrical characteristics agree with those required by the equipment or system manufacturer.
- E. Verify that wiring and support components for equipment are complete and tested.
- F. Execute start-up under supervision of applicable Contractor personnel and manufacturer's representative in accordance with manufacturers' instructions.
- G. When specified in individual specification Sections, require manufacturer to provide authorized representative to be present at site to inspect, check, and approve equipment or system installation prior to start-up, and to supervise placing equipment or system in operation.
- H. Submit a written report that equipment or system has been properly installed and is functioning correctly.

### **3.11 DEMONSTRATION AND INSTRUCTION**

- A. See Section 01 7900 - Demonstration and Training.

### **3.12 ADJUSTING**

- A. Adjust operating products and equipment to ensure smooth and unhindered operation.

### **3.13 FINAL CLEANING**

- A. Execute final cleaning prior to final project assessment.
  - 1. Clean areas to be occupied by Owner prior to final completion before Owner occupancy.
- B. Use cleaning materials that are nonhazardous.
- C. Clean interior and exterior glass, surfaces exposed to view; remove temporary labels, stains and foreign substances, polish transparent and glossy surfaces, vacuum carpeted and soft surfaces.
- D. Remove all labels that are not permanent. Do not paint or otherwise cover fire test labels or nameplates on mechanical and electrical equipment.
- E. Clean equipment and fixtures to a sanitary condition with cleaning materials appropriate to the surface and material being cleaned.
- F. Clean filters of operating equipment.
- G. Clean debris from roofs, gutters, downspouts, scuppers, overflow drains, area drains, and drainage systems.
- H. Clean site; sweep paved areas, rake clean landscaped surfaces.
- I. Remove waste, surplus materials, trash/rubbish, and construction facilities from the site; dispose of in legal manner; do not burn or bury.

### **3.14 CLOSEOUT PROCEDURES**

- A. Make submittals that are required by governing or other authorities.
  - 1. Provide copies to Architect and Owner.
- B. Accompany Project Coordinator on preliminary inspection to determine items to be listed for completion or correction in the Contractor's Correction Punch List for Contractor's Notice of Substantial Completion.
- C. Notify Architect when work is considered ready for Architect's Substantial Completion inspection.
- D. Submit written certification containing Contractor's Correction Punch List, that Contract Documents have been reviewed, work has been inspected, and that work is complete in accordance with Contract Documents and ready for Architect's Substantial Completion inspection.
- E. Conduct Substantial Completion inspection and create Final Correction Punch List containing Architect's and Contractor's comprehensive list of items identified to be completed or corrected and submit to Architect.

- F. Correct items of work listed in Final Correction Punch List and comply with requirements for access to Owner-occupied areas.
- G. Notify Architect when work is considered finally complete and ready for Architect's Substantial Completion final inspection.
- H. Complete items of work determined by Architect listed in executed Certificate of Substantial Completion.

### **3.15 MAINTENANCE**

- A. Provide service and maintenance of components indicated in specification sections.
- B. Maintenance Period: As indicated in specification sections or, if not indicated, not less than one year from the Date of Substantial Completion or the length of the specified warranty, whichever is longer.
- C. Examine system components at a frequency consistent with reliable operation. Clean, adjust, and lubricate as required.
- D. Include systematic examination, adjustment, and lubrication of components. Repair or replace parts whenever required. Use parts produced by the manufacturer of the original component.
- E. Maintenance service shall not be assigned or transferred to any agent or subcontractor without prior written consent of the Owner.

**END OF SECTION 01 7000**

This page intentionally left blank

**SECTION 01 7800**  
**CLOSEOUT SUBMITTALS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Project record documents.
- B. Operation and maintenance data.
- C. Warranties and bonds.

**1.02 RELATED REQUIREMENTS**

- A. Section 01 3000 - Administrative Requirements: Submittals procedures, shop drawings, product data, and samples.
- B. Section 01 7000 - Execution and Closeout Requirements: Contract closeout procedures.
- C. Individual Product Sections: Specific requirements for operation and maintenance data.
- D. Individual Product Sections: Warranties required for specific products or Work.

**1.03 SUBMITTALS**

- A. Project Record Documents: Submit documents to Architect with claim for final Application for Payment.
- B. Operation and Maintenance Data:
  1. Submit two copies of preliminary draft or proposed formats and outlines of contents before start of Work. Architect will review draft and return one copy with comments.
  2. For equipment, or component parts of equipment put into service during construction and operated by Owner, submit completed documents within ten days after acceptance.
  3. Submit one copy of completed documents 15 days prior to final inspection. This copy will be reviewed and returned after final inspection, with Architect comments. Revise content of all document sets as required prior to final submission.
  4. Submit two sets of revised final documents in final form within 10 days after final inspection.
- C. Warranties and Bonds:
  1. For equipment or component parts of equipment put into service during construction with Owner's permission, submit documents within 10 days after acceptance.
  2. Make other submittals within 10 days after Date of Substantial Completion, prior to final Application for Payment.
  3. For items of Work for which acceptance is delayed beyond Date of Substantial Completion, submit within 10 days after acceptance, listing the date of acceptance as the beginning of the warranty period.

**PART 2 PRODUCTS - NOT USED**

**PART 3 EXECUTION**

**3.01 PROJECT RECORD DOCUMENTS**

- A. Maintain on site one set of the following record documents; record actual revisions to the Work:
  1. Drawings.
  2. Specifications.
  3. Addenda.
  4. Change Orders and other modifications to the Contract.
  5. Reviewed shop drawings, product data, and samples.
  6. Manufacturer's instruction for assembly, installation, and adjusting.
- B. Ensure entries are complete and accurate, enabling future reference by Owner.
- C. Store record documents separate from documents used for construction.
- D. Record information concurrent with construction progress.

- E. Specifications: Legibly mark and record at each product section description of actual products installed, including the following:
  - 1. Manufacturer's name and product model and number.
  - 2. Product substitutions or alternates utilized.
  - 3. Changes made by Addenda and modifications.
- F. Record Drawings and Shop Drawings: Legibly mark each item to record actual construction including:
  - 1. Measured depths of foundations in relation to finish first floor datum.
  - 2. Measured horizontal and vertical locations of underground utilities and appurtenances, referenced to permanent surface improvements.
  - 3. Measured locations of internal utilities and appurtenances concealed in construction, referenced to visible and accessible features of the Work.
  - 4. Field changes of dimension and detail.
  - 5. Details not on original Contract drawings.

### **3.02 OPERATION AND MAINTENANCE DATA**

- A. Source Data: For each product or system, list names, addresses and telephone numbers of Subcontractors and suppliers, including local source of supplies and replacement parts.
- B. Product Data: Mark each sheet to clearly identify specific products and component parts, and data applicable to installation. Delete inapplicable information.
- C. Drawings: Supplement product data to illustrate relations of component parts of equipment and systems, to show control and flow diagrams. Do not use Project Record Documents as maintenance drawings.
- D. Typed Text: As required to supplement product data. Provide logical sequence of instructions for each procedure, incorporating manufacturer's instructions.

### **3.03 OPERATION AND MAINTENANCE DATA FOR MATERIALS AND FINISHES**

- A. For Each Product, Applied Material, and Finish:
  - 1. Product data, with catalog number, size, composition, and color and texture designations.
  - 2. Information for re-ordering custom manufactured products.
- B. Instructions for Care and Maintenance: Manufacturer's recommendations for cleaning agents and methods, precautions against detrimental cleaning agents and methods, and recommended schedule for cleaning and maintenance.
- C. Moisture protection and weather-exposed products: Include product data listing applicable reference standards, chemical composition, and details of installation. Provide recommendations for inspections, maintenance, and repair.
- D. Additional information as specified in individual product specification sections.
- E. Where additional instructions are required, beyond the manufacturer's standard printed instructions, have instructions prepared by personnel experienced in the operation and maintenance of the specific products.

### **3.04 OPERATION AND MAINTENANCE DATA FOR EQUIPMENT AND SYSTEMS**

- A. For Each Item of Equipment and Each System:
  - 1. Description of unit or system, and component parts.
  - 2. Identify function, normal operating characteristics, and limiting conditions.
  - 3. Include performance curves, with engineering data and tests.
  - 4. Complete nomenclature and model number of replaceable parts.
- B. Where additional instructions are required, beyond the manufacturer's standard printed instructions, have instructions prepared by personnel experienced in the operation and maintenance of the specific products.
- C. Panelboard Circuit Directories: Provide electrical service characteristics, controls, and communications; typed.

- D. Include color coded wiring diagrams as installed.
- E. Operating Procedures: Include start-up, break-in, and routine normal operating instructions and sequences. Include regulation, control, stopping, shut-down, and emergency instructions. Include summer, winter, and any special operating instructions.
- F. Maintenance Requirements: Include routine procedures and guide for preventative maintenance and trouble shooting; disassembly, repair, and reassembly instructions; and alignment, adjusting, balancing, and checking instructions.
  - 1. Include HVAC outdoor and exhaust air damper calibration strategy.
    - a. Include provisions which ensure that full closure of dampers can be achieved.
  - 2. Include Carbon Dioxide Monitoring Protocol.
  - 3. Include Carbon Monoxide Monitoring Protocol.
  - 4. Include Frost Mitigation Strategy for ventilation heat-recovery system.
- G. Provide servicing and lubrication schedule, and list of lubricants required.
- H. Include manufacturer's printed operation and maintenance instructions.
- I. Include sequence of operation by controls manufacturer.
- J. Provide original manufacturer's parts list, illustrations, assembly drawings, and diagrams required for maintenance.
- K. Provide control diagrams by controls manufacturer as installed.
- L. Provide Contractor's coordination drawings, with color coded piping diagrams as installed.
- M. Provide charts of valve tag numbers, with location and function of each valve, keyed to flow and control diagrams.
- N. Provide list of original manufacturer's spare parts, current prices, and recommended quantities to be maintained in storage.
- O. Include test and balancing reports.
- P. Additional Requirements: As specified in individual product specification sections.

### **3.05 ASSEMBLY OF OPERATION AND MAINTENANCE MANUALS**

- A. Assemble operation and maintenance data into durable manuals for Owner's personnel use, with data arranged in the same sequence as, and identified by, the specification sections.
- B. Where systems involve more than one specification section, provide separate tabbed divider for each system.
- C. Binders: Commercial quality, 8-1/2 by 11 inch three D side ring binders with durable plastic covers; 2 inch maximum ring size. When multiple binders are used, correlate data into related consistent groupings.
- D. Cover: Identify each binder with typed or printed title **OPERATION AND MAINTENANCE INSTRUCTIONS**; identify title of Project; identify subject matter of contents.
- E. Project Directory: Title and address of Project; names, addresses, and telephone numbers of Architect, Consultants, Contractor and subcontractors, with names of responsible parties.
- F. Tables of Contents: List every item separated by a divider, using the same identification as on the divider tab; where multiple volumes are required, include all volumes Tables of Contents in each volume, with the current volume clearly identified.
- G. Dividers: Provide tabbed dividers for each separate product and system; identify the contents on the divider tab; immediately following the divider tab include a description of product and major component parts of equipment.
- H. Text: Manufacturer's printed data, or typewritten data on 20 pound paper.
- I. Drawings: Provide with reinforced punched binder tab. Bind in with text; fold larger drawings to size of text pages.
- J. Arrangement of Contents: Organize each volume in parts as follows:

1. Project Directory.
2. Table of Contents, of all volumes, and of this volume.
3. Operation and Maintenance Data: Arranged by system, then by product category.
  - a. Source data.
  - b. Product data, shop drawings, and other submittals.
  - c. Operation and maintenance data.
  - d. Field quality control data.
  - e. Photocopies of warranties and bonds.
4. Design Data: To allow for addition of design data furnished by Architect or others, provide a tab labeled "Design Data" and provide a binder large enough to allow for insertion of at least 20 pages of typed text.

### **3.06 WARRANTIES AND BONDS**

- A. Obtain warranties and bonds, executed in duplicate by responsible Subcontractors, suppliers, and manufacturers, within 10 days after completion of the applicable item of work. Except for items put into use with Owner's permission, leave date of beginning of time of warranty until Date of Substantial completion is determined.
- B. Verify that documents are in proper form, contain full information, and are notarized.
- C. Co-execute submittals when required.
- D. Retain warranties and bonds until time specified for submittal.
- E. Manual: Bind in commercial quality 8-1/2 by 11 inch three D side ring binders with durable plastic covers.
- F. Cover: Identify each binder with typed or printed title WARRANTIES AND BONDS, with title of Project; name, address and telephone number of Contractor and equipment supplier; and name of responsible company principal.
- G. Table of Contents: Neatly typed, in the sequence of the Table of Contents of the Project Manual, with each item identified with the number and title of the specification section in which specified, and the name of product or work item.
- H. Separate each warranty or bond with index tab sheets keyed to the Table of Contents listing. Provide full information, using separate typed sheets as necessary. List Subcontractor, supplier, and manufacturer, with name, address, and telephone number of responsible principal.

**END OF SECTION 01 7800**

## **SECTION 02 4100 DEMOLITION**

### **PART 1 GENERAL**

#### **1.01 SECTION INCLUDES**

- A. Selective demolition of building elements for alteration purposes.

### **PART 3 EXECUTION**

#### **2.01 GENERAL PROCEDURES AND PROJECT CONDITIONS**

- A. Comply with applicable codes and regulations for demolition operations and safety of adjacent structures and the public.
  - 1. Obtain required permits.
  - 2. Take precautions to prevent catastrophic or uncontrolled collapse of structures to be removed; do not allow worker or public access within range of potential collapse of unstable structures.
  - 3. Provide, erect, and maintain temporary barriers and security devices.
  - 4. Conduct operations to minimize effects on and interference with adjacent structures and occupants.
  - 5. Do not close or obstruct roadways or sidewalks without permits from authority having jurisdiction.
  - 6. Conduct operations to minimize obstruction of public and private entrances and exits. Do not obstruct required exits at any time. Protect persons using entrances and exits from removal operations.
  - 7. Obtain written permission from owners of adjacent properties when demolition equipment will traverse, infringe upon, or limit access to their property.
- B. Do not begin removal until receipt of notification to proceed from Owner.
- C. Protect existing structures and other elements to remain in place and not removed.
  - 1. Provide bracing and shoring.
  - 2. Prevent movement or settlement of adjacent structures.
  - 3. Stop work immediately if adjacent structures appear to be in danger.

#### **2.02 SELECTIVE DEMOLITION FOR ALTERATIONS**

- A. Existing construction and utilities indicated on drawings are based on casual field observation and existing record documents only.
  - 1. Verify construction and utility arrangements are as indicated.
  - 2. Report discrepancies to Architect before disturbing existing installation.
  - 3. Beginning of demolition work constitutes acceptance of existing conditions that would be apparent upon examination prior to starting demolition.
- B. Protect existing work to remain.
  - 1. Prevent movement of structure. Provide shoring and bracing as required.
  - 2. Perform cutting to accomplish removal work neatly and as specified for cutting new work.
  - 3. Repair adjacent construction and finishes damaged during removal work.
  - 4. Patch to match new work.

#### **2.03 DEBRIS AND WASTE REMOVAL**

- A. Remove debris, junk, and trash from site.
- B. Leave site in clean condition, ready for subsequent work.
- C. Clean up spillage and wind-blown debris from public and private lands.

**END OF SECTION 02 4100**

This page intentionally left blank

## SECTION 06 1000 ROUGH CARPENTRY

### **PART 1 GENERAL**

#### **1.01 SECTION INCLUDES**

- A. Preservative treated wood materials.
- B. Fire retardant treated wood materials.
- C. Miscellaneous framing and sheathing.
- D. Communications and electrical room mounting boards.
- E. Concealed wood blocking, nailers, and supports.

#### **1.02 REFERENCE STANDARDS**

- A. ANSI A208.1 - American National Standard for Particleboard; 2022.
- B. ASTM A153/A153M - Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware; 2023.
- C. ASTM C557 - Standard Specification for Adhesives for Fastening Gypsum Wallboard to Wood Framing; 2003 (Reapproved 2017).
- D. ASTM D2898 - Standard Practice for Accelerated Weathering of Fire-Retardant-Treated Wood for Fire Testing; 2010 (Reapproved 2024).
- E. ASTM D3498 - Standard Specification for Adhesives for Field-Gluing Wood Structural Panels (Plywood or Oriented Strand Board) to Wood Based Floor System Framing; 2019a.
- F. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- G. AWPA U1 - Use Category System: User Specification for Treated Wood; 2025.
- H. PS 1 - Structural Plywood; 2023.
- I. PS 2 - Performance Standard for Wood Structural Panels; 2019.
- J. PS 20 - American Softwood Lumber Standard; 2025.

#### **1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Product Data: Provide technical data on wood preservative materials and application instructions.
- C. Structural Composite Lumber: Submit manufacturer's published structural data including span tables, marked to indicate which sizes and grades are being used; if structural composite lumber is being substituted for dimension lumber or timbers, submit grading agency structural tables marked for comparison.
- D. Manufacturer's Certificate: Certify that wood products supplied for rough carpentry meet or exceed specified requirements.
- E. Warranty Documentation: Submit manufacturer warranty and ensure that forms have been completed in Owner's name and registered with manufacturer.

#### **1.04 DELIVERY, STORAGE, AND HANDLING**

- A. General: Cover wood products to protect against moisture. Support stacked products to prevent deformation and to allow air circulation.
- B. Fire Retardant Treated Wood: Prevent exposure to precipitation during shipping, storage, and installation.

#### **1.05 WARRANTY**

- A. See Section 01 7800 - Closeout Submittals for additional warranty requirements.

B. Correct defective work within a two-year period commencing on Date of Substantial Completion.

## PART 2 PRODUCTS

### 2.01 GENERAL REQUIREMENTS

- A. Dimension Lumber: Comply with PS 20 and requirements of specified grading agencies.
  1. Species: Douglas Fir-Larch, unless otherwise indicated.
  2. If no species is specified, provide species graded by the agency specified; if no grading agency is specified, provide lumber graded by grading agency meeting the specified requirements.
  3. Grading Agency: Grading agency whose rules are approved by the Board of Review, American Lumber Standard Committee at [www.alsc.org](http://www.alsc.org), and who provides grading service for the species and grade specified; provide lumber stamped with grade mark unless otherwise indicated.
  4. Lumber of other species or grades is acceptable provided structural and appearance characteristics are equivalent to or better than products specified.
- B. Provide sustainably harvested wood; see Section 01 6000 - Product Requirements for requirements.
- C. Lumber salvaged from deconstruction or demolition of existing buildings or structures is permitted provided it is clean, denailed, and free of paint and finish materials, and other contamination; identify source.
- D. Lumber fabricated from recovered timber is permitted, unless otherwise noted, provided it meets the specified requirements for new lumber and is free of contamination; identify source.

### 2.02 CONSTRUCTION PANELS

- A. Communications and Electrical Room Mounting Boards: PS 1 A-D plywood, or medium density fiberboard; 3/4 inch thick; flame spread index of 25 or less, smoke developed index of 450 or less, when tested in accordance with ASTM E84.
  1. Fire-Retardant treated.
- B. Other Applications:
  1. Plywood Concealed From View But Located Within Exterior Enclosure: PS 1, C-C Plugged or better, Exterior grade.
  2. Plywood Exposed to View But Not Exposed to Weather: PS 1, A-C, or better.
  3. Other Locations: PS 1, C-D Plugged or better.
  4. Wood Structural Sheathing: Provide fire treated sheathing type required by indicated tested assembly.

### 2.03 ACCESSORIES

- A. Fasteners and Anchors:
  1. Metal and Finish: Hot-dipped galvanized steel complying with ASTM A153/A153M for high humidity and preservative-treated wood locations, unfinished steel elsewhere.
  2. Drywall Screws: Bugle head, hardened steel, power driven type, length three times thickness of sheathing.
    - a. Not allowed at exterior applications.
- B. Construction Adhesives: Adhesives complying with ASTM C557 or ASTM D3498.
- C. Water-Resistive Barrier: See Section 07 2500.

### 2.04 FACTORY WOOD TREATMENT

- A. Treated Lumber and Plywood: Comply with requirements of AWPA U1 - Use Category System for wood treatments determined by use categories, expected service conditions, and specific applications.
  1. Fire-Retardant Treated Wood: Mark each piece of wood with producer's stamp indicating compliance with specified requirements.

2. Preservative-Treated Wood: Provide lumber and plywood marked or stamped by an ALSC-accredited testing agency, certifying level and type of treatment in accordance with AWPA standards.

B. Fire Retardant Treatment:

1. Exterior Type: AWPA U1, Category UCFB, Commodity Specification H, chemically treated and pressure impregnated; capable of providing a maximum flame spread index of 25 when tested in accordance with ASTM E84, with no evidence of significant combustion when test is extended for an additional 20 minutes both before and after accelerated weathering test performed in accordance with ASTM D2898.
  - a. Kiln dry wood after treatment to a maximum moisture content of 19 percent for lumber and 15 percent for plywood.
  - b. Treat exterior rough carpentry items.
  - c. Do not use treated wood in direct contact with the ground.
2. Interior Type A: AWPA U1, Use Category UCFA, Commodity Specification H, low temperature (low hygroscopic) type, chemically treated and pressure impregnated; capable of providing a maximum flame spread index of 25 when tested in accordance with ASTM E84, with no evidence of significant combustion when test is extended for an additional 20 minutes.
  - a. Kiln dry wood after treatment to a maximum moisture content of 19 percent for lumber and 15 percent for plywood.
  - b. Treat rough carpentry items as indicated .
  - c. Do not use treated wood in applications exposed to weather or where the wood may become wet.

C. Preservative Treatment:

1. Preservative Pressure Treatment of Lumber Above Grade: AWPA U1, Use Category UC3B, Commodity Specification A using waterborne preservative.
  - a. Kiln dry lumber after treatment to maximum moisture content of 19 percent.
  - b. Treat lumber exposed to weather.
  - c. Treat lumber in contact with roofing, flashing, or waterproofing.
  - d. Treat lumber in contact with masonry or concrete.
  - e. Treat lumber less than 18 inches above grade.
2. Preservative Pressure Treatment of Plywood Above Grade: AWPA U1, Use Category UC2 and UC3B, Commodity Specification F using waterborne preservative.
  - a. Kiln dry plywood after treatment to maximum moisture content of 19 percent.
  - b. Treat plywood in contact with roofing, flashing, or waterproofing.
  - c. Treat plywood in contact with masonry or concrete.
  - d. Treat plywood less than 18 inches above grade.
3. Preservative Pressure Treatment of Lumber in Contact with Soil: AWPA U1, Use Category UC4A, Commodity Specification A using waterborne preservative.
  - a. Preservative for Field Application to Cut Surfaces: As recommended by manufacturer of factory treatment chemicals for brush-application in the field.
  - b. Restrictions: Do not use lumber or plywood treated with chromated copper arsenate (CCA) in exposed exterior applications subject to leaching.

### **PART 3 EXECUTION**

#### **3.01 INSTALLATION - GENERAL**

- A. Select material sizes to minimize waste.
- B. Reuse scrap to the greatest extent possible; clearly separate scrap for use on site as accessory components, including: shims, bracing, and blocking.
- C. Where treated wood is used on interior, provide temporary ventilation during and immediately after installation sufficient to remove indoor air contaminants.

### **3.02 BLOCKING, NAILERS, AND SUPPORTS**

- A. Provide framing and blocking members as indicated or as required to support finishes, fixtures, specialty items, and trim.
- B. In framed assemblies that have concealed spaces, provide solid wood fireblocking as required by applicable local code, to close concealed draft openings between floors and between top story and roof/attic space; other material acceptable to authorities having jurisdiction may be used in lieu of solid wood blocking.
- C. In metal stud walls, provide continuous blocking around door and window openings for anchorage of frames, securely attached to stud framing.
- D. In walls, provide blocking attached to studs as backing and support for wall-mounted items, unless item can be securely fastened to two or more studs or other method of support is explicitly indicated.
- E. Where ceiling-mounting is indicated, provide blocking and supplementary supports above ceiling, unless other method of support is explicitly indicated.
- F. Provide the following specific nonstructural framing and blocking:
  - 1. Cabinets and shelf supports.
  - 2. Wall brackets.
  - 3. Handrails.
  - 4. Grab bars.
  - 5. Towel and bath accessories.
  - 6. Wall-mounted door stops.
  - 7. Chalkboards and marker boards.
  - 8. Wall paneling and trim.
  - 9. Joints of rigid wall coverings that occur between studs.

### **3.03 INSTALLATION OF CONSTRUCTION PANELS**

- A. Communications and Electrical Room Mounting Boards: Secure with screws to studs with edges over firm bearing; space fasteners at maximum 24 inches on center on all edges and into studs in field of board.
  - 1. At fire-rated walls, install board over wall board indicated as part of the fire-rated assembly.
  - 2. Where boards are indicated as full floor-to-ceiling height, install with long edge of board parallel to studs.
  - 3. Install adjacent boards without gaps.
  - 4. Size: 48 by 96 inches, installed horizontally at ceiling height.

### **3.04 CLEANING**

- A. Waste Disposal: See Section 01 7419 - Construction Waste Management and Disposal.
  - 1. Comply with applicable regulations.
  - 2. Do not burn scrap on project site.
  - 3. Do not burn scraps that have been pressure treated.
  - 4. Do not send materials treated with pentachlorophenol, CCA, or ACA to co-generation facilities or "waste-to-energy" facilities.
- B. Do not leave wood, shavings, sawdust, etc. on the ground or buried in fill.
- C. Prevent sawdust and wood shavings from entering the storm drainage system.

**END OF SECTION 06 1000**

**SECTION 06 4100**  
**ARCHITECTURAL WOOD CASEWORK**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Specially fabricated cabinet units.
- B. Countertops.
- C. Cabinet hardware.
- D. Factory finishing.

**1.02 REFERENCE STANDARDS**

- A. AWI/AWMAC/WI (AWS) - Architectural Woodwork Standards, 2nd Edition; 2014, with Errata (2016).
- B. AWMAC/WI (NAAWS) - North American Architectural Woodwork Standards; 2021, with Errata.
- C. BHMA A156.9 - Cabinet Hardware; 2020.
- D. AWI/AWMAC/WI (AWS) - Architectural Woodwork Standards; 2009.
- E. BHMA A156.9 - American National Standard for Cabinet Hardware; Builders Hardware Manufacturers Association; 2010 (ANSI/BHMA A156.9).

**1.03 ADMINISTRATIVE REQUIREMENTS**

- A. Preinstallation Meeting: Convene a preinstallation meeting not less than one week before starting work of this section; require attendance by all affected installers.

**1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Shop Drawings: Indicate materials, component profiles, fastening methods, jointing details, and accessories.
  - 1. Scale of Drawings: 1-1/2 inch to 1 foot, minimum.
  - 2. Provide the information required by AWI/AWMAC/WI (AWS) or AWMAC/WI (NAAWS).
- C. Product Data: Provide data for hardware accessories.
- D. Samples: Submit actual samples of architectural cabinet construction, minimum 12 inches square, illustrating proposed cabinet, countertop, and shelf unit substrate and finish.
- E. Samples: Submit actual sample items of proposed pulls, hinges, shelf standards, and locksets, demonstrating hardware design, quality, and finish.

**1.05 QUALITY ASSURANCE**

- A. Fabricator Qualifications: Company specializing in fabricating the products specified in this section with minimum five years of documented experience.
  - 1. Company with at least one project in the past 10 years with value of woodwork within 20 percent of cost of woodwork for this Project.
  - 2. Accredited participant in the specified certification program prior to the commencement of fabrication and throughout the duration of the project.

**1.06 MOCK-UP**

- A. Provide mock-up of typical base cabinet, wall cabinet, and countertop, including hardware, finishes, and plumbing accessories.
- B. Mock-up may not remain as part of the Work.

**1.07 DELIVERY, STORAGE, AND HANDLING**

- A. Protect units from moisture damage.

## 1.08 FIELD CONDITIONS

- A. During and after installation of custom cabinets, maintain temperature and humidity conditions in building spaces at same levels planned for occupancy.

## PART 2 PRODUCTS

### 2.01 CABINETS

- A. Quality Standard: Premium Grade, in accordance with AWI/AWMAC/WI (AWS) or AWMAC/WI (NAAWS), unless noted otherwise.
- B. Cabinets:
  - 1. Finish - Exposed Exterior Surfaces: Decorative laminate.
  - 2. Finish - Exposed Interior Surfaces: Decorative laminate.
  - 3. Finish - Semi-Exposed Surfaces: Decorative laminate
  - 4. Finish - Concealed Surfaces: Manufacturer's option.
  - 5. Door and Drawer Front Edge Profiles: Square edge with thick applied band.
  - 6. Door and Drawer Front Retention Profiles: Fixed panel.
  - 7. Casework Construction Type: Type A - Frameless.
  - 8. Cabinet Design Series: As indicated on drawings.
  - 9. Adjustable Shelf Loading: 50 lbs. per sq. ft.
    - a. Deflection: L/144.
  - 10. Cabinet Style: Flush overlay.
  - 11. Drawer Side Construction: Multiple-dovetailed.
  - 12. Drawer Construction Technique: Dovetail joints.
  - 13. Drawer Material: Solid hardwood.

### 2.02 WOOD-BASED COMPONENTS

- A. Wood fabricated from old growth timber is not permitted.
- B. Substrate - Provide moisture resistant substrate under all laminates that are exposed to view.

### 2.03 LAMINATE MATERIALS

- A. Manufacturers:
  - 1. Formica Corporation: [www.formica.com/#sle](http://www.formica.com/#sle).
  - 2. Wilsonart: [www.wilsonart.com](http://www.wilsonart.com).
  - 3. Substitutions: See Section 01 6000 - Product Requirements.
- B. Provide specific types as indicated.
  - 1. Horizontal and Vertical Surfaces: HGS, 0.048 inch nominal thickness.

### 2.04 COUNTERTOPS

- A. Solid Surfacing Countertops: Solid surfacing sheet or plastic resin casting over continuous substrate.
  - 1. Flat Sheet Thickness: 1/2 inch, minimum.
  - 2. Solid Surfacing Sheet and Plastic Resin Castings: Complying with ISFA-2 and NEMA LD 3; acrylic or polyester resin, mineral filler, and pigments; homogenous, non-porous and capable of being worked and repaired using standard woodworking tools; no surface coating; color and pattern consistent throughout thickness.
    - a. Surface Burning Characteristics: Flame spread 25, maximum; smoke developed 450, maximum; when tested in accordance with ASTM E84.
    - b. Sinks and Bowls: Separate units for undercounter mounting or drop in sinks; minimum 3/4 inch wall thickness; comply with ANSI Z124.3.
    - c. Finish on Exposed Surfaces: Matte, gloss rating of 5 to 20.
    - d. Color and Pattern: As indicated on drawings.
    - e. Manufacturers:
      - 1) Dupont : [www.corian.com](http://www.corian.com).
      - 2) Formica Corporation : [www.formica.com](http://www.formica.com).

- 3) Wilsonart International, Inc : [www.wilsonart.com](http://www.wilsonart.com).
- 4) Substitutions: See Section 01 6000 - Product Requirements.
- 3. Other Components Thickness: 1/2 inch, minimum.
- 4. Exposed Edge Treatment: Built up to minimum 1-1/4 inch thick; square edge; use marine edge at sinks.
- 5. Back and End Splashes: Same sheet material, square top; minimum 4 inches high.
- 6. Skirts: As indicated on drawings.
- 7. Fabricate in accordance with AWI/AWMAC/WI (AWS) standards, Section 11 - Premium Grade.

## 2.05 ACCESSORIES

- A. Adhesive: Type recommended by fabricator to suit application.
- B. Fasteners: Size and type to suit application.
- C. Bolts, Nuts, Washers, Lags, Pins, and Screws: Of size and type to suit application; galvanized or chrome-plated finish in concealed locations and stainless steel or chrome-plated finish in exposed locations.
- D. Concealed Joint Fasteners: Threaded steel.
- E. Grommets: Standard plastic, painted metal, or rubber grommets for cut-outs, in color to match adjacent surface.
- F. Hardware: BHMA A156.9, types as recommended by fabricator for quality grade specified.
- G. Adjustable Shelf Supports: Standard side-mounted system using recessed metal shelf standards and coordinated self rests, satin chrome finish, for nominal 1 inch spacing adjustments.
- H. Drawer and Door Pulls: Refer to the drawings.
- I. Catches: Magnetic.
- J. Drawer Slides:
  - 1. Type: Extension types as indicated.
  - 2. Static Load Capacity: Commercial grade.
  - 3. Mounting: Side mounted.
  - 4. Stops: Integral type.
  - 5. Features: Provide self closing/stay closed type.
- K. Hinges: European style concealed self-closing type, steel with polished finish.

## 2.06 FABRICATION

- A. Assembly: Shop assemble cabinets for delivery to site in units easily handled and to permit passage through building openings.
- B. Edging: Fit shelves, doors, and exposed edges with specified edging. Do not use more than one piece for any single length.
- C. Fitting: When necessary to cut and fit on site, provide materials with ample allowance for cutting. Provide matching trim for scribing and site cutting.
- D. Plastic Laminate: Apply plastic laminate finish in full uninterrupted sheets consistent with manufactured sizes. Fit corners and joints hairline; secure with concealed fasteners. Slightly bevel arises. Locate counter butt joints minimum 2 feet from sink cut-outs.
  - 1. Apply laminate backing sheet to reverse side of plastic laminate finished surfaces.
  - 2. Cap exposed plastic laminate finish edges with material of same finish and pattern.
- E. Mechanically fasten back splash to countertops at 16 inches on center.
- F. Provide cutouts for plumbing fixtures. Verify locations of cutouts from on-site dimensions. Prime paint cut edges.
- G. Shop glaze glass materials using the Interior Dry method as specified in Section 08 8000.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify adequacy of backing and support framing.
- B. Verify location and sizes of utility rough-in associated with work of this section.

### **3.02 INSTALLATION**

- A. Set and secure custom cabinets in place, assuring that they are rigid, plumb, and level.
- B. Use fixture attachments in concealed locations for wall mounted components.
- C. Use concealed joint fasteners to align and secure adjoining cabinet units.
- D. Carefully scribe casework abutting other components, with maximum gaps of 1/32 inch. Do not use additional overlay trim for this purpose.
- E. Secure cabinets to floor using appropriate angles and anchorages.
- F. Countersink anchorage devices at exposed locations. Conceal with solid wood plugs of species to match surrounding wood; finish flush with surrounding surfaces.

### **3.03 ADJUSTING**

- A. Adjust installed work.

### **3.04 CLEANING**

- A. Clean casework, counters, shelves, hardware, fittings, and fixtures.

**END OF SECTION 06 4100**

**SECTION 06 8316**  
**FIBERGLASS REINFORCED PANELING**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Fiberglass reinforced plastic panels.
- B. Trim.

**1.02 REFERENCE STANDARDS**

- A. ASTM D2583 - Standard Test Method for Indentation Hardness of Rigid Plastics by Means of a Barcol Impressor; 2013a.
- B. ASTM D5319 - Standard Specification for Glass-Fiber Reinforced Polyester Wall and Ceiling Panels; 2022.
- C. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- D. FDA Food Code - Chapter 6 - Physical Facilities; Current Edition.

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data on specified products, describing physical and performance characteristics; including sizes, patterns and colors available; and installation instructions.
- C. Samples: Submit two samples 6" by 6" inch in size illustrating material and surface design of panels.

**PART 2 PRODUCTS**

**2.01 MANUFACTURERS**

- A. Fiberglass Reinforced Plastic Panels:
  - 1. Crane Composites, Inc: [www.cranecomposites.com/#sle](http://www.cranecomposites.com/#sle).
  - 2. Marlite, Inc: [www.marlite.com/#sle](http://www.marlite.com/#sle).
  - 3. Nudo Products, Inc: [www.nudo.com/#sle](http://www.nudo.com/#sle).
  - 4. Panolam Industries International, Inc: [www.panolam.com/#sle](http://www.panolam.com/#sle).
  - 5. Substitutions: See Section 01 6000 - Product Requirements.

**2.02 PANEL SYSTEMS**

- A. Wall Panels:
  - 1. Panel Size: 4 by 9 feet.
  - 2. Panel Thickness: 0.10 inch.
  - 3. Surface Design: match existing.
  - 4. Color: match existing.
  - 5. Attachment Method: Adhesive only, with trim and sealant in joints.

**2.03 MATERIALS**

- A. Panels: Fiberglass reinforced plastic (FRP), complying with ASTM D5319.
  - 1. Surface Burning Characteristics: Maximum flame spread index of 25 and smoke developed index of 450; when system tested in accordance with ASTM E84.
  - 2. Scratch Resistance: Barcol hardness score greater than 35, when tested in accordance with ASTM D2583.
  - 3. Surface Characteristics and Cleanability: Provide products that are smooth, durable, and easily cleanable, in compliance with FDA Food Code, Chapter 6 - Physical Facilities.
- B. Trim: Vinyl; color coordinating with panel.
- C. Sealant: Type recommended by panel manufacturer; white.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify existing conditions and substrate flatness before starting work.
- B. Verify that substrate conditions are ready to receive the work of this section.

### **3.02 INSTALLATION - WALLS**

- A. Install panels in accordance with manufacturer's instructions.
- B. Cut and drill panels with carbide tipped saw blades, drill bits, or snips.
- C. Apply adhesive to the back side of the panel using trowel as recommended by adhesive manufacturer.
- D. Apply panels to wall with seams plumb and pattern aligned with adjoining panels.
- E. Install panels with manufacturer's recommended gap for panel field and corner joints.
- F. Place trim on panel before fastening edges, as required.
- G. Fill channels in trim with sealant before attaching to panel.
- H. Install trim with adhesive and screws or nails, as required.
- I. Seal gaps at floor, ceiling, and between panels with applicable sealant to prevent moisture intrusion.
- J. Remove excess sealant after paneling is installed and prior to curing.

**END OF SECTION 06 8316**

## SECTION 07 7200 ROOF ACCESSORIES

### PART 1 GENERAL

#### 1.01 REFERENCE STANDARDS

#### 1.02 SUBMITTALS

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Product Data: Manufacturer's data sheets on each product to be used.
  - 1. Preparation instructions and recommendations.
  - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.
  - 4. Maintenance requirements.
- C. Shop Drawings: Submit detailed layout developed for this project and provide dimensioned location and number for each type of roof accessory.
- D. Warranty Documentation:
  - 1. Submit manufacturer warranty.
  - 2. Ensure that forms have been completed in Owner's name and registered with manufacturer.

#### 1.03 WARRANTY

- A. See Section 01 7800 - Closeout Submittals for additional warranty requirements.
- B. Extended Correction Period: Correct defective work within 5-year period commencing on Date of Substantial Completion.

### PART 2 PRODUCTS

#### 2.01 ROOF CURBS

- A. Roof Curbs Manufacturers:
  - 1. Active Ventilation Products, Inc; Insulated Roof Curbs: [www.roofvents.com/#sle](http://www.roofvents.com/#sle).
  - 2. AES Industries Inc; \_\_\_\_\_: [www.aescurb.com/#sle](http://www.aescurb.com/#sle).
  - 3. The Pate Company; \_\_\_\_\_: [www.patecurbs.com/#sle](http://www.patecurbs.com/#sle).
  - 4. LMCurbs; Roof Curbs: [www.lmcurbs.com/#sle](http://www.lmcurbs.com/#sle).
  - 5. MKT Metal Manufacturing; \_\_\_\_\_: [www.mktduct.com/#sle](http://www.mktduct.com/#sle).
- B. Roof Curbs Mounting Assemblies: Factory fabricated hollow sheet metal construction, internally reinforced, and capable of supporting superimposed live and dead loads and designated equipment load with fully mitered and sealed corner joints welded or mechanically fastened, and integral counterflashing with top and edges formed to shed water.
  - 1. Roof Curb Mounting Substrate: Curb substrate consists of standing seam metal roof panel system.
  - 2. Sheet Metal Material:
    - a. Aluminum: 0.080 inch minimum thickness, with 3003 alloy, and H14 temper.
  - 3. Fabricate curb bottom and mounting flanges for installation directly on metal roof panel system to match slope and configuration of system.
    - a. Extend side flange to next adjacent roof panel seam and comply with seam configurations and seal connection, providing at least 6 inch clearance between curb and metal roof panel flange allowing water to properly flow past curb.
    - b. Where side of curb aligns with metal roof panel flange, attach fasteners on upper slope of flange to curb connection allowing water to flow past below fasteners, and seal connection.
    - c. Maintain at least 12 inch clearance from curb, and lap upper curb flange on underside of down sloping metal roof panel, and seal connection.
    - d. Lap lower curb flange overtop of down sloping metal roof panel and seal connection.

- C. Roof Curb Caps: Square-type aluminum cap with weathertight seal when vent or equipment is not installed.
  - 1. Size: Field Verify.

## **PART 3 EXECUTION**

### **3.01 INSTALLATION**

- A. Install in accordance with manufacturer's instructions, in manner that maintains roofing system weather-tight integrity.

**END OF SECTION 07 7200**

## SECTION 07 9200 JOINT SEALANTS

### PART 1 GENERAL

#### 1.01 SECTION INCLUDES

- A. Nonsag gunnable joint sealants.
- B. Self-leveling pourable joint sealants.
- C. Joint backings and accessories.

#### 1.02 RELATED REQUIREMENTS

- A. Section 01 6116 - Volatile Organic Compound (VOC) Content Restrictions: Additional requirements for sealants and primers.
- B. Section 07 2500 - Weather Barriers: Sealants required in conjunction with water-resistive barriers.
- C. Section 07 8400 - Firestopping: Firestopping sealants.
- D. Section 07 9100 - Preformed Joint Seals: Precompressed foam, gaskets, and strip seals.
- E. Section 09 2116 - Gypsum Board Assemblies: Sealing acoustical and sound-rated walls and ceilings.
- F. Section 09 3000 - Tiling: Sealant between tile and plumbing fixtures and at junctions with other materials and changes in plane.

#### 1.03 REFERENCE STANDARDS

- A. ASTM C661 - Standard Test Method for Indentation Hardness of Elastomeric-Type Sealants by Means of a Durometer; 2015 (Reapproved 2022).
- B. ASTM C794 - Standard Test Method for Adhesion-in-Peel of Elastomeric Joint Sealants; 2018 (Reapproved 2022).
- C. ASTM C834 - Standard Specification for Latex Sealants; 2017 (Reapproved 2023).
- D. ASTM C881/C881M - Standard Specification for Epoxy-Resin-Base Bonding Systems for Concrete; 2020a.
- E. ASTM C919 - Standard Practice for Use of Sealants in Acoustical Applications; 2024.
- F. ASTM C920 - Standard Specification for Elastomeric Joint Sealants; 2018 (Reapproved 2024).
- G. ASTM C1087 - Standard Test Method for Determining Compatibility of Liquid-Applied Sealants with Accessories Used in Structural Glazing Systems; 2023.
- H. ASTM C1193 - Standard Guide for Use of Joint Sealants; 2016 (Reapproved 2023).
- I. ASTM C1248 - Standard Test Method for Staining of Porous Substrate by Joint Sealants; 2022.
- J. ASTM C1330 - Standard Specification for Cylindrical Sealant Backing for Use with Cold Liquid-Applied Sealants; 2023.
- K. ASTM C1521 - Standard Practice for Evaluating Adhesion of Installed Weatherproofing Sealant Joints; 2019 (Reapproved 2025).
- L. ASTM D2240 - Standard Test Method for Rubber Property--Durometer Hardness; 2015 (Reapproved 2021).
- M. ASTM D412 - Standard Test Methods for Vulcanized Rubber and Thermoplastic Elastomers--Tension; 2016 (Reapproved 2021).
- N. ASTM D695 - Standard Test Method for Compressive Properties of Rigid Plastics; 2023.
- O. SCAQMD 1168 - Adhesive and Sealant Applications; 1989, with Amendment (2022).

#### 1.04 SUBMITTALS

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.

- B. Product Data for Sealants: Submit manufacturer's technical data sheets for each product to be used, that includes the following.
  - 1. Physical characteristics, including movement capability, VOC content, hardness, cure time, and color availability.
  - 2. List of backing materials approved for use with the specific product.
  - 3. Substrates that product is known to satisfactorily adhere to and with which it is compatible.
  - 4. Substrates the product should not be used on.
  - 5. Substrates for which use of primer is required.
  - 6. Substrates for which laboratory adhesion and/or compatibility testing is required.
  - 7. Installation instructions, including precautions, limitations, and recommended backing materials and tools.
  - 8. Sample product warranty.
- C. Product Data for Accessory Products: Submit manufacturer's technical data sheet for each product to be used, including physical characteristics, installation instructions, and recommended tools.
- D. Color Cards for Selection: Where sealant color is not specified, submit manufacturer's color cards showing standard colors available for selection.
- E. Samples for Verification: Where custom sealant color is specified, obtain directions from Architect and submit at least two physical samples for verification of color of each required sealant.
- F. Joint-Sealant Schedule: Include the following information:
  - 1. Joint-sealant application, joint location, and designation.
    - a. Include name of adjacent material(s).
  - 2. Joint-sealant manufacturer and product name
  - 3. Joint-sealant formulation.
  - 4. Joint-sealant color.
  - 5. Provide drawing(s) or matrix to clearly indicate locations for each type sealant. Identify sealants as part of this Section and where included in the Work in another Section.
- G. Sustainable Design Documentation: For sealants and primers, submit VOC content and emissions documentation; see Section 01 6116.
- H. Preconstruction Laboratory Test Reports: Submit at least four weeks prior to start of installation.
- I. Installation Plan: Submit at least four weeks prior to start of installation.
- J. Preinstallation Field Adhesion Test Plan: Submit at least two weeks prior to start of installation.
- K. Field Quality Control Plan: Submit at least two weeks prior to start of installation.
- L. Preinstallation Field Adhesion Test Reports: Submit filled out Preinstallation Field Adhesion Test Reports log within 10 days after completion of tests; include bagged test samples and photographic records.
- M. Installation Log: Submit filled out log for each length or instance of sealant installed.
- N. Field Quality Control Log: Submit filled out log for each length or instance of sealant installed, within 10 days after completion of inspections/tests; include bagged test samples and photographic records, if any.

## 1.05 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum five years documented experience.
- B. Installer Qualifications: Company specializing in performing the work of this section and with at least three years of documented experience.
- C. Testing Agency Qualifications: Independent firm specializing in performing testing and inspections of the type specified in this section.

- D. Preconstruction Laboratory Testing: Arrange for sealant manufacturer(s) to test each combination of sealant, substrate, backing, and accessories.
  - 1. Adhesion Testing: In accordance with ASTM C794.
  - 2. Compatibility Testing: In accordance with ASTM C1087.
  - 3. Stain Testing: In accordance with ASTM C1248; required only for stone substrates.
  - 4. Allow sufficient time for testing to avoid delaying the work.
  - 5. Deliver to manufacturer sufficient samples for testing.
  - 6. Report manufacturer's recommended corrective measures, if any, including primers or techniques not indicated in product data submittals.
  - 7. Testing is not required if sealant manufacturer provides data showing previous testing, not older than 24 months, that shows satisfactory adhesion, lack of staining, and compatibility.
- E. Installation Plan: Include schedule of sealed joints, including the following.
  - 1. Method to be used to protect adjacent surfaces from sealant droppings and smears, with acknowledgement that some surfaces cannot be cleaned to like-new condition and therefore prevention is imperative.
  - 2. Installation Log Form: Include the following data fields, with known information filled out.
    - a. Unique identification of each length or instance of sealant installed.
    - b. Location on project.
    - c. Substrates.
    - d. Sealant used.
    - e. Stated movement capability of sealant.
    - f. Primer to be used, or indicate as "No primer" used.
    - g. Size and actual backing material used.
    - h. Date of installation.
    - i. Name of installer.
    - j. Actual joint width; provide space to indicate maximum and minimum width.
    - k. Actual joint depth to face of backing material at centerline of joint.
    - l. Air temperature.
- F. Preinstallation Field Adhesion Test Plan: Include destructive field adhesion testing of one sample of each combination of sealant type and substrate, except interior acrylic latex sealants, and include the following for each tested sample.
  - 1. Identification of testing agency.
  - 2. Name(s) of sealant manufacturers' field representatives who will be observing
  - 3. Preinstallation Field Adhesion Test Log Form: Include the following data fields, with known information filled out.
    - a. Substrate; if more than one type of substrate is involved in a single joint, provide two entries on form, for testing each sealant substrate side separately.
    - b. Test date.
    - c. Location on project.
    - d. Sealant used.
    - e. Stated movement capability of sealant.
    - f. Test method used.
    - g. Date of installation of field sample to be tested.
    - h. Date of test.
    - i. Copy of test method documents.
    - j. Age of sealant upon date of testing.
    - k. Test results, modeled after the sample form in the test method document.
    - l. Indicate use of photographic record of test.
- G. Field Quality Control Plan:
  - 1. Visual inspection of entire length of sealant joints.
  - 2. Non-destructive field adhesion testing of sealant joints, except interior acrylic latex sealants.

3. Destructive field adhesion testing of sealant joints, except interior acrylic latex sealant.
  - a. For each different sealant and substrate combination, allow for one test every 100 feet in the first 1000 linear feet, and one test per 1000 linear feet thereafter, or once per floor on each elevation.
  - b. If any failures occur in the first 1000 linear feet, continue testing at frequency of one test per 500 linear feet at no extra cost to Owner.
4. Field testing agency's qualifications.
5. Field Quality Control Log Form: Show same data fields as on Preinstallation Field Adhesion Test Log, with known information filled out and lines for multiple tests per sealant/substrate combinations; include visual inspection and specified field testing; allow for possibility that more tests than minimum specified may be necessary.

H. Field Adhesion Test Procedures:

1. Allow sealants to fully cure as recommended by manufacturer before testing.
2. Have a copy of the test method document available during tests.
3. Record the type of failure that occurred, other information required by test method, and the information required on the Field Quality Control Log.
4. When performing destructive tests, also inspect the opened joint for proper installation characteristics recommended by manufacturer, and report any deficiencies.
5. Deliver the samples removed during destructive tests in separate sealed plastic bags, identified with project, location, test date, and test results, to Owner.
6. If any combination of sealant type and substrate does not show evidence of minimum adhesion or shows cohesion failure before minimum adhesion, report results to Architect.

I. Non-Destructive Field Adhesion Test: Test for adhesion in accordance with ASTM C1521, using Nondestructive Spot Method.

1. Record results on Field Quality Control Log.
2. Repair failed portions of joints.

J. Destructive Field Adhesion Test: Test for adhesion in accordance with ASTM C1521, using Destructive Tail Procedure.

1. Sample: At least 18 inches long.
2. Minimum Elongation Without Adhesive Failure: Consider the tail at rest, not under any elongation stress; multiply the stated movement capability of the sealant in percent by two; then multiply 1 inch by that percentage; if adhesion failure occurs before the "1 inch mark" is that distance from the substrate, the test has failed.
3. If either adhesive or cohesive failure occurs prior to minimum elongation, take necessary measures to correct conditions and re-test; record each modification to products or installation procedures.
4. Record results on Field Quality Control Log.
5. Repair failed portions of joints.

K. Field Adhesion Tests of Joints: Test for adhesion using most appropriate method in accordance with ASTM C1521, or other applicable method as recommended by manufacturer.

## 1.06 WARRANTY

- A. See Section 01 7800 - Closeout Submittals for additional warranty requirements.
- B. Correct defective work within a five year period after Date of Substantial Completion.
- C. Warranty: Include coverage for installed sealants and accessories that fail to achieve watertight seal, exhibit loss of adhesion or cohesion, or do not cure.

## PART 2 PRODUCTS

### 2.01 MANUFACTURERS

- A. Non-Sag Sealants: Permits application in joints on vertical surfaces without sagging or slumping.
  1. Dow: [www.dow.com/#sle](http://www.dow.com/#sle).
  2. Master Builders Solutions: [www.master-builders-solutions.com/en-us/#sle](http://www.master-builders-solutions.com/en-us/#sle).

3. Pecora Corporation: [www.pecora.com/#sle](http://www.pecora.com/#sle).
4. Sherwin-Williams Company: [www.sherwin-williams.com/#sle](http://www.sherwin-williams.com/#sle).
5. Tremco Commercial Sealants & Waterproofing: [www.tremcosealants.com/#sle](http://www.tremcosealants.com/#sle).
6. W.R. Meadows, Inc: [www.wrmeadows.com/#sle](http://www.wrmeadows.com/#sle).
7. Substitutions: See Section 01 6000 - Product Requirements.

B. Self-Leveling Sealants: Pourable or self-leveling sealant that has sufficient flow to form a smooth, level surface when applied in a horizontal joint.

1. Dow: [www.dow.com/#sle](http://www.dow.com/#sle).
2. Master Builders Solutions: [www.master-builders-solutions.com/en-us/#sle](http://www.master-builders-solutions.com/en-us/#sle).
3. Pecora Corporation: [www.pecora.com/#sle](http://www.pecora.com/#sle).
4. Tremco Commercial Sealants & Waterproofing: [www.tremcosealants.com/#sle](http://www.tremcosealants.com/#sle).
5. W.R. Meadows, Inc: [www.wrmeadows.com/#sle](http://www.wrmeadows.com/#sle).
6. Substitutions: See Section 01 6000 - Product Requirements.

## 2.02 JOINT SEALANT APPLICATIONS

A. Scope:

1. Exterior Joints: Seal open joints, whether or not the joint is indicated on drawings, unless specifically indicated not to be sealed. Exterior joints to be sealed include, but are not limited to, the following items.
  - a. Wall expansion and control joints.
  - b. Joints between door, window, and other frames and adjacent construction.
  - c. Joints between different exposed materials.
  - d. Openings below ledge angles in masonry.
  - e. Other joints indicated below.
2. Interior Joints: Do not seal interior joints unless specifically indicated to be sealed. Interior joints to be sealed include, but are not limited to, the following items.
  - a. Joints between door, window, and other frames and adjacent construction.
  - b. In sound-rated wall and ceiling assemblies, gaps at electrical outlets, wiring devices, piping, and other openings; between wall/ceiling and other construction; and other flanking sound paths.
    - 1) Exception: Such gaps and openings in gypsum board and plaster finished stud walls and suspended ceilings.
    - 2) Exception: Through-penetrations in sound-rated assemblies that are also fire-rated assemblies.
  - c. Other joints indicated below.
3. Do not seal the following types of joints.
  - a. Intentional weepholes in masonry.
  - b. Joints indicated to be treated with manufactured expansion joint cover or some other type of sealing device.
  - c. Joints where sealant is specified to be provided by manufacturer of product to be sealed.
  - d. Joints where installation of sealant is specified in another section.
  - e. Joints between suspended panel ceilings/grid and walls.

B. Exterior Joints: Use non-sag non-staining silicone sealant, unless otherwise indicated.

1. Control and Expansion Joints in Concrete Paving: Self-Leveling polyurethane "traffic-grade" sealant.

C. Interior Joints: Use non-sag polyurethane sealant, unless otherwise indicated.

1. Joints between Fixtures in Wet Areas and Floors, Walls, and Ceilings: Mildew-resistant silicone sealant; white.
2. In Sound-Rated Assemblies: Acrylic emulsion latex sealant.
3. Other Floor Joints: Self-leveling polyurethane "traffic-grade" sealant.

- D. Interior Wet Areas: Bathrooms, restrooms, kitchens, food service areas, and food processing areas; fixtures in wet areas include plumbing fixtures, food service equipment, countertops, cabinets, and other similar items.
- E. Sound-Rated Assemblies: Walls and ceilings identified as "STC-rated", "sound-rated", or "acoustical".

## 2.03 JOINT SEALANTS - GENERAL

- A. Sealants and Primers: Provide products having lower volatile organic compound (VOC) content than indicated in SCAQMD 1168.
- B. Colors: As indicated on drawings.

## 2.04 NONSAG JOINT SEALANTS

- A. Non-Staining Silicone Sealant: ASTM C920, Grade NS, Uses M and A; not expected to withstand continuous water immersion or traffic.
  - 1. Non-Staining to Porous Stone: Non-staining to light-colored natural stone when tested in accordance with ASTM C1248.
  - 2. Dirt Pick-Up: Reduced dirt pick-up compared to other silicone sealants.
  - 3. Hardness Range: 15 to 35, Shore A, when tested in accordance with ASTM C661.
  - 4. Color: Match adjacent finished surfaces.
    - a. Unless otherwise indicated.
- B. Silicone Sealant: ASTM C920, Grade NS, Uses M and A; not expected to withstand continuous water immersion or traffic.
  - 1. Movement Capability: Plus and minus 25 percent, minimum.
  - 2. Hardness Range: 15 to 35, Shore A, when tested in accordance with ASTM C661.
  - 3. Color: Match adjacent finished surfaces.
- C. Mildew-Resistant Silicone Sealant: ASTM C920, Grade NS, Uses M and A; single component, mildew resistant; not expected to withstand continuous water immersion or traffic.
  - 1. Color: Match adjacent finish, unless otherwise indicated.
- D. Polymer Sealant: ASTM C920; single component, cured sealant is paintable and mold/mildew resistant, low odor and VOC, and ultraviolet (UV) resistant.
  - 1. Color: Match adjacent finish, unless otherwise indicated.
- E. Hybrid Urethane Sealant: ASTM C920, Grade NS, Uses M and A; single component; not expected to withstand continuous water immersion or traffic.
  - 1. Movement Capability: Plus and minus 35 percent, minimum.
  - 2. Hardness Range: 20 to 40, Shore A, when tested in accordance with ASTM C661.
  - 3. Color: Match adjacent finished surfaces.
- F. Polyurethane Sealant: ASTM C920, Grade NS, Uses M and A; single or multi-component; not expected to withstand continuous water immersion or traffic.
  - 1. Hardness Range: 20 to 35, Shore A, when tested in accordance with ASTM C661.
  - 2. Color: Match adjacent finished surfaces.
- G. Tamper-Resistant Polyurethane Sealant: ASTM C920, Grade NS, Uses M, G, and A; single or multi-component; not expected to withstand continuous water immersion or traffic.
  - 1. Movement Capability: Plus and minus 12-1/2 percent, minimum.
  - 2. Hardness Range: 50 to 60, Shore A, when tested in accordance with ASTM C661.
  - 3. Color: Match adjacent finished surfaces.
- H. Epoxy Sealant: ASTM C881/C881M, Type I and III, Grade 3, Class B and C; two-component.
  - 1. Hardness Range: 65 to 75, Shore D, when tested in accordance with ASTM C661.
  - 2. Compressive Strength: 11,000 psi, when tested in accordance with ASTM D695.
  - 3. Color: Match adjacent finished surfaces.
- I. Acrylic-Urethane Sealant: ASTM C920, Grade NS, Uses M and A; single component; paintable; not expected to withstand continuous water immersion or traffic.

1. Movement Capability: Plus and minus 12-1/2 percent, minimum.
2. Hardness Range: 15 to 40, Shore A, when tested in accordance with ASTM C661.
3. Color: Match adjacent finish, unless otherwise indicated.

J. Acrylic Emulsion Latex: Water-based; ASTM C834, single component, non-staining, non-bleeding, non-sagging; not intended for exterior use.

1. Color: Standard colors matching finished surfaces, Type OP (opaque).
2. Grade: ASTM C834; Grade 0 Degrees F (Minus 18 Degrees C).

## 2.05 SELF-LEVELING SEALANTS

- A. Self-Leveling Silicone Sealant: ASTM C920, Grade P, Uses M and A; single or multicomponent, explicitly approved by manufacturer for traffic exposure when recessed below traffic surface; not expected to withstand continuous water immersion.
  1. Movement Capability: Plus 100 percent, minus 50 percent, minimum.
  2. Hardness Range: 0 to 15, Shore A, when tested in accordance with ASTM C661.
  3. Color: Gray.
    - a. Unless otherwise indicated
- B. Self-Leveling Polyurethane Sealant: ASTM C920, Grade P, Uses M and A; single or multi-component; explicitly approved by manufacturer for traffic exposure; not expected to withstand continuous water immersion .
  1. Movement Capability: Plus and minus 25 percent, minimum.
  2. Hardness Range: 35 to 55, Shore A, when tested in accordance with ASTM C661.
  3. Color: Gray.
    - a. Unless otherwise indicated
- C. Self-Leveling Polyurethane Sealant for Horizontal Expansion Joints: ASTM C920, Grade P, Uses T, M, and O; multi-component; explicitly approved by manufacturer for horizontal expansion joints.
  1. Movement Capability: Plus and minus 25 percent, minimum.
  2. Hardness Range: 30 to 35, Shore A, when tested in accordance with ASTM C661.
  3. Color: Gray.
    - a. Unless otherwise indicated
- D. Self-Leveling Polyurethane Sealant for Continuous Water Immersion: Polyurethane; ASTM C920, Grade P, Uses M and A; single component; explicitly approved by manufacturer for traffic exposure and continuous water immersion.
  1. Movement Capability: Plus and minus 25 percent, minimum.
  2. Hardness Range: 35 to 55, Shore A, when tested in accordance with ASTM C661.
  3. Color: Gray.
    - a. Unless otherwise indicated
- E. Self-Leveling Silyl-Terminated Polyether/Polyurethane (STPE/STPU) Sealant: ASTM C920, Grade P, Uses M and A; single component; explicitly approved by manufacturer for traffic exposure; not expected to withstand continuous water immersion.
  1. Movement Capability: Plus and minus 35 percent.
  2. Hardness Range: 30 to 55, Shore A, when tested in accordance with ASTM C661.
  3. Color: Gray.
    - a. Unless otherwise indicated
- F. Rigid Self-Leveling Polyurethane Joint Filler: Two part, low viscosity, fast setting; intended for cracks and control joints not subject to significant movement.
  1. Hardness Range: Greater than 100, Shore A, and 50 to 80, Shore D, when tested in accordance with ASTM C661.
- G. Semi-Rigid Self-Leveling Epoxy Joint Filler: Epoxy or epoxy/polyurethane copolymer; intended for filling cracks and control joints not subject to significant movement; rigid enough to support concrete edges under traffic.
  1. Composition: Multi-component, 100 percent solids by weight.

2. Durometer Hardness: Minimum of 85 for Type A or 35 for Type D, after seven days when tested in accordance with ASTM D2240.
3. Color: Concrete gray.
4. Joint Width, Minimum: 1/8 inch.
5. Joint Width, Maximum: 1/4 inch.

H. Semi-Rigid Self-Leveling Polyurea Joint Filler: Two-component, 100 percent solids; intended for filling cracks and control joints not subject to significant movement; rigid enough to support concrete edges under traffic.

1. Durometer Hardness, Type A: 75, minimum, after seven days when tested in accordance with ASTM D2240.
2. Color: Concrete gray.
3. Joint Width, Minimum: 1/8 inch.
4. Joint Width, Maximum: 3/4 inch.

## 2.06 ACCESSORIES

- A. Backer Rod: Cylindrical cellular foam rod with surface that sealant will not adhere to, compatible with specific sealant used, and recommended by backing and sealant manufacturers for specific application.
  1. Type for Joints Not Subject to Pedestrian or Vehicular Traffic: ASTM C1330; Type O - Open Cell Polyurethane.
  2. Type for Joints Subject to Pedestrian or Vehicular Traffic: ASTM C1330; Type B - Bi-Cellular Polyethylene.
  3. Open Cell: 40 to 50 percent larger in diameter than joint width.
  4. Closed Cell and Bi-Cellular: 25 to 33 percent larger in diameter than joint width.
- B. Preformed Extruded Polyurethane Joint Seal: Medium-modulus, preformed polyurethane extrusion used to bridge joints under elastomeric wall coatings, in sizes to fit applications indicated on drawings, combined with polyurethane sealant for bonding joint seal to substrates.
  1. Size: 1-1/2 inch wide, in rolls 100 feet long.
  2. Thickness: 0.051 inch, with ridges along outside bottom edges for bonding area.
  3. Color: Light gray.
    - a. Unless otherwise indicated.
- C. Backing Tape: Self-adhesive polyethylene tape with surface that sealant will not adhere to and recommended by tape and sealant manufacturers for specific application.
- D. Masking Tape: Self-adhesive, nonabsorbent, non-staining, removable without adhesive residue, and compatible with surfaces adjacent to joints and sealants.
- E. Joint Cleaner: Non-corrosive and non-staining type, type recommended by sealant manufacturer; compatible with joint forming materials.
- F. Primers: Type recommended by sealant manufacturer to suit application; non-staining.

## PART 3 EXECUTION

### 3.01 EXAMINATION

- A. Verify that joints are ready to receive work.
- B. Verify that backing materials are compatible with sealants.
- C. Verify that backer rods are of the correct size.
- D. Preinstallation Adhesion Testing: Install a sample for each test location indicated in the test plan.
  1. Test each sample as specified in PART 1 under QUALITY ASSURANCE article.
  2. Notify Architect of date and time that tests will be performed, at least seven days in advance.
  3. Arrange for sealant manufacturer's technical representative to be present during tests.
  4. Record each test on Preinstallation Adhesion Test Log as indicated.

5. If any sample fails, review products and installation procedures, consult manufacturer, or take whatever other measures are necessary to ensure adhesion; re-test in a different location; if unable to obtain satisfactory adhesion, report to Architect.
6. After completion of tests, remove remaining sample material and prepare joint for new sealant installation.

### **3.02 PREPARATION**

- A. Remove loose materials and foreign matter that could impair adhesion of sealant.
- B. Clean joints, and prime as necessary, in accordance with manufacturer's instructions.
- C. Perform preparation in accordance with manufacturer's instructions and ASTM C1193.
- D. Mask elements and surfaces adjacent to joints from damage and disfigurement due to sealant work; be aware that sealant drips and smears may not be completely removable.
- E. Concrete Floor Joints That Will Be Exposed in Completed Work: Test joint filler in inconspicuous area to verify that it does not stain or discolor slab.

### **3.03 INSTALLATION**

- A. Perform work in accordance with sealant manufacturer's requirements for preparation of surfaces and material installation instructions.
- B. Perform installation in accordance with ASTM C1193.
- C. Perform acoustical sealant application work in accordance with ASTM C919.
- D. Measure joint dimensions and size joint backers to achieve width-to-depth ratio, neck dimension, and surface bond area as recommended by manufacturer, except where specific dimensions are indicated.
- E. Install bond breaker backing tape where backer rod cannot be used.
- F. Install sealant free of air pockets, foreign embedded matter, ridges, and sags, and without getting sealant on adjacent surfaces.
- G. Do not install sealant when ambient temperature is outside manufacturer's recommended temperature range, or will be outside that range during the entire curing period, unless manufacturer's approval is obtained and instructions are followed.
- H. Nonsag Sealants: Tool surface concave, unless otherwise indicated; remove masking tape immediately after tooling sealant surface.
- I. Concrete Floor Joint Filler: After full cure, shave joint filler flush with top of concrete slab.

### **3.04 FIELD QUALITY CONTROL**

- A. Perform field quality control inspection/testing as specified in PART 1 under QUALITY ASSURANCE article.
- B. Non-Destructive Adhesion Testing: If there are any failures in first 100 linear feet, notify Architect immediately.
- C. Destructive Adhesion Testing: If there are any failures in first 1000 linear feet, notify Architect immediately.
- D. Remove and replace failed portions of sealants using same materials and procedures as indicated for original installation.
- E. Repair destructive test location damage immediately after evaluation and recording of results.

### **3.05 POST-OCCUPANCY**

- A. Post-Occupancy Inspection: Perform visual inspection of entire length of project sealant joints at a time that joints have opened to their greatest width; i.e. at low temperature in thermal cycle. Report failures immediately and repair.

**END OF SECTION 07 9200**

This page intentionally left blank

**SECTION 08 1113**  
**HOLLOW METAL DOORS AND FRAMES**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Non-fire-rated hollow metal doors and frames.
- B. Hollow metal frames for wood doors.
- C. Fire-rated hollow metal doors and frames.
- D. Thermally insulated hollow metal doors with thermal break frames.
- E. Sound-rated hollow metal doors and frames.
- F. Hollow metal borrowed lites glazing frames.
- G. Accessories, including glazing, matching panels, and as indicated on drawings.

**1.02 ABBREVIATIONS AND ACRONYMS**

- A. ANSI: American National Standards Institute.
- B. ASCE: American Society of Civil Engineers.
- C. HMMA: Hollow Metal Manufacturers Association.
- D. NAAMM: National Association of Architectural Metal Manufacturers.
- E. NFPA: National Fire Protection Association.
- F. SDI: Steel Door Institute.
- G. UL: Underwriters Laboratories.

**1.03 REFERENCE STANDARDS**

- A. ADA Standards - 2010 ADA Standards for Accessible Design; 2010.
- B. ANSI/SDI A250.3 - Test Procedure and Acceptance Criteria for Factory Applied Finish Coatings for Steel Doors and Frames; 2025.
- C. ANSI/SDI A250.4 - Test Procedure and Acceptance Criteria for Physical Endurance for Steel Doors, Frames and Frame Anchors; 2024.
- D. ANSI/SDI A250.6 - Recommended Practice for Hardware Reinforcing on Standard Steel Doors and Frames; 2024.
- E. ANSI/SDI A250.8 - Specifications for Standard Steel Doors and Frames (SDI-100); 2023.
- F. ANSI/SDI A250.10 - Test Procedure and Acceptance Criteria for Prime Painted Steel Surfaces for Steel Doors and Frames; 2025.
- G. ASTM A653/A653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process; 2023.
- H. ASTM A1008/A1008M - Standard Specification for Steel, Sheet, Cold-Rolled, Carbon, Structural, High-Strength Low-Alloy, High-Strength Low-Alloy with Improved Formability, Required Hardness, Solution Hardened, and Bake Hardenable; 2023, with Editorial Revision.
- I. ASTM A1011/A1011M - Standard Specification for Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy, High-Strength Low-Alloy with Improved Formability, and Ultra-High Strength; 2023.
- J. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- K. ASTM E330/E330M - Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference; 2014 (Reapproved 2021).
- L. BHMA A156.115 - Hardware Preparation in Steel Doors and Frames; 2016.

- M. FEMA P-361 - Safe Rooms for Tornadoes and Hurricanes: Guidance for Community and Residential Safe Rooms; 2024.
- N. FLA (PAD) - Florida Building Code Online - Product Approval Directory; Current Edition.
- O. ICC 500 - ICC/NSSA Standard for the Design and Construction of Storm Shelters; 2020.
- P. ICC A117.1 - Accessible and Usable Buildings and Facilities; 2017.
- Q. ITS (DIR) - Directory of Listed Products; Current Edition.
- R. Miami (APD) - Approved Products Directory; Miami-Dade County; Current Edition.
- S. NAAMM HMMA 830 - Hardware Selection for Hollow Metal Doors and Frames; 2002.
- T. NAAMM HMMA 831 - Hardware Locations for Hollow Metal Doors and Frames; 2024.
- U. NAAMM HMMA 840 - Guide Specifications for Receipt, Storage and Installation of Hollow Metal Doors and Frames; 2024.
- V. NAAMM HMMA 861 - Guide Specifications for Commercial Hollow Metal Doors and Frames; 2014.
- W. NFPA 80 - Standard for Fire Doors and Other Opening Protectives; 2025.
- X. NFPA 105 - Standard for Smoke Door Assemblies and Other Opening Protectives; 2025.
- Y. NFPA 252 - Standard Methods of Fire Tests of Door Assemblies; 2022.
- Z. SDI 117 - Manufacturing Tolerances for Standard Steel Doors and Frames; 2023.
- AA. UL (DIR) - Online Certifications Directory; Current Edition.
- BB. UL 10B - Standard for Fire Tests of Door Assemblies; Current Edition, Including All Revisions.
- CC. UL 10C - Standard for Positive Pressure Fire Tests of Door Assemblies; Current Edition, Including All Revisions.
- DD. UL 1784 - Standard for Air Leakage Tests of Door Assemblies and Other Opening Protectives; Current Edition, Including All Revisions.

#### **1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Materials and details of design and construction, hardware locations, reinforcement type and locations, anchorage and fastening methods, and finishes.
- C. Shop Drawings: Details of each opening, showing elevations, glazing, frame profiles, and any indicated finish requirements.
  - 1. Show thermal break frames on Shop Drawings.
  - 2. Include the following for all types:
    - a. Elevations of each door design.
    - b. Details of doors, including vertical and horizontal edge details and metal thicknesses.
    - c. Frame details for each frame type, including dimensioned profiles and metal thicknesses.
    - d. Locations of reinforcement and preparations for hardware.
    - e. Details of anchorages, joints, field splices, and connections.
    - f. Details of accessories.
    - g. Details of moldings, removable stops, and glazing.
    - h. Details of conduit and preparations for power, signal, and control systems.
    - i. Show proposed field splice locations when shipping limitations dictate large openings need to be fabricated in sections.
- D. Door hardware supplier is to furnish templates, template reference number and/or physical hardware to the steel door and frame supplier in order to prepare the doors and frames to receive the finish hardware items.
- E. Door schedule indicating door and frame location, type, size and swing.

1. Prepared by or under the supervision of supplier, using same reference numbers for details and openings as those on Drawings.
- F. Samples: Submit two samples of metal, 2 inch by 2 inch in size showing factory finishes, colors, and surface texture.
- G. Installation Instructions: Manufacturer's published instructions, including any special installation instructions relating to this project.
- H. Manufacturer's Certificate: Certification that products meet or exceed specified requirements.
- I. Manufacturer's Qualification Statement.
- J. Installer's Qualification Statement.

## 1.05 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Provide hollow metal doors and frames from SDI Certified manufacturer: [www.steeldoor.org/sdicertified.php/#sle](http://www.steeldoor.org/sdicertified.php/#sle).
- B. Installer Qualifications: Company specializing in performing work of the type specified and with at least ten years of documented experience.
- C. Maintain at project site copies of reference standards relating to installation of products specified.

## 1.06 WARRANTY

- A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace doors that fail in materials or workmanship within specified warranty period.
- B. Warranty includes installation and finishing that may be required due to repair or replacement of defective doors.

# PART 2 PRODUCTS

## 2.01 MANUFACTURERS

- A. Hollow Metal Doors and Frames:
- B. Subject to compliance with requirements, available SDI certified manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
  1. Ceco Door, an Assa Abloy Group company: [www.assaabloydss.com](http://www.assaabloydss.com).
  2. Curries, an Assa Abloy Group company: [www.assaabloydss.com](http://www.assaabloydss.com).
  3. Republic Doors, an Allegion brand: [www.republicdoor.com/#sle](http://www.republicdoor.com/#sle).
  4. Steelcraft, an Allegion brand: [www.allegion.com/#sle](http://www.allegion.com/#sle).
  5. Substitutions: See Section 01 6000 - Product Requirements.

## 2.02 PERFORMANCE REQUIREMENTS

- A. Requirements for Hollow Metal Doors and Frames:
  1. Steel Sheet: Comply with one or more of the following requirements; galvannealed steel complying with ASTM A653/A653M, cold-rolled steel complying with ASTM A1008/A1008M, or hot-rolled pickled and oiled (HRPO) steel complying with ASTM A1011/A1011M, commercial steel (CS) Type B, for each.
  2. Accessibility: Comply with ICC A117.1 and ADA Standards.
  3. Exterior Door Top Closures: Flush end closure channel, with top and door faces aligned.
  4. Typical Door Face Sheets: Flush.
  5. Glazed Lights: Non-removable stops on non-secure side; sizes and configurations as indicated on drawings. Style: Flush, square, low-profile .
    - a. Glazing Stop Fasteners: Pre-finished. Design intent is to match specified frame paint color. Style: Flush.
  6. Hardware Preparations, Selections and Locations: Comply with NAAMM HMMA 830 and NAAMM HMMA 831 or BHMA A156.115 and ANSI/SDI A250.8 (SDI-100) in accordance with specified requirements.

B. Combined Requirements: If a particular door and frame unit is indicated to comply with more than one type of requirement, comply with the specified requirements for each type; for instance, an exterior door that is also indicated as being sound-rated must comply with the requirements specified for exterior doors and for sound-rated doors; where two requirements conflict, comply with the most stringent.

## 2.03 HOLLOW METAL DOORS

A. Exterior Doors: Thermally insulated.

1. Based on SDI Standards: ANSI/SDI A250.8 (SDI-100).
  - a. Level 3 - Extra Heavy-duty.
  - b. Physical Performance Level A, 1,000,000 cycles; in accordance with ANSI/SDI A250.4.
  - c. Model 3 - Stile and Rail.
  - d. Door Face Metal Thickness: 16 gage, 0.053 inch, minimum.
  - e. Top and Bottom Edges: Reinforce tops and bottoms of doors with a continuous steel channel not less than 16 gauge, extending the full width of the door and welded to the face sheet.
    - 1) Doors with an inverted top channel to include a steel closure channel, screw attached, with the web of the channel flush with the face sheets of the door. Plastic or composite channel fillers are not acceptable.
  - f. Zinc Coating: A60/ZF180 galvannealed coating; ASTM A653/A653M.
2. Door Thickness: 1-3/4 inch, nominal.
3. Weatherstripping: Refer to Section 08 7100.
4. Door Finish: Factory finished.
5. Weep Holes: Provide weep-hole openings in bottom of exterior doors to permit moisture to escape.

B. Interior Doors, Non-Fire-Rated:

1. Based on SDI Standards: ANSI/SDI A250.8 (SDI-100).
  - a. Level 3 - Extra Heavy-duty.
  - b. Physical Performance Level A, 1,000,000 cycles; in accordance with ANSI/SDI A250.4.
  - c. Model 3 - Stile and Rail.
  - d. Door Face Metal Thickness: 16 gage, 0.053 inch, minimum.
  - e. Top and Bottom Edges: Reinforce tops and bottoms of doors with a continuous steel channel not less than 16 gauge, extending the full width of the door and welded to the face sheet.
  - f. Hinge Reinforcement: Minimum 7 gauge (3/16 inch) plate 1-1/4 inch by 9 inch or minimum 14 gauge continuous channel with pierced holes, drilled and tapped.
  - g. Zinc Coating: A60/ZF180 galvannealed coating; ASTM A653/A653M.
2. Door Thickness: 1-3/4 inch, nominal.
3. Door Finish: Factory primed and field finished.

C. Fire-Rated Doors:

1. Based on SDI Standards: ANSI/SDI A250.8 (SDI-100).
  - a. Level 3 - Extra Heavy-duty.
  - b. Physical Performance Level A, 1,000,000 cycles; in accordance with ANSI/SDI A250.4.
  - c. Model 3 - Stile and Rail.
  - d. Door Face Metal Thickness: 16 gage, 0.053 inch, minimum.
  - e. Zinc Coating: A60/ZF180 galvannealed coating; ASTM A653/A653M.
2. Fire Rating: As indicated on Door Schedule, tested in accordance with UL 10C and NFPA 252 ("positive pressure fire tests").
3. Provide units listed and labeled by UL (DIR) or ITS (DIR).
  - a. Attach fire rating label to each fire rated unit.

4. Door Thickness: 1-3/4 inch, nominal.
5. Door Finish: Factory primed and field finished.

## 2.04 HOLLOW METAL FRAMES

- A. Comply with standards and/or custom guidelines as indicated for corresponding door in accordance with applicable door frame requirements.
- B. Exterior Door Frames: Full profile/continuously welded type.
  1. Galvanizing: Components hot-dipped zinc-iron alloy-coated (galvannealed) in accordance with ASTM A653/A653M, with A60/ZF180 coating.
  2. Frame Metal Thickness: 14 gage, 0.067 inch, minimum.
  3. Frame Finish: Factory finished.
  4. Weatherstripping: Separate, see Section 08 7100.
  5. Thermal Break Frames: Subject to the same compliance standards and requirements as standard hollow metal frames. Tested for thermal performance in accordance with NFRC 102, and resistance to air infiltration in accordance with NFRC 400. Provide thermally broken frame profiles available for use in both masonry and drywall construction. Fabricate with 1/16 inch positive thermal break and integral vinyl weatherstripping.
- C. Interior Door/Window Frames, Non-Fire Rated: Full profile/continuously welded type.
  1. Frame Metal Thickness: 16 gage, 0.053 inch, minimum.
  2. Frame Finish: Factory primed and field finished.
- D. Door Frames, Fire-Rated: Full profile/continuously welded type.
  1. Fire Rating: Same as door, labeled.
  2. Frame Metal Thickness: 16 gage, 0.053 inch, minimum.
- E. Sound-Rated Door Frames: Full profile/continuously welded type.
  1. Frame Metal Thickness: 16 gage, 0.053 inch, minimum.
  2. Frame Finish: Factory primed and field finished.
- F. Frames for Wood Doors: Comply with frame requirements in accordance with corresponding door.
- G. Mullions for Pairs of Doors: Removable type, with profile similar to jambs.
- H. Borrowed Lites Glazing Frames: Construction and face dimensions to match door frames, and as indicated on drawings.
  1. Stops and Moldings: Provide stops and moldings around glazed lites where indicated. Form corners of stops and moldings with mitered hairline joints at fabricator's shop. Fixed and removable stops to allow multiple glazed lites each to be removed independently. Coordinate frame rabbet widths between fixed and removable stops with the type of glazing and installation indicated.
    - a. Provide flush, countersunk fasteners. Fastener finish to match specified frame paint colors, as indicated on drawings. Provide security screws at exterior locations.
  2. Moldings for Glazed Lites in Doors and Loose Stops for Glazed Lites in Frames: Minimum 20 gauge thick, fabricated from same material as door face sheet in which they are installed.
  3. Fixed Frame Moldings: Formed integral with hollow metal frames, a minimum of 5/8 inch (16 mm) high unless otherwise indicated. Provide fixed frame moldings and stops on outside of exterior and on secure side of interior doors and frames.
  4. Preformed Metal Frames for Light Openings: Manufacturer's standard frame formed of 0.048-inch-thick, cold rolled steel sheet; with baked enamel or powder coated finish; and approved for use in doors of fire protection rating indicated. Match pre-finished door paint color where applicable.
- I. Sidelight and Transom Bar Frames: Provide closed tubular members with no visible face seams or joints, fabricated from same material as door frame. Fasten members at crossings and to jambs by butt welding.
  1. Profile: Same as jamb and head.

- J. Frames Wider than 48 inches: Reinforce with steel channel fitted tightly into frame head, flush with top.
  - 1. High Frequency Hinge Reinforcement: Provide high frequency hinge reinforcements at door openings 48-inches and wider with mortise butt type hinges at top hinge locations.
- K. Welded Frames: Weld flush face joints continuously; grind, fill, dress, and make smooth, flush, and invisible.
  - 1. Welded frames are to be provided with two steel spreaders temporarily attached to the bottom of both jambs to serve as a brace during shipping and handling. Spreader bars are for bracing only and are not to be used to size the frame opening.

## 2.05 FINISHES

- A. Primer: Rust-inhibiting, complying with ANSI/SDI A250.10, door manufacturer's standard.
- B. Factory Finish: Complying with ANSI/SDI A250.3, manufacturer's standard coating.
  - 1. Color: As selected by Architect from manufacturer's standard range.

## 2.06 ACCESSORIES

- A. Jamb Anchors:
  - 1. Stud Wall Type: Designed to engage stud and not less than 0.042 inch thick.
  - 2. Jamb Anchors: Provide number and spacing of anchors as follows:
    - a. Stud Wall Type: Locate anchors not more than 18 inches from top and bottom of frame. Space anchors not more than 32 inches o.c. and as follows:
      - 1) Three anchors per jamb up to 60 inches high.
      - 2) Four anchors per jamb from 60 to 90 inches high.
      - 3) Five anchors per jamb from 90 to 96 inches high.
      - 4) Five anchors per jamb plus 1 additional anchor per jamb for each 24 inches or fraction thereof above 96 inches high.
      - 5) Two anchors per head for frames above 42 inches wide and mounted in metal stud partitions.
      - 6) Severe Storm Shelter Openings: Provide jamb, head, and sill anchors in accordance with manufacturer's tested and approved assemblies.
- B. Door Window Frames: Door window frames with glazing securely fastened within door opening.
  - 1. Frame Material: 18 gage, 0.0478 inch, galvanized steel.
- C. Glazing: Clear sheet glass, 1/4 inch (6 mm) thick, factory installed.
- D. Removable Stops: Formed sheet steel, Flush, low-profile, mitered corners; prepared for countersink style tamper proof screws.
- E. Astragals and Edges for Double Doors: Pairs of door astragals, and door edge sealing and protection devices.
  - 1. UL listed products in compliance with requirements of authorities having jurisdiction.
- F. Silencers: Resilient rubber or vinyl, fitted into drilled hole; provide three on strike side of single door, three on center mullion of pairs, and two on head of pairs without center mullions.
  - 1. Silencers to be supplied by frame manufacturer regardless if specified in Division 08 Section "Door Hardware".
- G. Temporary Frame Spreaders: Provide for factory- or shop-assembled frames.
- H. Hardware Preparation: Factory prepare hollow metal work to receive template mortised hardware; include cutouts, reinforcement, mortising, drilling, and tapping according to the Door Hardware Schedule and templates furnished as specified in Division 08 Section "Door Hardware."
  - 1. Locate hardware as indicated, or if not indicated, according to ANSI/SDI A250.8.
  - 2. Reinforce doors and frames to receive non-template, mortised and surface mounted door hardware.

- 3. Comply with applicable requirements in ANSI/SDI A250.6 and ANSI/DHI A115 Series specifications for preparation of hollow metal work for hardware.
- 4. Coordinate locations of conduit and wiring boxes for electrical connections with Division 26 Sections.
- I. Prime Finishes: Doors and frames to be cleaned, and chemically treated to insure maximum finish paint adhesion. Surfaces of the door and frame exposed to view to receive a factory applied coat of rust inhibiting shop primer.
  - 1. Shop Primer: Manufacturer's standard, fast-curing, lead and chromate free primer complying with ANSI/SDI A250.10 acceptance criteria; recommended by primer manufacturer for substrate; and compatible with substrate and field-applied coatings.

## **PART 3 EXECUTION**

### **3.01 INSTALLATION**

- A. Install doors and frames in accordance with manufacturer's instructions and related requirements of specified door and frame standards or custom guidelines indicated.
- B. Install fire rated units in accordance with NFPA 80.
- C. Coordinate frame anchor placement with wall construction.
- D. Install door hardware as specified in Section 08 7100.
- E. Coordinate installation of electrical connections to electrical hardware items.
- F. Repace doors with damaged factory finishes.

### **3.02 TOLERANCES**

- A. Maximum Diagonal Distortion: 1/16 inch measured with straight edge, corner to corner.

### **3.03 ADJUSTING AND CLEANING**

- A. Adjust for smooth and balanced door movement.
- B. Remove grout and other bonding material from hollow metal work immediately after installation.

**END OF SECTION 08 1113**

This page intentionally left blank

**SECTION 08 4313**  
**ALUMINUM-FRAMED STOREFRONTS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Aluminum-framed storefront, with vision glass.
- B. Aluminum doors and frames.
- C. Door hardware.

**1.02 REFERENCE STANDARDS**

- A. AAMA 609 & 610 - Cleaning and Maintenance Guide for Architecturally Finished Aluminum; 2025.
- B. ASTM B221 - Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes; 2021.
- C. ASTM B221M - Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles, and Tubes (Metric); 2021.
- D. ASTM E283/E283M - Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Skylights, Curtain Walls, and Doors Under Specified Pressure Differences Across the Specimen; 2019.
- E. ASTM E330/E330M - Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference; 2014 (Reapproved 2021).

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Product Data: Provide component dimensions, describe components within assembly, anchorage and fasteners, glass and infill, door hardware, and internal drainage details.
- C. Shop Drawings: Indicate system dimensions, framed opening requirements and tolerances, affected related work, expansion and contraction joint location and details, and field welding required.
- D. Hardware Schedule: Complete itemization of each item of hardware to be provided for each door, cross-referenced to door identification numbers in Contract Documents.
- E. Installer's qualification statement.
- F. Specimen warranty.

**1.04 WARRANTY**

- A. See Section 01 7800 - Closeout Submittals for additional warranty requirements.
- B. Correct defective Work within a five year period after Date of Substantial Completion.
- C. Provide five year manufacturer warranty against failure of glass seal on insulating glass units, including interpane dusting or misting. Include provision for replacement of failed units.

**PART 2 PRODUCTS**

**2.01 MANUFACTURERS**

- A. Aluminum-Framed Storefronts:
  - 1. Kawneer North America: [www.kawneer.com/#sle](http://www.kawneer.com/#sle).
  - 2. Substitutions: See Section 01 6000 - Product Requirements.

**2.02 BASIS OF DESIGN -- FRAMING FOR MONOLITHIC GLAZING**

- A. Match existing set style.
- B. Match existing framing dimensions.

## **2.03 BASIS OF DESIGN -- SWINGING DOORS**

- A. Match existing doors in width, height and style.
- B. Thickness: 1-3/4 inches.

## **2.04 ALUMINUM-FRAMED STOREFRONT**

- A. Aluminum-Framed Storefront: Factory fabricated, factory finished aluminum framing members with infill, and related flashings, anchorage and attachment devices.
  - 1. Finish: Match existing.
    - a. Factory finish all surfaces that will be exposed in completed assemblies.
    - b. Touch-up surfaces cut during fabrication so that no natural aluminum is visible in completed assemblies, including joint edges.
  - 2. Fabrication: Joints and corners flush, hairline, and weatherproof, accurately fitted and secured; prepared to receive anchors and hardware; fasteners and attachments concealed from view; reinforced as required for imposed loads.
  - 3. Construction: Eliminate noises caused by wind and thermal movement, prevent vibration harmonics, and prevent "stack effect" in internal spaces.
  - 4. System Internal Drainage: Drain to the exterior by means of a weep drainage network any water entering joints, condensation occurring in glazing channel, and migrating moisture occurring within system.
  - 5. Expansion/Contraction: Provide for expansion and contraction within system components caused by cycling temperature range of 170 degrees F over a 12 hour period without causing detrimental effect to system components, anchorages, and other building elements.
  - 6. Movement: Allow for movement between storefront and adjacent construction, without damage to components or deterioration of seals.
  - 7. Perimeter Clearance: Minimize space between framing members and adjacent construction while allowing expected movement.
- B. Performance Requirements
  - 1. Wind Loads: Design and size components to withstand the specified load requirements without damage or permanent set, when tested in accordance with ASTM E330/E330M, using loads 1.5 times the design wind loads and 10 second duration of maximum load.
    - a. Member Deflection: Limit member deflection to flexure limit of glass in any direction, with full recovery of glazing materials.
  - 2. Air Leakage: 0.06 cfm/sq ft maximum leakage of storefront wall area when tested in accordance with ASTM E283/E283M at 1.57 psf pressure difference.

## **2.05 COMPONENTS**

- A. Aluminum Framing Members: Tubular aluminum sections, drainage holes and internal weep drainage system.
  - 1. Glazing Stops: Flush.
- B. Glazing: See Section 08 8000.
- C. Swing Doors: Glazed aluminum.
  - 1. Thickness: 1-3/4 inches.
  - 2. Top Rail: Match existing.
  - 3. Vertical Stiles: Match existing.
  - 4. Bottom Rail: Match existing.
  - 5. Glazing Stops: Square.
  - 6. Finish: Same as storefront.
  - 7. Double swinging.

## **2.06 MATERIALS**

- A. Extruded Aluminum: ASTM B221 (ASTM B221M).
- B. Fasteners: Stainless steel.

- C. Glazing Gaskets: Type to suit application to achieve weather, moisture, and air infiltration requirements.

## **2.07 FINISHES**

- A. Color: Match existing.

## **2.08 HARDWARE**

- A. Other Door Hardware: Storefront manufacturer's standard type to suit application.
  - 1. Finish on Hand-Contacted Items: Polished chrome.
  - 2. For each door, include pivots, push handle, pull handle, and closer.
- B. Door Closers: Concealed overhead.

# **PART 3 EXECUTION**

## **3.01 EXAMINATION**

- A. Verify dimensions, tolerances, and method of attachment with other work.
- B. Verify that storefront wall openings and adjoining water-resistive and/or air barrier seal materials are ready to receive work of this section.

## **3.02 INSTALLATION**

- A. Install wall system in accordance with manufacturer's instructions.
- B. Attach to structure to permit sufficient adjustment to accommodate construction tolerances and other irregularities.
- C. Provide alignment attachments and shims to permanently fasten system to building structure.
- D. Align assembly plumb and level, free of warp or twist. Maintain assembly dimensional tolerances, aligning with adjacent work.
- E. Provide thermal isolation where components penetrate or disrupt building insulation.
- F. Install sill flashings. Turn up ends and edges; seal to adjacent work to form water tight dam.
- G. Where fasteners penetrate sill flashings, make watertight by seating and sealing fastener heads to sill flashing.
- H. Pack fibrous insulation in shim spaces at perimeter of assembly to maintain continuity of thermal barrier.
- I. Set thresholds in bed of sealant and secure.
- J. Install hardware using templates provided.
- K. Touch-up minor damage to factory applied finish; replace components that cannot be satisfactorily repaired.

## **3.03 TOLERANCES**

- A. Maximum Variation from Plumb: 0.06 inch per 3 feet non-cumulative or 0.06 inch per 10 feet, whichever is less.
- B. Maximum Misalignment of Two Adjoining Members Abutting in Plane: 1/32 inch.

## **3.04 ADJUSTING**

- A. Adjust operating hardware and sash for smooth operation.

## **3.05 CLEANING**

- A. Remove protective material from pre-finished aluminum surfaces.
- B. Wash down surfaces with a solution of mild detergent in warm water, applied with soft, clean wiping cloths, and take care to remove dirt from corners and to wipe surfaces clean.
- C. Upon completion of installation, thoroughly clean aluminum surfaces in accordance with AAMA 609 & 610.

### **3.06 PROTECTION**

- A. Protect installed products from damage until Date of Substantial Completion.

**END OF SECTION 08 4313**

**SECTION 08 7100  
DOOR HARDWARE  
END OF SECTION 08 7100**

This page intentionally left blank

## SECTION 08 8000 GLAZING

### PART 1 GENERAL

#### 1.01 SECTION INCLUDES

- A. Glazing units.
- B. Plastic films.
- C. Locations and glazing types are indicated on drawings.
- D. Glazing compounds and accessories.

#### 1.02 REFERENCE STANDARDS

- A. 16 CFR 1201 - Safety Standard for Architectural Glazing Materials; Current Edition.
- B. ANSI Z97.1 - American National Standard for Safety Glazing Materials Used in Buildings - Safety Performance Specifications and Methods of Test; 2015 (Reaffirmed 2020).
- C. ASCE 7 - Minimum Design Loads and Associated Criteria for Buildings and Other Structures; Most Recent Edition Cited by Referring Code or Reference Standard.
- D. ASTM C864 - Standard Specification for Dense Elastomeric Compression Seal Gaskets, Setting Blocks, and Spacers; 2005 (Reapproved 2019).
- E. ASTM C920 - Standard Specification for Elastomeric Joint Sealants; 2018 (Reapproved 2024).
- F. ASTM C1036 - Standard Specification for Flat Glass; 2021.
- G. ASTM C1048 - Standard Specification for Heat-Strengthened and Fully Tempered Flat Glass; 2018.
- H. ASTM C1172 - Standard Specification for Laminated Architectural Flat Glass; 2019.
- I. ASTM C1193 - Standard Guide for Use of Joint Sealants; 2016 (Reapproved 2023).
- J. ASTM C1376 - Standard Specification for Pyrolytic and Vacuum Deposition Coatings on Flat Glass; 2021a.
- K. ASTM E1300 - Standard Practice for Determining Load Resistance of Glass in Buildings; 2016.
- L. ASTM E1996 - Standard Specification for Performance of Exterior Windows, Curtain Walls, Doors, and Impact Protective Systems Impacted by Windborne Debris in Hurricanes; 2023.
- M. ASTM E2190 - Standard Specification for Insulating Glass Unit Performance and Evaluation; 2019.
- N. ASTM F1233 - Standard Test Method for Security Glazing Materials And Systems; 2021.
- O. GANA (GM) - GANA Glazing Manual; 2022.
- P. GANA (SM) - GANA Sealant Manual; 2008.
- Q. GANA (LGRM) - Laminated Glazing Reference Manual; 2019.
- R. ICC (IBC) - International Building Code; Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.
- S. IGMA TM-3000 - North American Glazing Guidelines for Sealed Insulating Glass Units for Commercial & Residential Use; 1990 (Reaffirmed 2016).
- T. NFRC 100 - Procedure for Determining Fenestration Product U-factors; 2023.
- U. NFRC 200 - Procedure for Determining Fenestration Product Solar Heat Gain Coefficient and Visible Transmittance at Normal Incidence; 2023.
- V. NFRC 300 - Test Method for Determining the Solar Optical Properties of Glazing Materials and Systems; 2023.

### **1.03 ADMINISTRATIVE REQUIREMENTS**

- A. Preinstallation Meeting: Convene a preinstallation meeting one week before starting work of this section; require attendance by each of the affected installers.

### **1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Product Data on Glazing Unit Glazing Types: Provide structural, physical and environmental characteristics, size limitations, special handling and installation requirements.
- C. Product Data on Glazing Compounds and Accessories: Provide chemical, functional, and environmental characteristics, limitations, special application requirements, and identify available colors.
- D. Glazing Schedule: List glass types and thicknesses for each size opening and location. Use same designations indicated on drawings.
- E. Delegated-Design Submittal: For glass indicated to comply with performance requirements and design criteria, including analysis data signed and sealed by the qualified professional engineer responsible for their preparation.
- F. Initial Samples: Submit two samples 12 by 12 inch in size of glass units.
  - 1. For each type of clear glass specified.
- G. Certificate: Certify that products of this section meet or exceed specified requirements.
- H. Warranty Documentation: Submit manufacturer warranty and ensure that forms have been completed in Owner's name and registered with manufacturer.
- I. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
  - 1. See Section 01 6000 - Product Requirements, for additional provisions.
  - 2. Extra Insulating Glass Units: One of each glass size and each glass type.

### **1.05 QUALITY ASSURANCE**

- A. Perform Work in accordance with GANA (GM), GANA (SM), GANA (LGRM), and IGMA TM-3000 for glazing installation methods. Maintain one copy on site.
- B. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years of documented experience.
  - 1. Provide certified glass products through ANSI accredited certifications that include plant audits and independent laboratory performance testing.
    - a. Insulating Glass Certification Council (IGCC).
    - b. Safety Glazing Certification Council (SGCC).
- C. Installer Qualifications: Company specializing in performing work of the type specified and with at least ten years documented experience.
- D. Provide fully tempered and / or safety glazing at locations as required by code.

### **1.06 FIELD CONDITIONS**

- A. Do not install glazing when ambient temperature is less than 40 degrees F.
- B. Maintain minimum ambient temperature before, during and 24 hours after installation of glazing compounds.

### **1.07 WARRANTY**

- A. See Section 01 7800 - Closeout Submittals for additional warranty requirements.
- B. Heat Soaked Tempered Glass: Provide a ten (10) year manufacturer warranty to include coverage for spontaneous breakage of fully tempered glass caused by nickel sulfide (NiS) inclusions.

## PART 2 PRODUCTS

### 2.01 MANUFACTURERS

- A. Etched Glass Manufacturers:
  - 1. Basis-of-Design: Vitro Architectural Glass (formerly PPG Glass):  
[www.vitroglaszings.com/#sle](http://www.vitroglaszings.com/#sle).

### 2.02 GLASS MATERIALS

- A. Float Glass: Provide float glass based glazing unless otherwise indicated.
  - 1. Kind HS - Heat-Strengthened Type: Complies with ASTM C1048.
    - a. Provide heat strengthened glass at all locations, except where tempered / safety glass is indicated or required for safety based on application or as required by code.
    - b. Maximum peak to valley rollerwave 0.005" (0.127mm) in the central area.
  - 2. Kind FT - Fully Tempered Type: Complies with ASTM C1048.
    - a. Provide as required for application and as required by code.
    - b. Maximum peak to valley rollerwave 0.005" (0.127mm) in the central area.
  - 3. Fully Tempered Safety Glass: Complies with ANSI Z97.1 or 16 CFR 1201 criteria for safety glazing used in hazardous locations.
    - a. Provide as required for application and as required by code, whether or not shown on drawings. It is the Contractor's responsibility to confirm and provide safety glass as required by code.
  - 4. Heat-Soak Testing (HST): Provide HST of fully tempered glass used on canopy, point-supported, spider wall, high-risk, sloping overhead, horizontal overhead, free-standing glass protective barrier, or other demanding applications of project, to reduce risks of spontaneous breakage due to nickel sulfide (NiS) induced fractures in accordance with industry established testing requirements.
  - 5. Thicknesses: As indicated; provide greater thickness as required for exterior glazing wind load design.
- B. Laminated Glass: Float glass laminated in accordance with ASTM C1172.
  - 1. Laminated Safety Glass: Complies with ANSI Z97.1 - Class B or 16 CFR 1201 - Category I impact test requirements.
  - 2. Provide as required for application and as required by code.

### 2.03 INSULATING GLASS UNITS

- A. Manufacturers:
  - 1. Glass: Any of the manufacturers specified for float glass.

### 2.04 GLAZING UNITS

- A. Monolithic Interior Vision Glazing:
  - 1. Applications: Interior glazing unless otherwise indicated.
  - 2. Glass Type: Fully tempered float glass.
  - 3. Tint: Clear. Etched where indicated.
  - 4. Thickness: 1/4 inch, nominal.

### 2.05 PLASTIC FILMS

- A. Decorative Plastic Film: Polyester type.
  - 1. Application: Locations as indicated on drawings.
  - 2. Series Type: As indicated on drawings.
  - 3. Color: As indicated on drawings.
  - 4. Thickness Without Liner: 0.002 inch.

### 2.06 LAMINATED GLASS INTERLAYERS

- A. Polyvinyl Butyral (PVB) Interlayer for Laminated Glazing:
  - 1. Functionality: Post-breakage safety and security.
  - 2. Applications:

- a. Single pane, laminated glass unit.
- b. Interior laminated pane of insulating glass unit.
- 3. Color: Clear.
- 4. Thickness: As required for indicated performance of laminated glass application.

## 2.07 ACCESSORIES

- A. Setting Blocks: Silicone, with 80 to 90 Shore A durometer hardness; ASTM C864 Option II. Length of 0.1 inch for each square foot of glazing or minimum 4 inch by width of glazing rabbet space minus 1/16 inch by height to suit glazing method and pane weight and area.
- B. Spacer Shims: Neoprene, 50 to 60 Shore A durometer hardness; ASTM C864 Option II. Continuous by one half the height of the glazing stop by thickness to suit application, self adhesive on one face.
- C. Glazing Tape, Back Bedding Mastic Type: Preformed, butyl-based, 100 percent solids compound with integral resilient spacer rod applicable to application indicated; 5 to 30 cured Shore A durometer hardness; coiled on release paper; black color.
  - 1. Width: As required for application.
  - 2. Thickness: As required for application.
  - 3. Spacer Rod Diameter: As required for application.
- D. Glazing Splines: Resilient silicone extruded shape to suit glazing channel retaining slot; ASTM C864 Option II; color black.
- E. Glazing Clips: Manufacturer's standard type.
- F. Smoke Removal Window/Glazing Unit Markings: Adhesive backed markings affixed to manually operable or fixed windows of high-rise buildings to identify units intended for post-fire smoke removal in compliance with ICC (IBC) and local building officials.

## PART 3 EXECUTION

### 3.01 VERIFICATION OF CONDITIONS

- A. Verify that openings for glazing are correctly sized and within tolerances, including those for size, squareness, and offsets at corners.
- B. Verify that the minimum required face and edge clearances are being provided.
- C. Verify that surfaces of glazing channels or recesses are clean, free of obstructions that may impede moisture movement, weeps are clear, and support framing is ready to receive glazing system.
- D. Verify that sealing between joints of glass framing members has been completed effectively.
- E. Proceed with glazing system installation only after unsatisfactory conditions have been corrected.

### 3.02 PREPARATION

- A. Clean contact surfaces with appropriate solvent and wipe dry immediately before glazing. Remove coatings that are not tightly bonded to substrates.
- B. Seal porous glazing channels or recesses with substrate compatible primer or sealer.
- C. Prime surfaces scheduled to receive sealant where required for proper sealant adhesion.

### 3.03 INSTALLATION, GENERAL

- A. Install glazing in compliance with written instructions of glass, gaskets, and other glazing material manufacturers, unless more stringent requirements are indicated, including those in glazing referenced standards.
- B. Install glazing sealants in accordance with ASTM C1193, GANA (SM), and manufacturer's instructions.
- C. Do not exceed edge pressures around perimeter of glass lites as stipulated by glass manufacturer.

- D. Set glass lites of system with uniform pattern, draw, bow, and similar characteristics.
- E. Set glass lites in proper orientation so that coatings face exterior or interior as indicated.
- F. Prevent glass from contact with any contaminating substances that may be the result of construction operations such as, and not limited to the following; weld splatter, fire-safing, plastering, mortar droppings, etc.

#### **3.04 CLEANING**

- A. Remove excess glazing materials from finish surfaces immediately after application using solvents or cleaners recommended by manufacturers.
- B. Remove nonpermanent labels immediately after glazing installation is complete.
- C. Clean glass and adjacent surfaces after sealants are fully cured.
- D. Clean glass on both exposed surfaces not more than 4 days prior to Date of Substantial Completion in accordance with glass manufacturer's written recommendations.

#### **3.05 PROTECTION**

- A. After installation, mark pane with an 'X' by using removable plastic tape or paste; do not mark heat absorbing or reflective glass units.
- B. Remove and replace glass that is damaged during construction period prior to Date of Substantial Completion.

**END OF SECTION 08 8000**

This page intentionally left blank

**SECTION 09 0561**  
**COMMON WORK RESULTS FOR FLOORING PREPARATION**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. This section applies to floors identified in Contract Documents that are receiving the following types of floor coverings:
  1. Resilient tile and sheet.
  2. Thin-set porceramic tile and stone tile.
- B. Testing of concrete floor slabs for moisture and alkalinity (pH).
- C. Patching compound.
- D. Remedial floor coatings.
- E. Preparation of new wood-based floors for installation of new floor coverings.

**1.02 REFERENCE STANDARDS**

- A. ASTM C109/C109M - Standard Test Method for Compressive Strength of Hydraulic Cement Mortars (Using 50 mm [2 in.] Cube Specimens); 2023.
- B. ASTM C472 - Standard Test Methods for Physical Testing of Gypsum, Gypsum Plasters, and Gypsum Concrete; 2020.
- C. ASTM F710 - Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring; 2022.
- D. ASTM F1869 - Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride; 2023.
- E. ASTM F2170 - Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using *in situ* Probes; 2019a.
- F. RFCI (RWP) - Recommended Work Practices for Removal of Resilient Floor Coverings; 2018.

**1.03 ADMINISTRATIVE REQUIREMENTS**

- A. Coordinate scheduling of cleaning and testing, so that preliminary cleaning has been completed for at least 24 hours prior to testing.

**1.04 SUBMITTALS**

- A. Floor Covering and Adhesive Manufacturers' Product Literature: For each specific combination of substrate, floor covering, and adhesive to be used; showing:
  1. Moisture and alkalinity (pH) limits and test methods.
  2. Manufacturer's required bond/compatibility test procedure.
- B. Remedial Materials Product Data: Manufacturer's published data on each product to be used for remediation.
  1. Manufacturer's qualification statement.
  2. Certificate: Manufacturer's certification of compatibility with types of flooring applied over remedial product.
  3. Test reports indicating compliance with specified performance requirements, performed by nationally recognized independent testing agency.
  4. Manufacturer's installation instructions.
  5. Specimen Warranty: Copy of warranty to be issued by coating manufacturer and certificate of underwriter's coverage of warranty.
- C. Testing Agency's Report:
  1. Description of areas tested; include floor plans and photographs if helpful.
  2. Summary of conditions encountered.
  3. Moisture and alkalinity (pH) test reports.
  4. Copies of specified test methods.

- 5. Recommendations for remediation of unsatisfactory surfaces.
- 6. Product data for recommended remedial coating.
- 7. Certificate: Include certification of accuracy by authorized official of testing agency.
- 8. Submit report to Architect.
- 9. Submit report not more than two business days after conclusion of testing.
- D. Adhesive Bond and Compatibility Test Report.
- E. Floor Moisture Testing Technician Certificate: International Concrete Repair Institute (ICRI) Concrete Slab Moisture Testing Technician- Grade I certificate.
- F. Copy of RFCI (RWP).

## 1.05 QUALITY ASSURANCE

- A. Moisture and alkalinity (pH) testing shall be performed by an independent testing agency employed and paid by Contractor.
- B. Testing Agency Qualifications: Independent testing agency experienced in the types of testing specified.
  - 1. Submit evidence of experience consisting of at least 3 test reports of the type required, with project Owner's project contact information.
- C. Contractor's Responsibility Relating to Independent Agency Testing:
  - 1. Provide access for and cooperate with testing agency.
  - 2. Confirm date of start of testing at least 10 days prior to actual start.
  - 3. Allow at least 4 business days on site for testing agency activities.
  - 4. Achieve and maintain specified ambient conditions.
  - 5. Notify Architect when specified ambient conditions have been achieved and when testing will start.

## 1.06 DELIVERY, STORAGE, AND HANDLING

- A. Deliver, store, handle, and protect products in accordance with manufacturer's instructions and recommendations.
- B. Deliver materials in manufacturer's packaging; include installation instructions.
- C. Keep materials from freezing.

## 1.07 FIELD CONDITIONS

- A. Maintain ambient temperature in spaces where concrete testing is being performed, and for at least 48 hours prior to testing, at not less than 65 degrees F or more than 85 degrees F.
- B. Maintain relative humidity in spaces where concrete testing is being performed, and for at least 48 hours prior to testing, at not less than 40 percent and not more than 60 percent.

## PART 2 PRODUCTS

### 2.01 MATERIALS

- A. Patching Compound: Floor covering manufacturer's recommended product, suitable for conditions, and compatible with adhesive and floor covering. In the absence of any recommendation from flooring manufacturer, provide a product with the following characteristics:
  - 1. Cementitious moisture-, mildew-, and alkali-resistant compound, compatible with floor, floor covering, and floor covering adhesive, and capable of being feathered to nothing at edges.
  - 2. Compressive Strength: 3000 psi, minimum, after 28 days, when tested in accordance with ASTM C109/C109M or ASTM C472, whichever is appropriate.
- B. Alternate Flooring Adhesive: Floor covering manufacturer's recommended product, suitable for the moisture and pH conditions present; low-VOC. In the absence of any recommendation from flooring manufacturer, provide a product recommended by adhesive manufacturer as suitable for substrate and floor covering and for conditions present.

- C. Remedial Floor Coating: Single- or multi-layer coating or coating/overlay combination intended by its manufacturer to resist water vapor transmission to degree sufficient to meet flooring manufacturer's emission limits, resistant to the level of alkalinity (pH) found, and suitable for adhesion of flooring without further treatment.
  - 1. Thickness: As required for application and in accordance with manufacturer's installation instructions.
  - 2. Products:
    - a. LATICRETE International, Inc; LATICRETE SUPERCAP Moisture Vapor Control with LATICRETE SUPERCAP Underlayment: [www.laticrete.com/#sle](http://www.laticrete.com/#sle).
    - b. Substitutions: See Section 01 6000 - Product Requirements.

## PART 3 EXECUTION

### 3.01 CONCRETE SLAB PREPARATION

- A. Follow recommendations of testing agency.
- B. Perform following operations in the order indicated:
  - 1. Preliminary cleaning.
  - 2. Moisture vapor emission tests; 3 tests in the first 1000 square feet and one test in each additional 1000 square feet, unless otherwise indicated or required by flooring manufacturer.
  - 3. Internal relative humidity tests; in same locations as moisture vapor emission tests, unless otherwise indicated.
  - 4. Alkalinity (pH) tests; in same locations as moisture vapor emission tests, unless otherwise indicated.
  - 5. Specified remediation, if required.
  - 6. Patching, smoothing, and leveling, as required.
  - 7. Other preparation specified.
  - 8. Adhesive bond and compatibility test.
  - 9. Protection.
- C. Remediations:
  - 1. Active Water Leaks or Continuing Moisture Migration to Surface of Slab: Correct this condition before doing any other remediation; re-test after correction.
  - 2. Excessive Moisture Emission or Relative Humidity: If an adhesive that is resistant to the level of moisture present is available and acceptable to flooring manufacturer, use that adhesive for installation of the flooring; if not, apply remedial floor coating or remedial sheet membrane over entire suspect floor area.
  - 3. Excessive Alkalinity (pH): If remedial floor coating is necessary to address excessive moisture, no additional remediation is required; if not, if an adhesive that is resistant to the level present is available and acceptable to the flooring manufacturer, use that adhesive for installation of the flooring; otherwise, apply a skim coat of specified patching compound over entire suspect floor area.

### 3.02 PRELIMINARY CLEANING

- A. Clean floors of dust, solvents, paint, wax, oil, grease, asphalt, residual adhesive, adhesive removers, film-forming curing compounds, sealing compounds, alkaline salts, excessive laitance, mold, mildew, and other materials that might prevent adhesive bond.
- B. Do not use solvents or other chemicals for cleaning.

### 3.03 MOISTURE VAPOR EMISSION TESTING

- A. Where the floor covering manufacturer's requirements conflict with either the referenced test method or this specification, comply with the manufacturer's requirements.
- B. Where this specification conflicts with the referenced test method, comply with the requirements of this section.
- C. Test in accordance with ASTM F1869 and as follows.

- D. Plastic sheet test and mat bond test may not be substituted for the specified ASTM test method, as those methods do not quantify the moisture content sufficiently.
- E. In the event that test values exceed floor covering manufacturer's limits, perform remediation as indicated. In the absence of manufacturer limits, perform remediation if test values exceed 3 pounds per 1000 square feet per 24 hours.
- F. Report: Report the information required by the test method.

#### **3.04 INTERNAL RELATIVE HUMIDITY TESTING**

- A. Where the floor covering manufacturer's requirements conflict with either the referenced test method or this specification, comply with the manufacturer's requirements.
- B. Where this specification conflicts with the referenced test method, comply with the requirements of this section.
- C. Test in accordance with ASTM F2170 Procedure A and as follows.
- D. Testing with electrical impedance or resistance apparatus may not be substituted for the specified ASTM test method, as the values determined are not comparable to the ASTM test values and do not quantify the moisture content sufficiently.
- E. In the event that test values exceed floor covering manufacturer's limits, perform remediation as indicated. In the absence of manufacturer limits, perform remediation if any test value exceeds 75 percent relative humidity.
- F. Report: Report the information required by the test method.

#### **3.05 ALKALINITY TESTING**

- A. Where the floor covering manufacturer's requirements conflict with either the referenced test method or this specification, comply with the manufacturer's requirements.
- B. The following procedure is the equivalent of that described in ASTM F710, repeated here for the Contractor's convenience.
  1. Use a wide range alkalinity (pH) test paper, its associated chart, and distilled or deionized water.
  2. Place several drops of water on a clean surface of concrete, forming a puddle approximately 1 inch in diameter. Allow the puddle to set for approximately 60 seconds, then dip the alkalinity (pH) test paper into the water, remove it, and compare immediately to chart to determine alkalinity (pH) reading.
  3. Use of a digital pH meter with probe is acceptable; follow meter manufacturer's instructions.
- C. In the event that test values exceed floor covering manufacturer's limits, perform remediation as indicated. In the absence of manufacturer limits, perform remediation if alkalinity (pH) test value is over 10.

#### **3.06 PREPARATION**

- A. See individual floor covering section(s) for additional requirements.
- B. Comply with recommendations of testing agency.
- C. Comply with requirements and recommendations of floor covering manufacturer.
- D. Fill and smooth surface cracks, grooves, depressions, control joints and other non-moving joints, and other irregularities with patching compound.
- E. Do not fill expansion joints, isolation joints, or other moving joints.

#### **3.07 ADHESIVE BOND AND COMPATIBILITY TESTING**

- A. Comply with requirements and recommendations of floor covering manufacturer.

#### **3.08 APPLICATION OF REMEDIAL FLOOR COATING**

- A. Comply with requirements and recommendations of coating manufacturer.

### **3.09 PROTECTION**

- A. Cover prepared floors with building paper or other durable covering.

**END OF SECTION 09 0561**

This page intentionally left blank

**SECTION 09 2116**  
**GYPSUM BOARD ASSEMBLIES**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Performance criteria for gypsum board assemblies.
- B. Metal stud wall framing.
- C. Metal channel ceiling framing.
- D. Resilient sound isolation clips.
- E. Acoustic insulation.
- F. Gypsum sheathing.
- G. Gypsum wallboard.
- H. Joint treatment and accessories.
- I. Plenum space sound control.
- J. Acoustic (sound-dampening) wall and ceiling board.
- K. Noise barriers in gypsum board assemblies.

**1.02 REFERENCE STANDARDS**

- A. AISI S220 - North American Standard for Cold-Formed Steel Nonstructural Framing; 2020.
- B. AISI S240 - North American Standard for Cold-Formed Steel Structural Framing; 2015, with Errata (2020).
- C. ASTM A1003/A1003M - Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for Cold-Formed Framing Members; 2015.
- D. ASTM C1007 - Standard Specification for Installation of Load Bearing (Transverse and Axial) Steel Studs and Related Accessories; 2020.
- E. ASTM C475/C475M - Standard Specification for Joint Compound and Joint Tape for Finishing Gypsum Board; 2017 (Reapproved 2022).
- F. ASTM C665 - Standard Specification for Mineral-Fiber Blanket Thermal Insulation for Light Frame Construction and Manufactured Housing; 2023.
- G. ASTM C754 - Standard Specification for Installation of Steel Framing Members to Receive Screw-Attached Gypsum Panel Products; 2020.
- H. ASTM C840 - Standard Specification for Application and Finishing of Gypsum Board; 2023.
- I. ASTM C1047 - Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base; 2019.
- J. ASTM C1396/C1396M - Standard Specification for Gypsum Board; 2017.
- K. ASTM D3273 - Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber; 2021.
- L. ASTM E90 - Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements; 2023.
- M. ASTM E413 - Classification for Rating Sound Insulation; 2022.
- N. GA-216 - Application and Finishing of Gypsum Panel Products; 2024.

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Product Data:
  - 1. Provide data on metal framing, gypsum board, accessories, and joint finishing system.

- 2. Provide manufacturer's data on partition head to structure connectors, showing compliance with requirements.
- C. Shop Drawings: Indicate special details associated with fireproofing and acoustic seals.
- D. Test Reports: For stud framing products that do not comply with AISI S220 or ASTM C754, provide independent laboratory reports showing maximum stud heights at required spacings and deflections.

#### **1.04 QUALITY ASSURANCE**

- A. Designer Qualifications: Perform design under direct supervision of a Professional Engineer experienced in design of this type of work and licensed in the State in which the Project is located.
- B. Installer Qualifications: Company specializing in performing work of the type specified and with at least ten years of documented experience.

### **PART 2 PRODUCTS**

#### **2.01 GYPSUM BOARD ASSEMBLIES**

- A. Provide completed assemblies complying with ASTM C840 and GA-216.
- B. Interior Partitions, Indicated as Acoustic: Provide completed assemblies with the following characteristics:
  - 1. Acoustic Attenuation: STC as indicated calculated in accordance with ASTM E413, based on tests conducted in accordance with ASTM E90.

#### **2.02 METAL FRAMING MATERIALS**

- A. Steel Sheet: ASTM A1003/A1003M, subject to the ductility limitations indicated in AISI S220 or equivalent.
- B. Manufacturers - Metal Framing, Connectors, and Accessories:
  - 1. CEMCO: [www.cemcosteel.com/#sle](http://www.cemcosteel.com/#sle).
  - 2. ClarkDietrich: [www.clarkdietrich.com/#sle](http://www.clarkdietrich.com/#sle).
  - 3. Jaimes Industries: [www.jaimesind.com/#sle](http://www.jaimesind.com/#sle).
  - 4. Substitutions: See Section 01 6000 - Product Requirements.
- C. Nonstructural Framing System Components: AISI S220; galvanized sheet steel, of size and properties necessary to comply with ASTM C754 for the spacing indicated, with maximum deflection of wall framing of L/120 at 5 psf.
  - 1. Studs: C-shaped with knurled or embossed faces.
  - 2. Paired Studs for Sound-Rated Assemblies: Engineered single-piece assemblies comprised of paired studs coupled by sound isolators, designed to replace conventional side-by-side, parallel, double-wall partition framing.
  - 3. Runners: U shaped, sized to match studs.
  - 4. Ceiling Channels: C-shaped.

#### **2.03 BOARD MATERIALS**

- A. Gypsum Wallboard: Paper-faced gypsum panels as defined in ASTM C1396/C1396M; sizes to minimize joints in place; ends square cut.
  - 1. Application: Use for vertical surfaces and ceilings, unless otherwise indicated.
  - 2. Thickness:
    - a. Vertical Surfaces: 5/8 inch.
    - b. Ceilings: 1/2 inch.
- B. Acoustical Sound Dampening Wall and Ceiling Board: Two layers of heavy paper-faced, high-density gypsum board separated by a viscoelastic polymer layer and capable of achieving STC rating of 60 or more in typical stud wall assemblies as calculated in accordance with ASTM E413 and when tested in accordance with ASTM E90.
  - 1. Thickness: 5/8 inch.
  - 2. Long Edges: Tapered.

3. Mold Resistance: Score of 10, when tested in accordance with ASTM D3273.

## **2.04 GYPSUM BOARD ACCESSORIES**

- A. Acoustic Insulation: ASTM C665; preformed mineral-fiber, friction fit type, unfaced; thickness as required for STC.
- B. Acoustic Sealant: Acrylic emulsion latex or water-based elastomeric sealant; do not use solvent-based non-curing butyl sealant.
  1. Products:
    - a. Franklin International, Inc; Titebond Acoustical Smoke & Sound Sealant: [www.titebond.com/#sle](http://www.titebond.com/#sle).
- C. Beads, Joint Accessories, and Other Trim: ASTM C1047, galvanized steel or rolled zinc, unless noted otherwise.
  1. Corner Beads: Low profile, for 90 degree outside corners.
- D. Joint Materials: ASTM C475/C475M and as recommended by gypsum board manufacturer for project conditions.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify that project conditions are appropriate for work of this section to commence.

### **3.02 FRAMING INSTALLATION**

- A. Metal Framing: Install in accordance with ASTM C1007/AISI S220 and manufacturer's instructions.
- B. Suspended Ceilings and Soffits: Space framing and furring members as indicated.
- C. Studs: Space studs at 16 inches on center.
  1. Extend partition framing to structure where indicated and to ceiling in other locations.
  2. Partitions Terminating at Ceiling: Attach ceiling runner securely to ceiling track in accordance with manufacturer's instructions.

### **3.03 ACOUSTIC ACCESSORIES INSTALLATION**

- A. Acoustic Insulation: Place tightly within spaces, around cut openings, behind and around electrical and mechanical items within partitions, and tight to items passing through partitions.
- B. Acoustic Sealant: Install in accordance with manufacturer's instructions.

### **3.04 BOARD INSTALLATION**

- A. Comply with ASTM C840, GA-216, and manufacturer's instructions. Install to minimize butt end joints, especially in highly visible locations.
- B. Single-Layer Nonrated: Install gypsum board in most economical direction, with ends and edges occurring over firm bearing.
- C. Double-Layer, Nonrated: Use gypsum board for first layer, placed parallel to framing or furring members, with ends and edges occurring over firm bearing. Use glass mat faced gypsum board at exterior walls and at other locations as indicated. Place second layer perpendicular to framing or furring members. Offset joints of second layer from joints of first layer.
- D. Installation on Metal Framing: Use screws for attachment of gypsum board except face layer of nonrated double-layer assemblies, which may be installed by means of adhesive lamination.

### **3.05 INSTALLATION OF TRIM AND ACCESSORIES**

- A. Control Joints: Place control joints consistent with lines of building spaces and as indicated.
- B. Corner Beads: Install at external corners, using longest practical lengths.

### **3.06 JOINT TREATMENT**

- A. Finish gypsum board in accordance with levels defined in ASTM C840, as follows:

1. Level 5: Walls and ceilings to receive semi-gloss or gloss paint finish and other areas specifically indicated.
- B. Tape, fill, and sand exposed joints, edges, and corners to produce smooth surface ready to receive finishes.
  1. Feather coats of joint compound so that camber is maximum 1/32 inch.
- C. Where Level 5 finish is indicated, spray apply high build drywall surfer over entire surface after joints have been properly treated; achieve a flat and tool mark-free finish.

**END OF SECTION 09 2116**

## SECTION 09 3000 TILING

### PART 1 GENERAL

#### 1.01 SECTION INCLUDES

- A. Tile for floor applications.
- B. Tile for wall applications.
- C. Cementitious backer board as tile substrate.
- D. Coated glass mat backer board as tile substrate.
- E. Non-ceramic trim.
- F. Tile types and locations are indicated on drawings.
- G. Elastomeric joints at tile work (Control joints and soft joints).

#### 1.02 REFERENCE STANDARDS

- A. ANSI A108/A118/A136 - American National Standard Specifications for the Installation of Ceramic Tile (Compendium); 2024.
- B. ANSI A108.1a - American National Standard Specifications for Installation of Ceramic Tile in the Wet-Set Method, with Portland Cement Mortar; 2023.
- C. ANSI A108.1b - Installation of Ceramic Tile on a Cured Portland Cement Mortar Setting Bed with Dry-Set, Modified Dry-Set, or Improved Modified Dry-Set Cement Mortar; 2023.
- D. ANSI A108.1c - Contractor's Option: Installation of Ceramic Tile in the Wet-Set Method with Portland Cement Mortar or Installation of Ceramic Tile on a Cured Portland Cement Mortar Setting Bed with Dry-Set, Modified Dry-Set, or Improved Modified Dry-Set Cement Mortar; 2023.
- E. ANSI A108.2 - American National Standard General Requirements: Materials, Environmental and Workmanship; 2019.
- F. ANSI A108.4 - American National Standard Specifications for Installation of Ceramic Tile with Organic Adhesive or Water Cleanable Tile-Setting Epoxy Adhesive; 2023.
- G. ANSI A108.5 - Setting of Ceramic Tile with Dry-Set Cement Mortar, Modified Dry-Set Cement Mortar, EGP (Exterior Glue Plywood) Modified Dry-Set Cement Mortar, or Improved Modified Dry-Set Cement Mortar; 2023.
- H. ANSI A108.6 - American National Standard Specifications for Installation of Ceramic Tile with Chemical Resistant, Water Cleanable Tile-Setting and -Grout Epoxy; 2023.
- I. ANSI A108.8 - American National Standard Specifications for Installation of Ceramic Tile with Chemical Resistant Furan Resin Mortar and Grout; 1999 (Reaffirmed 2024).
- J. ANSI A108.9 - American National Standard Specifications for Installation of Ceramic Tile with Modified Epoxy Emulsion Mortar/Grout; 2023.
- K. ANSI A108.10 - American National Standard Specifications for Installation of Grout in Tilework; 2017 (Reaffirmed 2022).
- L. ANSI A108.11 - American National Standard Specifications for Interior Installation of Cementitious Backer Units; 2023.
- M. ANSI A108.12 - Installation of Ceramic Tile with EGP (Exterior Glue Plywood) Modified Dry-Set Mortar; 2023.
- N. ANSI A108.13 - American National Standard for Installation of Load Bearing, Bonded, Waterproof Membranes for Thin-Set Ceramic Tile and Dimension Stone; 2005 (Reaffirmed 2021).

- O. ANSI A108.19 - American National Standard Specifications for Interior Installation of Gauged Porcelain Tiles and Gauged Porcelain Tile Panels/Slabs by the Thin-Bed Method Bonded with Modified Dry-Set Cement Mortar or Improved Modified Dry-Set Cement Mortar; 2020.
- P. ANSI A108.20 - American National Standard Specifications for Exterior Installation of Gauged Porcelain Tiles and Gauged Porcelain Tile Panels/Slabs; 2020.
- Q. ANSI A118.3 - American National Standard Specifications for Chemical Resistant, Water Cleanable Tile-Setting and -Grouting Epoxy and Water Cleanable Tile-Setting Epoxy Adhesive; 2021.
- R. ANSI A118.4 - American National Standard Specifications for Modified Dry-Set Cement Mortar; 2023.
- S. ANSI A118.6 - American National Standard Specifications for Standard Cement Grouts for Tile Installation; 2019.
- T. ANSI A118.7 - American National Standard Specifications for High Performance Cement Grouts for Tile Installation; 2019.
- U. ANSI A118.9 - American National Standard Specifications for Test Methods and Specifications for Cementitious Backer Units; 2023.
- V. ANSI A118.10 - American National Standard Specifications for Load Bearing, Bonded, Waterproof Membranes for Thin-Set Ceramic Tile and Dimension Stone Installation; 2023.
- W. ANSI A118.12 - American National Standard Specifications for Crack Isolation Membranes for Thin-Set Ceramic Tile and Dimension Stone Installation; 2014 (Reaffirmed 2024).
- X. ANSI A118.13 - American National Standard Specification for Bonded Sound Reduction Membranes for Thin-Set Ceramic Tile Installation; 2014 (Reaffirmed 2024).
- Y. ANSI A118.15 - American National Standard Specifications for Improved Modified Dry-Set Cement Mortar; 2023.
- Z. ANSI A136.1 - American National Standard Specifications for Organic Adhesives for Installation of Ceramic Tile; 2020.
- AA. ANSI A137.1 - American National Standard Specifications for Ceramic Tile; 2022.
- BB. ASTM C373 - Standard Test Methods for Determination of Water Absorption and Associated Properties by Vacuum Method for Pressed Ceramic Tiles and Glass Tiles and Boil Method for Extruded Ceramic Tiles and Non-tile Fired Ceramic Whiteware Products; 2018 (Reapproved 2023).
- CC. ASTM C1178/C1178M - Standard Specification for Coated Glass Mat Water-Resistant Gypsum Backing Panel; 2018.
- DD. ASTM D4068 - Standard Specification for Chlorinated Polyethylene (CPE) Sheeting for Concealed Water-Containment Membrane; 2017 (Reapproved 2022).
- EE. ASTM E492 - Standard Test Method for Laboratory Measurement of Impact Sound Transmission through Floor-Ceiling Assemblies Using the Tapping Machine; 2022.
- FF. ASTM E2179 - Standard Test Method for Laboratory Measurement of the Effectiveness of Floor Coverings in Reducing Impact Sound Transmission Through Concrete Floors; 2025.
- GG. ICC-ES AC380 - Acceptance Criteria for Termite Physical Barrier Systems; 2021, with Editorial Revision (2022).
- HH. TCNA (HB) - Handbook for Ceramic, Glass, and Stone Tile Installation; 2025.

### **1.03 ADMINISTRATIVE REQUIREMENTS**

- A. Preinstallation Meeting: Convene a preinstallation meeting one week before starting work of this section; require attendance by affected installers.

### **1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.

- B. Product Data: Provide manufacturers' data sheets on tile, mortar, grout, and accessories. Include instructions for using grouts and adhesives.
  - 1. For adhesives and sealants, include printed statement of VOC content.
- C. Shop Drawings: Indicate tile layout, patterns, color arrangement, perimeter conditions, junctions with dissimilar materials, control and expansion joints, thresholds, ceramic accessories, and setting details.
- D. Samples: Mount tile and apply grout on two plywood panels, minimum 18 by 18 inches in size illustrating pattern, color variations, and grout joint size variations.
- E. Manufacturer's Certificate: Certify that products meet or exceed specified requirements.
- F. Installer's Qualification Statement:
- G. Maintenance Data: Include recommended cleaning methods, cleaning materials, and stain removal methods.
- H. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
  - 1. See Section 01 6000 - Product Requirements, for additional provisions.
  - 2. Extra Tile: 5 percent of each size, color, and surface finish combination, but not less than ten of each type.

## 1.05 QUALITY ASSURANCE

- A. Maintain one copy of and ANSI A108/A118/A136 and TCNA (HB) on site.
- B. Manufacturer Qualifications: Company specializing in manufacturing the types of products specified in this section, with minimum five years of documented experience.
- C. Installer Qualifications: Natural Stone Institute (NSI) Accredited Commercial B Contractor (light commercial): [www.naturalstoneinstitute.org/#sle](http://www.naturalstoneinstitute.org/#sle).
- D. Installer Qualifications:
  - 1. Company specializing in performing tile installation, with minimum of five years of documented experience.
- E. Single-Source Responsibility for Setting and Grouting Materials: Obtain ingredients of a uniform quality from one manufacturer for each cementitious and admixture component and from one source or producer for each aggregate.

## 1.06 DELIVERY, STORAGE, AND HANDLING

- A. Protect adhesives from freezing or overheating in accordance with manufacturer's instructions.

## 1.07 FIELD CONDITIONS

- A. Do not install solvent-based products in an unventilated environment.
- B. Maintain ambient and substrate temperature above 50 degrees F and below 100 degrees F during installation and curing of setting materials.

# PART 2 PRODUCTS

## 2.01 TILE

- A. General: Provide tile that complies with ANSI A137.1 for types, compositions and other characteristics indicated. Provide tile in the locations and of the types colors and pattern indicated on the Drawings. Tile shall also be provided in accordance with the following:
  - 1. Factory Blending: For tile exhibiting color variations within the ranges selected under Submittal of samples, blend tile in the factory and package so tile taken from one package shows the same range of colors as those taken from other packages.
  - 2. Factory Applied Temporary Protective Coatings: Where required by tile type and manufacturer's specifications, protect exposed surfaces of tile against adherence of mortar and grout by pre-coating with a continuous film of petroleum paraffin wax applied hot. Do not coat unexposed tile surfaces.
- B. Manufacturers: As indicated on drawings .
  - 1. Substitutions: See Section 01 6000 - Product Requirements.

- C. Porcelain Tile: ANSI A137.1 standard grade.
  - 1. Size: As indicated in Drawings.
  - 2. Color(s): As indicated on drawings.
  - 3. Pattern: As indicated on drawings.

## 2.02 TRIM AND ACCESSORIES

- A. Trim: Satin natural anodized extruded aluminum, style and dimensions to suit application, for setting using tile mortar or adhesive. Unless more stringent conditions are indicated on drawings, for setting using tile mortar or adhesive.
  - 1. Applications:
    - a. Open edges of wall tile.
    - b. Open edges of floor tile.
    - c. Wall corners, outside and inside.
    - d. Transition between floor finishes of different heights.
    - e. Thresholds at door openings.
    - f. Expansion and control joints, floor and wall.
    - g. Floor to wall joints.
    - h. Borders and other trim as indicated on drawings.
    - i. As indicated on drawings and as required for application.
  - 2. Manufacturers:
    - a. Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
    - b. Schluter-Systems: [www.schluter.com/#sle](http://www.schluter.com/#sle).
    - c. Substitutions: See Section 01 6000 - Product Requirements.

## 2.03 SETTING MATERIALS

- A. Manufacturers:
  - 1. Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
  - 2. Custom Building Products: [www.custombuildingproducts.com/#sle](http://www.custombuildingproducts.com/#sle).
  - 3. LATICRETE International, Inc: [www.laticrete.com/#sle](http://www.laticrete.com/#sle).
  - 4. Mapei; [www.mapei.com](http://www.mapei.com).
  - 5. Substitutions: See Section 01 6000 - Product Requirements.
- B. Latex-Portland Cement Mortar Bond Coat: ANSI A118.4.
  - 1. Applications: Use this type of bond coat where Large and Heavy Tile (LHT) mortar is indicated.
- C. Epoxy Adhesive and Mortar Bond Coat: ANSI A118.3.
  - 1. Applications: Wet Locations.
- D. Organic Adhesive: ANSI A136.1, thinset mastic type.
  - 1. Applications: Dry locations.
- E. Mortar Bed Materials: Pre-packaged mix of Portland cement, sand, latex additive, and water.

## 2.04 GROUTS

- A. Standard Grout: ANSI A118.6 standard cement grout.
  - 1. Applications: Use this type of grout where indicated unless otherwise indicated as wet location.
  - 2. Use sanded grout for joints 1/8 inch wide and larger; use unsanded grout for joints less than 1/8 inch wide.
  - 3. Color(s): As selected by Architect from manufacturer's full line.
- B. Epoxy Grout: ANSI A118.3 chemical resistant and water-cleanable epoxy grout.
  - 1. Applications: Kitchens and Wet Locations and as required for application.
  - 2. Color(s): As selected by Architect from manufacturer's full line.

## 2.05 MAINTENANCE MATERIALS

- A. General: Provide sealants, primers, backer rods, and other sealant accessories that comply with the following requirements and with the applicable requirements in Division 07 Section "Joint Sealants."
- B. Sealant / soft joint color: Match grout color unless otherwise indicated on drawings.
- C. Tile Sealant: Gunnable, silicone, siliconized acrylic, or urethane sealant; moisture and mildew resistant type.
  - 1. Applications:
    - a. Between tile and plumbing fixtures.
    - b. Between tile and adjacent materials.
    - c. Inside tile corners.
    - d. At wall to floor and wall to ceiling transitions.
    - e. Control joint locations as recommended by TCNA EJ171 and where indicated on drawings. If not indicated on drawings, follow TCNA recommendations.
      - 1) Tile control joints adjacent to gypsum board wall control joints: Provide tile soft joint / control joint to follow tile installation pattern. Do not cut tile. Install tile soft joint / control joint as close as possible to adjacent gypsum board wall control joint.
  - 2. Color(s): As selected by Architect from manufacturer's full line.
- D. Grout Sealer: Liquid-applied, moisture and stain protection for existing or new Portland cement grout.
  - 1. Composition: Water-based colorless silicone.

## 2.06 ACCESSORY MATERIALS

- A. Waterproofing Membrane at floors and walls: Specifically designed for bonding to cementitious substrate under thick mortar bed or thin-set tile; complying with ANSI A118.10.
  - 1. Crack Resistance: No failure at 1/16 inch gap, minimum; comply with ANSI A118.12.
- B. Waterproofing Membrane at shower and wet locations: Specifically designed for bonding to cementitious substrate under thick mortar bed or thin-set tile; complying with ANSI A118.10.
  - 1. Fluid or Trowel Applied Type:
    - a. Material: Synthetic rubber.
    - b. Material: Acrylic.
    - c. Thickness: 40 mils, minimum, dry film thickness.
- C. Waterproofing Membrane Under Thick Mortar Bed at showers and wet locations:
  - 1. Material: Chlorinated polyethylene sheet, 40 mils thick, minimum; complying with ASTM D4068.
- D. Reinforcing Mesh: 2 by 2 inch size weave of 16/16 wire size; welded fabric, galvanized.
- E. Underlayment at Floors: Specifically designed for bonding to thin-set setting mortar; not primarily a waterproofing material and having the following characteristics:
  - 1. Sound Reduction: Comply with ANSI A118.13 bonded membrane, ASTM E492, and ASTM E2179.
  - 2. Crack Resistance: No failure at 1/16 inch gap, minimum; comply with ANSI A118.12.
  - 3. Water Resistance: Comply with ANSI A118.10, bonded waterproofing.
  - 4. Termite Resistance: 100 percent when tested in accordance with ICC-ES AC380.
  - 5. Uncoupling Function: Allow for separation between membrane and the mortar adhering tile to the membrane when subjected to excessive substrate movement.
  - 6. Suitable for installation over green concrete.
  - 7. Suitable for installation over wood-based substrates.
  - 8. Type: Fluid or Trowel Applied.
- F. Backer Board: Cementitious type complying with ANSI A118.9; high density, glass fiber reinforced, 1/2 inch thick; 2 inch wide coated glass fiber tape for joints and corners.

- G. Backer Board: Coated glass mat type complying with ASTM C1178/C1178M; inorganic fiberglass mat on both surfaces and integral acrylic coating vapor retarder.
  - 1. Standard Type: Thickness 1/2 inch.
- H. Backer Board: High density polystyrene with reinforced cementitious coating on both sides; with compatible alkaline resistant joint tape; to be covered with waterproofing prior to installation of tile.
  - 1. Thickness: 1/2 inch.
- I. Mesh Tape: 2 inch wide self-adhesive fiberglass mesh tape.

### **PART 3 EXECUTION**

#### **3.01 EXAMINATION**

- A. Verify that subfloor surfaces are smooth and flat within the tolerances specified for that type of work and are ready to receive tile.
- B. Verify that wall surfaces are smooth and flat within the tolerances specified for that type of work, are dust-free, and are ready to receive tile.
- C. Verify that subfloor surfaces are dust free and free of substances that could impair bonding of setting materials to subfloor surfaces.
- D. Verify that required floor-mounted utilities are in correct location.

#### **3.02 PREPARATION**

- A. Protect surrounding work from damage.
- B. Vacuum clean surfaces and damp clean.
- C. Seal substrate surface cracks with filler. Level existing substrate surfaces to acceptable flatness tolerances.
- D. Install backer board in accordance with ANSI A108.11 and board manufacturer's instructions. Tape joints and corners, cover with skim coat of setting material to a feather edge.
- E. Prepare substrate surfaces for adhesive installation in accordance with adhesive manufacturer's instructions.
- F. Expansion Joints: Provide expansion joints and other sealant-filled joints, including control, contraction, and isolation joints, where indicated on drawings and where required by TCNA Installation Details. Form joints during installation of setting materials, mortar beds, and tile. Do not saw-cut joints after installing tiles.
- G. Blending: For tile exhibiting color variations, use factory blended tile or blend tiles at Project site before installing.

#### **3.03 INSTALLATION - GENERAL**

- A. Install tile, thresholds, and accessories and grout in accordance with applicable requirements of ANSI A108.1a through ANSI A108.20, manufacturer's instructions, and TCNA (HB) recommendations.
- B. Lay tile to pattern indicated. Do not interrupt tile pattern through openings.
  - 1. If tile pattern is not indicated, request tile pattern from Architect prior to installation. Random tile placement is not allowed.
- C. Cut and fit tile to penetrations through tile, leaving sealant joint space. Form corners and bases neatly. Align joints as indicated.
  - 1. If alignment is not indicated, request from Architect prior to installation.
- D. Place tile joints uniform in width, subject to variance in tolerance allowed in tile size. Make grout joints without voids, cracks, excess mortar or excess grout, or too little grout.
- E. Form internal angles square and external angles square.
  - 1. Unless otherwise indicated.
- F. Install ceramic accessories rigidly in prepared openings.

- G. Install non-ceramic trim in accordance with manufacturer's instructions.
- H. Install thresholds where indicated.
- I. Sound tile after setting. Replace hollow sounding units.
- J. Keep control and expansion joints free of mortar, grout, and adhesive.
- K. Prior to grouting, allow installation to completely cure; minimum of 48 hours.
- L. Grout tile joints unless otherwise indicated.
- M. At changes in plane and tile-to-tile control joints, use tile sealant instead of grout, with either bond breaker tape or backer rod as appropriate to prevent three-sided bonding.
- N. Exposed unfinished tile edges are not allowed.
- O. Do not install defective tile.
- P. Cutting: Saw cut only.
- Q. Provide uniform soft joint and spacing between tile and floor drains, cleanout covers and other floor or wall devices. Jagged or cracked tile is not allowed.

### **3.04 INSTALLATION - FLOORS - THIN-SET METHODS**

- A. Over exterior concrete substrates, install in accordance with TCNA (HB) Method F102, with specified grout.
- B. Over interior concrete substrates, install in accordance with TCNA (HB) Method F113, dry-set or latex-Portland cement bond coat, with standard grout, unless otherwise indicated.
  - 1. Where waterproofing membrane is indicated, install in accordance with TCNA (HB) Method F122, with latex-Portland cement grout.
  - 2. Where epoxy bond coat and grout are indicated, install in accordance with TCNA (HB) Method F131.
  - 3. Where epoxy or furan grout is indicated, but not epoxy or furan bond coat, install in accordance with TCNA (HB) Method F115.
- C. Over wood substrates, install in accordance with TCNA (HB) Method F142, with standard grout, unless otherwise indicated.
  - 1. Where epoxy bond coat and grout are indicated, install in accordance with TCNA (HB) Method F143.
- D. Over wood substrate with backer board underlayment, install in accordance with TCNA (HB) Method F144, for cementitious backer boards, with epoxy grout.
- E. Install tile-to-tile floor movement joints in accordance with TCNA (HB) Method EJ171F.

### **3.05 INSTALLATION - FLOORS - MORTAR BED METHODS**

- A. Over exterior concrete substrates, install in accordance with TCNA (HB) Method F101, bonded, with epoxy grout.
- B. Over interior concrete substrates, install in accordance with TCNA (HB) Method F111, with cleavage membrane, unless otherwise indicated.
  - 1. Where epoxy bond coat and grout are indicated, install in accordance with TCNA (HB) Method F132, bonded.
  - 2. Where epoxy or furan grout is indicated, but not epoxy or furan bond coat, install in accordance with TCNA (HB) Method F114, with cleavage membrane.
- C. Over wood substrates, install in accordance with TCNA (HB) Method F141, with standard grout, unless otherwise indicated.
- D. Cleavage Membrane: Lap edges and ends.
- E. Waterproofing Membrane: Install as recommended by manufacturer and as specified in the section in which the product is specified.
- F. Mortar Bed Thickness: 5/8 inch, unless otherwise indicated.

### **3.06 INSTALLATION - WALL TILE**

- A. On exterior walls install in accordance with TCNA (HB) Method W244, thin-set over cementitious backer units, with waterproofing membrane.
- B. Over cementitious backer units on studs, install in accordance with TCNA (HB) Method W244, using membrane at toilet rooms.
- C. Over coated glass mat backer board on studs, install in accordance with TCNA (HB) Method W245.
- D. Over gypsum wallboard on wood or metal studs install in accordance with TCNA (HB) Method W243, thin-set with dry-set or latex-Portland cement bond coat, unless otherwise indicated.
  - 1. Where mortar bed is indicated, install in accordance with TCNA (HB) Method W222, one coat method.
  - 2. Where waterproofing membrane is indicated other than at showers and bathtub walls, install in accordance with TCNA (HB) Method W222, one coat method.
- E. Over metal studs without backer install in accordance with TCNA (HB) Method W241, mortar bed, with membrane where indicated.
- F. Wall Tile: Center wall tile within room or space, unless specifically noted otherwise.

### **3.07 CLEANING**

- A. Clean tile and grout surfaces.

### **3.08 PROTECTION**

- A. Do not permit traffic over finished floor surface for 4 days after installation.

**END OF SECTION 09 3000**

**SECTION 09 5100**  
**ACOUSTICAL CEILINGS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Suspended metal grid ceiling system.
- B. Acoustical units.

**1.02 REFERENCE STANDARDS**

- A. ASTM C636/C636M - Standard Practice for Installation of Metal Ceiling Suspension Systems for Acoustical Tile and Lay-In Panels; 2019 (Reapproved 2025).
- B. ASTM E580/E580M - Standard Practice for Installation of Ceiling Suspension Systems for Acoustical Tile and Lay-in Panels in Areas Subject to Earthquake Ground Motions; 2024a.
- C. ASTM E1264 - Standard Classification for Acoustical Ceiling Products; 2023.

**1.03 ADMINISTRATIVE REQUIREMENTS**

- A. Sequence work to ensure acoustical ceilings are not installed until building is enclosed, sufficient heat is provided, dust generating activities have terminated, and overhead work is completed, tested, and approved.
- B. Do not install acoustical units until after interior wet work is dry.

**1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Shop Drawings: Indicate grid layout and related dimensioning.
- C. Product Data: Provide data on suspension system components.
- D. Samples: Submit two samples 12x12 inch in size illustrating material and finish of acoustical units.

**1.05 QUALITY ASSURANCE**

- A. Suspension System Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years documented experience.
- B. Acoustical Unit Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum three years documented experience.

**1.06 FIELD CONDITIONS**

- A. Maintain uniform temperature of minimum 60 degrees F, and maximum humidity of 40 percent prior to, during, and after acoustical unit installation.

**PART 2 PRODUCTS**

**2.01 MANUFACTURERS**

- A. Acoustic Tiles/Panels:
  1. Armstrong World Industries, Inc: [www.armstrong.com/#sle](http://www.armstrong.com/#sle).
  2. Substitutions: See Section 01 6000 - Product Requirements.
- B. Suspension Systems:
  1. Same as for acoustical units.

**2.02 ACOUSTICAL UNITS**

- A. Acoustical Tile: Painted mineral fiber, ASTM E1264 Type III, with the following characteristics:
  1. Size: As indicated on drawings.
  2. Thickness: 5/8 inches.
  3. Edge: Square.
  4. Surface Color: White.
  5. Products:

- a. As indicated in drawings.

## **2.03 SUSPENSION SYSTEM(S)**

- A. Metal Suspension Systems - General: Complying with ASTM C635/C635M; die cut and interlocking components, with stabilizer bars, clips, splices, perimeter moldings, and hold down clips as required.
- B. Exposed Suspension System: Formed galvanized steel, commercial quality cold rolled; intermediate-duty.
  1. Profile: Tee; 15/16 inch wide face, unless noted otherwise.
  2. Construction: Double web.
  3. Finish: As indicated on drawings.

## **2.04 ACCESSORIES**

- A. Support Channels and Hangers: Galvanized steel; size and type to suit application, seismic requirements, and ceiling system flatness requirement specified.
  1. At Exposed Grid: Provide L-shaped molding for mounting at same elevation as face of grid.
- B. Perimeter Moldings: Same material and finish as grid.
- C. Touch-up Paint: Type and color to match acoustical and grid units.

# **PART 3 EXECUTION**

## **3.01 EXAMINATION**

- A. Verify existing conditions before starting work.
- B. Verify that layout of hangers will not interfere with other work.

## **3.02 INSTALLATION - SUSPENSION SYSTEM**

- A. Install suspension system in accordance with ASTM C636/C636M, ASTM E580/E580M, ASTM C636/C636M, ASTM E580/E580M, ASTM C636/C636M, and ASTM E580/E580M and as supplemented in this section.
- B. Rigidly secure system, including integral mechanical and electrical components, for maximum deflection of 1:360.
- C. Locate system on room axis according to reflected plan.
- D. Install after major above-ceiling work is complete. Coordinate the location of hangers with other work.
- E. Hang suspension system independent of walls, columns, ducts, pipes and conduit. Where carrying members are spliced, avoid visible displacement of face plane of adjacent members.
- F. Where ducts or other equipment prevent the regular spacing of hangers, reinforce the nearest affected hangers and related carrying channels to span the extra distance.
- G. Do not support components on main runners or cross runners if weight causes total dead load to exceed deflection capability.
- H. Support fixture loads using supplementary hangers located within 6 inches of each corner, or support components independently.
- I. Do not eccentrically load system or induce rotation of runners.
  1. Use longest practical lengths.
  2. Overlap and rivet corners.

## **3.03 INSTALLATION - ACOUSTICAL UNITS**

- A. Install acoustical units in accordance with manufacturer's instructions.
- B. Fit acoustical units in place, free from damaged edges or other defects detrimental to appearance and function.
- C. Fit border trim neatly against abutting surfaces.

- D. Install units after above-ceiling work is complete.
- E. Install acoustical units level, in uniform plane, and free from twist, warp, and dents.
- F. Cutting Acoustical Units:
  - 1. Make field cut edges of same profile as factory edges.

#### **3.04 TOLERANCES**

- A. Maximum Variation from Flat and Level Surface: 1/8 inch in 10 feet.
- B. Maximum Variation from Plumb of Grid Members Caused by Eccentric Loads: 2 degrees.

**END OF SECTION 09 5100**

This page intentionally left blank

**SECTION 09 6500  
RESILIENT FLOORING**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Resilient tile flooring.
- B. Resilient base.
- C. Installation accessories.

**1.02 REFERENCE STANDARDS**

- A. ASTM F1066 - Standard Specification for Vinyl Composition Floor Tile; 2023.

**1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data on specified products, describing physical and performance characteristics; including sizes, patterns and colors available; and installation instructions.
- C. Shop Drawings: Indicate seaming plans and floor patterns.
- D. Selection Samples: Submit manufacturer's complete set of color samples for Architect's initial selection.
- E. Verification Samples: Submit two samples, 12 by 12 inch in size illustrating color and pattern for each resilient flooring product specified.
- F. Concrete Testing Standard: Submit a copy of ASTM F710.
- G. Certification: Prior to installation of flooring, submit written certification by flooring manufacturer and adhesive manufacturer that condition of sub-floor is acceptable.
- H. Maintenance Data: Include maintenance procedures, recommended maintenance materials, and suggested schedule for cleaning, stripping, and re-waxing.
- I. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
  - 1. See Section 01 6000 - Product Requirements, for additional provisions.
  - 2. Extra Flooring Material: 1 square feet of each type and color.
  - 3. Extra Wall Base: 100 linear feet of each type and color.
  - 4. Extra Stair Materials: Quantity equivalent to 5 percent of each type and color.

**1.04 DELIVERY, STORAGE, AND HANDLING**

- A. Protect roll materials from damage by storing on end.

**1.05 FIELD CONDITIONS**

- A. Maintain temperature in storage area between 55 degrees F and 90 degrees F.
- B. Store materials for not less than 48 hours prior to installation in area of installation at a temperature of 70 degrees F to achieve temperature stability. Thereafter, maintain conditions above 55 degrees F.

**PART 2 PRODUCTS**

**2.01 TILE FLOORING**

- A. Luxury Vinyl Tile:
  - 1. Manufacturers:
    - a. As indicated on drawings.
    - b. Substitutions: See Section 01 6000 - Product Requirements.
  - 2. Minimum Requirements: Comply with ASTM F1066, of Class corresponding to type specified.
  - 3. Size: As indicated on drawings.
  - 4. Color: As indicated on drawings.

## **2.02 RESILIENT BASE**

- A. Resilient Base: ASTM F1861, Type TS rubber, vulcanized thermoset; top set Style B, Cove.
  - 1. Manufacturers:
    - a. As indicated on drawings.
    - b. Substitutions: See Section 01 6000 - Product Requirements.
  - 2. Length: Roll.
  - 3. Color: As indicated on drawings.

## **2.03 ACCESSORIES**

- A. Subfloor Filler: White premix latex; type recommended by adhesive material manufacturer.
- B. Primers, Adhesives, and Seam Sealer: Waterproof; types recommended by flooring manufacturer.
- C. Moldings, Transition and Edge Strips: Same material as flooring.
- D. Filler for Coved Base: Plastic.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify that surfaces are flat to tolerances acceptable to flooring manufacturer, free of cracks that might telegraph through flooring, clean, dry, and free of curing compounds, surface hardeners, and other chemicals that might interfere with bonding of flooring to substrate.
- B. Verify that wall surfaces are smooth and flat within the tolerances specified for that type of work, are dust-free, and are ready to receive resilient base.

### **3.02 PREPARATION**

- A. Prepare floor substrates as recommended by flooring and adhesive manufacturers.
- B. Remove sub-floor ridges and bumps. Fill minor low spots, cracks, joints, holes, and other defects with sub-floor filler to achieve smooth, flat, hard surface.
- C. Prohibit traffic until filler is fully cured.
- D. Clean substrate.

### **3.03 INSTALLATION - GENERAL**

- A. Install in accordance with manufacturer's written instructions.
- B. Spread only enough adhesive to permit installation of materials before initial set.
- C. Fit joints and butt seams tightly.
- D. Set flooring in place, press with heavy roller to attain full adhesion.
- E. Where type of floor finish, pattern, or color are different on opposite sides of door, terminate flooring under centerline of door.
- F. Install edge strips at unprotected or exposed edges, where flooring terminates, and where indicated.
- G. Scribe flooring to walls, columns, cabinets, floor outlets, and other appurtenances to produce tight joints.

### **3.04 INSTALLATION - TILE FLOORING**

- A. Mix tile from container to ensure shade variations are consistent when tile is placed, unless otherwise indicated in manufacturer's installation instructions.

### **3.05 INSTALLATION - RESILIENT BASE**

- A. Fit joints tightly and make vertical. Maintain minimum dimension of 18 inches between joints.
- B. Install base on solid backing. Bond tightly to wall and floor surfaces.

### **3.06 CLEANING**

- A. Remove excess adhesive from floor, base, and wall surfaces without damage.
- B. Clean in accordance with manufacturer's written instructions.

### **3.07 PROTECTION**

- A. Prohibit traffic on resilient flooring for 48 hours after installation.

**END OF SECTION 09 6500**

This page intentionally left blank

## SECTION 09 9123 INTERIOR PAINTING

### **PART 1 GENERAL**

#### **1.01 SECTION INCLUDES**

- A. Surface preparation.
- B. Field application of paints.
- C. Scope: Finish interior surfaces exposed to view, unless fully factory-finished and unless otherwise indicated.
- D. Do Not Paint or Finish the Following Items:
  - 1. Items factory-finished unless otherwise indicated; materials and products having factory-applied primers are not considered factory finished.
  - 2. Items indicated to receive other finishes.
  - 3. Items indicated to remain unfinished.
  - 4. Fire rating labels, equipment serial number and capacity labels, bar code labels, and operating parts of equipment.
  - 5. Floors, unless specifically indicated.
  - 6. Glass.
  - 7. Concealed pipes, ducts, and conduits.

#### **1.02 REFERENCE STANDARDS**

- A. MPI (APSM) - Master Painters Institute Architectural Painting Specification Manual; Current Edition.
- B. SSPC-SP 1 - Solvent Cleaning; 2015, with Editorial Revision (2016).
- C. SSPC-SP 6 - Commercial Blast Cleaning; 2007.

#### **1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide complete list of products to be used, with the following information for each:
  - 1. Manufacturer's name, product name and/or catalog number, and general product category (e.g., "alkyd enamel").
  - 2. MPI product number (e.g., MPI #47).
  - 3. Cross-reference to specified paint system(s) product is to be used in; include description of each system.
- C. Samples: Submit three paper "draw down" samples, 8-1/2 by 11 inches in size, illustrating range of colors available for each finishing product specified.
  - 1. Where sheen is specified, submit samples in only that sheen.

#### **1.04 QUALITY ASSURANCE**

- A. Manufacturer Qualifications: Company specializing in manufacturing the products specified, with minimum three years documented experience.
- B. Applicator Qualifications: Company specializing in performing the type of work specified with minimum ten years experience and approved by manufacturer.

### **PART 2 PRODUCTS**

#### **2.01 MANUFACTURERS**

- A. Provide paints and finishes used in any individual system from the same manufacturer; no exceptions.
- B. Paints:
  - 1. Pittsburgh Paints: [www.ppgpaints.com/#sle](http://www.ppgpaints.com/#sle).
  - 2. Sherwin-Williams Company: [www.sherwin-williams.com/#sle](http://www.sherwin-williams.com/#sle).

## **2.02 PAINTS AND FINISHES - GENERAL**

- A. Paints and Finishes: Ready-mixed, unless intended to be a field-catalyzed paint.
  - 1. Provide paints and finishes of a soft paste consistency, capable of being readily and uniformly dispersed to a homogeneous coating, with good flow and brushing properties, and capable of drying or curing free of streaks or sags.
  - 2. Supply each paint material in quantity required to complete entire project's work from a single production run.
  - 3. Do not reduce, thin, or dilute paint or finishes or add materials unless such procedure is specifically described in manufacturer's product instructions.
- B. Colors: To be selected from manufacturer's full range of available colors.
  - 1. Selection to be made by Architect after award of contract. Unless noted otherwise.

## **2.03 PAINT SYSTEMS - INTERIOR**

- A. Paint I-OP-MD-DT - Medium Duty Door/Trim: For surfaces subject to frequent contact by occupants, including metals and wood:
  - 1. Two top coats and one coat primer.
- B. Paint I-OP-MD-WC - Medium Duty Vertical and Overhead: Including gypsum board, plaster, concrete, concrete masonry units, uncoated steel, shop primed steel, galvanized steel, and aluminum.
  - 1. Two top coats and one coat primer.

## **2.04 PRIMERS**

- A. Primers: Provide the following unless other primer is required or recommended by manufacturer of top coats.

## **2.05 ACCESSORY MATERIALS**

- A. Accessory Materials: Provide primers, sealers, cleaning agents, cleaning cloths, sanding materials, and clean-up materials as required for final completion of painted surfaces.
- B. Patching Material: Latex filler.
- C. Fastener Head Cover Material: Latex filler.

## **PART 3 EXECUTION**

### **3.01 PREPARATION**

- A. Clean surfaces thoroughly and correct defects prior to application.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.
- C. Remove or mask surface appurtenances, including electrical plates, hardware, light fixture trim, escutcheons, and fittings, prior to preparing surfaces or finishing.
- D. Seal surfaces that might cause bleed through or staining of topcoat.
- E. Gypsum Board: Fill minor defects with filler compound. Spot prime defects after repair.
- F. Ferrous Metal:
  - 1. Solvent clean according to SSPC-SP 1.
  - 2. Shop-Primed Surfaces: Sand and scrape to remove loose primer and rust. Feather edges to make touch-up patches inconspicuous. Clean surfaces with solvent. Prime bare steel surfaces. Re-prime entire shop-primed item.
  - 3. Remove rust, loose mill scale, and other foreign substances using methods recommended in writing by paint manufacturer and blast cleaning according to SSPC-SP 6 "Commercial Blast Cleaning". Protect from corrosion until coated.
- G. Wood Surfaces to Receive Opaque Finish: Wipe off dust and grit prior to priming. Seal knots, pitch streaks, and sappy sections with sealer. Fill nail holes and cracks after primer has dried; sand between coats. Back prime concealed surfaces before installation.

### **3.02 APPLICATION**

- A. Apply products in accordance with manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual".
- B. Do not apply finishes to surfaces that are not dry. Allow applied coats to dry before next coat is applied.
- C. Apply each coat to uniform appearance in thicknesses specified by manufacturer.
- D. Sand wood and metal surfaces lightly between coats to achieve required finish.
- E. Vacuum clean surfaces of loose particles. Use tack cloth to remove dust and particles just prior to applying next coat.
- F. Reinstall electrical cover plates, hardware, light fixture trim, escutcheons, and fittings removed prior to finishing.

**END OF SECTION 09 9123**

This page intentionally left blank

**SECTION 10 2113.19**  
**PLASTIC TOILET COMPARTMENTS**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Solid plastic toilet compartments.
- B. Urinal screens.

**1.02 RELATED REQUIREMENTS**

- A. Section 10 2800 - Toilet, Bath, and Laundry Accessories.

**1.03 REFERENCE STANDARDS**

- A. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- B. NFPA 286 - Standard Methods of Fire Tests for Evaluating Contribution of Wall and Ceiling Interior Finish to Room Fire Growth; 2024.

**1.04 ADMINISTRATIVE REQUIREMENTS**

- A. Coordination: Coordinate the work with placement of support framing and anchors in walls and ceilings.

**1.05 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data on panel construction, hardware, and accessories.
- C. Shop Drawings: Indicate partition plan, elevation views, dimensions, details of wall, floor, and ceiling supports, door swings.
- D. Samples: Submit two samples of partition panels, 6 by 6 inch in size illustrating panel finish, color, and sheen.

**PART 2 PRODUCTS**

**2.01 MANUFACTURERS**

- A. Solid Plastic Toilet Compartments:
- B. Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
  1. Scranton Products; Hiny Hiders Partitions: [www.scrantonproducts.com/#sle](http://www.scrantonproducts.com/#sle).
  2. Substitutions: Section 01 6000 - Product Requirements.

**2.02 PLASTIC TOILET COMPARTMENTS**

- A. Solid Plastic Toilet Compartments: Factory fabricated doors, pilasters, and divider panels made of solid molded high density polyethylene (HDPE), tested in accordance with NFPA 286; floor and ceiling anchored.
  1. Color: As selected by Architect from manufacturers full line of colors.
  2. Texture: Orange Peel
  3. Doors:
    - a. Thickness: 1 inch.
    - b. Width: 24 inch.
    - c. Width for Handicapped Use: 36 inch, out-swinging.
    - d. Height: 62 inch.
  4. Panels:
    - a. Thickness: 1 inch.
    - b. Height: 62 inch.
    - c. Depth: As indicated on drawings.
  5. Pilasters:

- a. Thickness: 1 inch.
- b. Width: As required to fit space; minimum 3 inch.
- 6. Screens: Without doors; to match compartments; mounted to wall with two panel brackets.

## **2.03 ACCESSORIES**

- A. Pilasters:
  - 1. Thickness: 1 inch.
  - 2. Width: As required to fit space; minimum 3 inch.
- B. Metal Posts: 82.75 inches high, heavy duty extruded aluminum, clear anodized finish, fastened to foot with stainless steel tamper resistant screw.
- C. Hidden Shoe (Foot): One-piece molded polyethylene invisible shoe inserted into metal post and secured to metal post with stainless steel tamper resistant screw.
- D. Wall Brackets: Stainless steel; manufacturer's standard type for conditions indicated on drawings.
- E. Attachments, Screws, and Bolts: Stainless steel, tamper proof type.
  - 1. For attaching panels and pilasters to brackets: Through-bolts and nuts; tamper proof.
- F. Hinges: Stainless steel, manufacturer's standard finish.
- G. Door Hardware: Stainless steel, manufacturer's standard finish.
  - 1. Door Latch: Slide type with exterior emergency access feature.
    - a. Occupancy Indicator
  - 2. Door Strike and Keeper with Rubber Bumper: Mount on pilaster in alignment with door latch.
  - 3. Provide door pull for outswinging doors.
- H. Coat Hook with Rubber Bumper: One per compartment, mounted on door.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify that field measurements are as instructed by the manufacturer.
- B. Verify correct spacing of and between plumbing fixtures.
- C. Verify correct location of built-in framing, anchorage, and bracing.

### **3.02 INSTALLATION**

- A. Install partitions secure, rigid, plumb, and level in accordance with manufacturer's instructions.
- B. Maintain 3/8 inch to 1/2 inch space between wall and panels and between wall and end pilasters.
  - 1. Unless smaller clearances are allowed by manufacturer.
- C. Attach panel brackets securely to walls using anchor devices.
- D. Attach panels and pilasters to brackets. Locate head rail joints at pilaster center lines.
- E. Field touch-up of scratches or damaged finish will not be permitted. Replace damaged or scratched materials with new materials.

### **3.03 TOLERANCES**

- A. Maximum Variation From True Position: 1/4 inch.
- B. Maximum Variation From Plumb: 1/8 inch.

### **3.04 ADJUSTING**

- A. Adjust and align hardware to uniform clearance at vertical edge of doors, not exceeding 3/16 inch.

- B. Adjust hinges to position doors in partial opening position when unlatched. Return out-swinging doors to closed position.
- C. Adjust adjacent components for consistency of line or plane.

**END OF SECTION 10 2113.19**

This page intentionally left blank

**SECTION 10 2800**  
**TOILET, BATH, AND LAUNDRY ACCESSORIES**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Commercial toilet accessories.
- B. Commercial shower and bath accessories.
- C. Under-lavatory pipe supply covers.
- D. Grab bars.
- E. Diaper changing stations.
- F. Utility room accessories.

**1.02 REFERENCE STANDARDS**

- A. ADA Standards - 2010 ADA Standards for Accessible Design; 2010.
- B. ASME A112.18.9 - Protectors/Insulators for Exposed Waste and Supplies on Accessible Fixtures; 2011 (Reaffirmed 2022).
- C. ASTM A269/A269M - Standard Specification for Seamless and Welded Austenitic Stainless Steel Tubing for General Service; 2025.
- D. ASTM A653/A653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process; 2023.
- E. ASTM A666/A666M - Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar; 2024.
- F. ASTM B86 - Standard Specification for Zinc and Zinc-Aluminum (ZA) Alloy Foundry and Die Castings; 2023.
- G. ASTM C1036 - Standard Specification for Flat Glass; 2021.
- H. ASTM C1048 - Standard Specification for Heat-Strengthened and Fully Tempered Flat Glass; 2018.
- I. ASTM C1503 - Standard Specification for Silvered Flat Glass Mirror; 2024.
- J. ASTM C1822 - Standard Specification for Insulating Covers on Accessible Lavatory Piping; 2021.
- K. ASTM E84 - Standard Test Method for Surface Burning Characteristics of Building Materials; 2023d.
- L. ASTM F2285 - Standard Consumer Safety Performance Specification for Diaper Changing Tables for Commercial Use; 2022.
- M. ASTM G21 - Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi; 2015, with Editorial Revision (2021).
- N. ICC A117.1 - Accessible and Usable Buildings and Facilities; 2017.

**1.03 ADMINISTRATIVE REQUIREMENTS**

- A. Coordinate the work with the placement of internal wall reinforcement, concealed ceiling supports, and reinforcement of toilet partitions to receive anchor attachments.

**1.04 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements, for submittal procedures.
- B. Product Data: Submit data on accessories describing size, finish, details of function, and attachment methods.
- C. Manufacturer's Installation Instructions: Indicate special procedures and conditions requiring special attention.

## PART 2 PRODUCTS

### 2.01 MANUFACTURERS

- A. Commercial Toilet, Shower, and Bath Accessories:
  - 1. Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but not limited to, the following.
    - a. Bradley Corporation; \_\_\_\_\_: [www.bradleycorp.com/#sle](http://www.bradleycorp.com/#sle).
    - b. Koala Kare Products: [www.koalabear.com](http://www.koalabear.com).
    - c. Bobrick: [www.bobrick.com](http://www.bobrick.com)
    - d. Substitutions: Section 01 6000 - Product Requirements.

### 2.02 MATERIALS

- A. Accessories - General: Shop assembled, free of dents and scratches and packaged complete with anchors and fittings, steel anchor plates, adapters, and anchor components for installation.
  - 1. Grind welded joints smooth.
  - 2. Fabricate units made of metal sheet of seamless sheets with flat surfaces.
- B. Keys: Provide keys for each accessory to Owner; master key lockable accessories.
- C. Stainless Steel Sheet: ASTM A666/A666M, Type 304.
- D. Stainless Steel Tubing: ASTM A269/A269M, Grade TP304 or TP316.
- E. Galvanized Sheet Steel: Hot-dipped galvanized steel sheet, ASTM A653/A653M, with G90/Z275 coating.
- F. Zinc Alloy: Die cast, ASTM B86.
- G. Mirror Glass: Annealed float glass, ASTM C1036 Type I, Class 1, Quality Q2, with silvering, protective and physical characteristics complying with ASTM C1503.
- H. Mirror Glass: Tempered safety glass, ASTM C1048; and ASTM C1036 Type I, Class 1, Quality Q2, with silvering as required.
- I. Adhesive: Two component epoxy type, waterproof.
- J. Fasteners, Screws, and Bolts: Hot dip galvanized; tamper-proof; security type.
- K. Expansion Shields: Fiber, lead, or rubber as recommended by accessory manufacturer for component and substrate.

### 2.03 FINISHES

- A. Stainless Steel: Satin finish, unless otherwise noted.
- B. Back paint components where contact is made with building finishes to prevent electrolysis.

### 2.04 COMMERCIAL TOILET ACCESSORIES

- A. As indicated in the drawings.
- B. Grab Bars: Stainless steel, smooth surface.
  - 1. Standard Duty Grab Bars:
    - a. Push/Pull Point Load: 250 pound-force, minimum.
    - b. Dimensions: 1-1/4 inch outside diameter, minimum 0.05 inch wall thickness, exposed flange mounting, 1-1/2 inch clearance between wall and inside of grab bar.
    - c. Finish: Satin.
    - d. Length and Configuration: As indicated on drawings.
    - e. Products:
      - 1) Bobrick; Grab Bars 5806 series: [www.bobrick.com](http://www.bobrick.com).
      - 2) Substitutions: Section 01 6000 - Product Requirements.
- C. Additional accessories as indicated on drawings.

### 2.05 UNDER-LAVATORY PIPE AND SUPPLY COVERS

- A. Under-Lavatory Pipe and Supply Covers:

1. Insulate exposed drainage piping, including hot, cold, and tempered water supplies under lavatories or sinks to comply with ADA Standards.
2. Exterior Surfaces: Smooth non-absorbent, non-abrasive surfaces.
3. Construction: 1/8 inch flexible PVC.
  - a. Surface Burning Characteristics: Flame spread index of 25 or less and smoke developed index of 450 or less, when tested in accordance with ASTM E84.
  - b. Comply with ASTM C1822, type indicated.
  - c. Comply with ASME A112.18.9.
  - d. Comply with ICC A117.1.
  - e. Microbial and Fungal Resistance: Comply with ASTM G21.
4. Color: White.
5. Fasteners: Reusable, snap-locking fasteners with no sharp or abrasive external surfaces.

## **2.06 DIAPER CHANGING STATIONS**

- A. Horizontal Diaper Changing Station: Wall-mounted folding diaper changing station for use in commercial toilet facilities, meeting or exceeding ASTM F2285.
  1. Material: Polyethylene.
  2. Mounting: Surface.
  3. Color: As selected.
  4. Minimum Rated Load: 250 pounds.
  5. Products:
    - a. Substitutions: 01 6000 - Product Requirements.

## **2.07 UTILITY ROOM ACCESSORIES**

- A. Mop and Broom Holder: 0.05 inch thick stainless steel, Type 304, hat-shaped channel.
  1. Holders: Three spring-loaded rubber cam holders.
  2. Length: 36 inches.
  3. Length: Manufacturer's standard length for number of holders.

## **PART 3 EXECUTION**

### **3.01 EXAMINATION**

- A. Verify existing conditions before starting work.
- B. Verify exact location of accessories for installation.
- C. Coordinate Owner furnished and installed items and locations with Owner
- D. For electrically-operated accessories, verify that electrical power connections are ready and in the correct locations.
- E. Verify that field measurements are as indicated on drawings.

### **3.02 PREPARATION**

- A. Deliver inserts and rough-in frames to site for timely installation.
- B. Provide templates and rough-in measurements as required.

### **3.03 INSTALLATION**

- A. Install accessories in accordance with manufacturers' instructions in locations indicated on drawings.
- B. Install plumb and level, securely and rigidly anchored to substrate.
- C. Mounting Heights: As required by accessibility regulations, unless otherwise indicated.
  1. Other Accessories: As indicated on drawings.

### **3.04 PROTECTION**

- A. Protect installed accessories from damage due to subsequent construction operations.

**END OF SECTION 10 2800**

This page intentionally left blank

## SECTION 32 1723 PAVEMENT MARKINGS

### **PART 1 GENERAL**

#### **1.01 SECTION INCLUDES**

- A. Painted pavement markings.

#### **1.02 REFERENCE STANDARDS**

- A. AASHTO M 247 - Standard Specification for Glass Beads Used in Pavement Markings; 2013 (Reapproved 2018).
- B. AASHTO MP 24 - Standard Specification for Waterborne White and Yellow Traffic Paints; 2015 (Reapproved 2020).

#### **1.03 SUBMITTALS**

- A. See Section 01 3000 - Administrative Requirements for submittal procedures.
- B. Shop Drawings: Indicate survey control points and pavement markings.
- C. Shop Drawings: Indicate traffic management plan with barricades, cones, and temporary markings.
- D. Product Data: Manufacturer's data sheets on each product to be used.
- E. Installer's qualification statement.

#### **1.04 QUALITY ASSURANCE**

- A. Manufacturer Qualifications: Company specializing in manufacturing products specified in this section, with not less than three years of documented experience.
- B. Installer Qualifications: Company specializing in performing work of the type specified and with at least ten years of documented experience and approved by manufacturer.

### **PART 2 PRODUCTS**

#### **2.01 MANUFACTURERS**

- A. Painted Pavement Markings:
  - 1. Dunn-Edwards Corporation; Vin-L-Stripe Specialty Interior/Exterior Flat Zone Marking Paint.
  - 2. Dunn-Edwards Corporation; Vin-L-Stripe Specialty Interior/Exterior Velvet Zone Marking Paint.
  - 3. Substitutions: See Section 01 6000 - Product Requirements.

#### **2.02 PAINTED PAVEMENT MARKINGS**

- A. Painted Pavement Markings: As indicated on drawings.
  - 1. Marking Paint: In accordance with AASHTO MP 24.
    - a. Parking Lots: White.
    - b. Symbols and Text: White.
    - c. Wheelchair Symbols: Provide blue and white.
    - d. Fire Lane: Red
  - 2. Reflective Glass Beads: Type 1, in accordance with AASHTO M 247.
  - 3. Obliterating Paint: Type I, in accordance with AASHTO MP 24.
    - a. Bituminous Pavement: Black.
    - b. Concrete Pavement: Gray.

### **PART 3 EXECUTION**

#### **3.01 EXAMINATION**

- A. Identify existing markings for removal.
- B. Verification of Conditions: Verify that pavement is dry and ready for installation.

- C. Notify Architect of unsatisfactory conditions before proceeding.

### **3.02 PREPARATION**

- A. Establish survey control points for locating and dimensioning of markings.
- B. Place barricades, warning signs, and flags as necessary to alert approaching traffic.
- C. Clean surfaces prior to installation.
  1. Remove dust, dirt, and other debris.
  2. Remove rubber deposits, existing paint markings, and other coatings.
- D. Apply paint stencils by type and color at necessary intervals.

### **3.03 INSTALLATION**

- A. General:
  1. Position pavement markings as indicated on drawings.
  2. Field location adjustments require approval of Architect.
- B. Painted Pavement Markings:
  1. Apply in accordance with manufacturer's instructions.
  2. Obliterating Paint: Apply as necessary to cover existing markings completely.
  3. Marking Paint: Apply uniformly, with sharp edges.
    - a. Applications: One coat.
    - b. Wet Film Thickness: 0.015 inch, minimum.
    - c. Stencils: Lay flat against pavement, align with striping, remove after application.
    - d. Glass Beads: Apply directly to paint, 10 second lag time, 6 lbs/gal of paint, uniform thickness and coverage.

### **3.04 TOLERANCES**

- A. Maximum Variation From True Position: 1 inch.
- B. Maximum Offset From True Alignment: 1 inch.

### **3.05 PROTECTION**

- A. Prevent approaching traffic from crossing newly applied pavement markings.
- B. Replace damaged or removed markings at no additional cost to Owner.
- C. Preserve survey control points until pavement marking acceptance.

**END OF SECTION 32 1723**