

## Spec Sheet

Cooling Liquid

Cylinders Displacement 567cc

Drive System Type On-Demand True AWD/2WD/VersaTrac Turf Mode

Engine Braking System (EBS) Not Equipped

Engine Type 4-Stroke Single Cylinder DOHC

Fuel System/Battery Electronic Fuel Injection

Horsepower 44

HP Transmission/Final Drive Automatic PVT H/L/N/R/P; Shaft

Bed Box Dimensions (L x W x H) 33.3 x 48.7 x 12.3 in

Box Capacity 500 lb (226.8 kg)

Estimated Dry Weight 1,550 lbs (703 kg)

Fuel Capacity 9.5 gal (35.9 L)

Ground Clearance 11 in (27.9 cm)

GVW 2,700 lbs

Hitch Towing Rating 1,500 lb (680 kg)

Hitch Type Standard 2 in (5 cm) Receiver

Overall Vehicle Size (L x W x H) 144 x 56 x 74 in. (365.8 x 142.2 x 188 cm)

Payload Capacity 1,100 lb (499 kg)

Person Capacity 4

Wheelbase 105 in (266.7 cm)

Front/Rear Brakes 4-Wheel Hydraulic Disc

Parking Brake Park In-Transmission

Adjustable Driver Seat Not Equipped

Cargo System Lock & Ride® Color / Graphics Ghost Gray

Electronic Power Steering Standard

Instrumentation 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter,

Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet

Lighting High/Low Beam LED Headlights LED Taillamps

Other Standard Features Gas Assist Dump Box, Single Latch Tailgate, Rear-mounted Fiberglass Insulated Exhaust System, Standard In-dash SAE Charge Port, 575 CCA Battery, 660W Charging System (Stator), 48.4 Gal. Onboard Storage with Enclosed Dash Bins and Integrated Cell-phone Holder, Sealed Suspension Bushings and Wheel Bearings, Full Coverage Steel Front Bumper with Integrated Winch and Plow Mounts, Full Coverage Skid Plate, Premium Body Panels, Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 positions), USB Charging Port, Front Stabilizer Bar, Rear Wheel Liners

RIDE COMMAND+ Available

Tilt Steering Standard

Front Tires 25 x 8-12; Carlisle 489

Rear Tires 25 x 10-12; Carlisle 489

Tire Ply Rating 4 Ply Rated

Wheels 12" Black Aluminum

Front Suspension MacPherson Strut 9 in (22.9 cm) Travel

Rear Suspension Dual A-Arm, IRS 10 in. (25.4 cm) Travel

Turning Radius 16.3 ft (497.8 cm)